

FUNCTIONAL SERVICING AND STORMWATER MANAGEMENT REPORT

FIRST SUBMISSION - OCTOBER 2024



12100 Creditview Road, Town of Caledon Proposed Commercial Development KWA PROJECT: 24045

Report Prepared for:

12100 Creditview Developments Limited
5400 Yonge St, 1st floor
Toronto, ON M2N 5R5

Report Prepared by:

KWA Site Development Consulting Inc.
2453 Auckland Drive
Burlington, Ontario
L7L 7A9





Table of Contents

1.0	Introduction	1
1.1	Project Background.....	2
1.2	Proposed development	2
1.3	Site access.....	2
1.4	Utilities.....	2
2.0	Stormwater management	4
2.1	Existing Drainage Conditions	4
2.2	Stormwater Management design criteria	6
2.3	Proposed Stormwater Outfall.....	6
2.4	Proposed Stormwater Management Design Strategy.....	8
2.5	Stormwater Quantity Control.....	8
2.6	Water balance.....	Error! Bookmark not defined.
2.7	Stormwater Quality Control.....	10
2.8	Construction Erosion and Sediment Control.....	11
2.9	Stormwater Management Summary	12
3.0	Sanitary Servicing.....	13
3.1	Existing Sanitary Servicing	13
3.2	Proposed Sanitary Servicing.....	13
3.3	Downstream Sanitary Analysis.....	13
4.0	Water Servicing	14
4.1	Existing Water Servicing.....	14
4.2	Proposed Water Servicing.....	14
4.3	Fire Hydrant Coverage.....	14
5.0	Conclusion.....	15
5.1	Recommendations:.....	16



Tables

- Table 1 – Pre-development Runoff Peak Flows
- Table 2 – Stage-Storage-Discharge for Storage Chamber
- Table 3 – Comparison of Pre-development and Post-development Peak Flows
- Table 4 – Dimensions of Infiltration Facilities

Figures

- Figure 1.1 – Location Plan
- Figure 1.2 – Proposed Development Plan
- Figure 1.1 – Existing Drainage Plan
- Figure 1.1 – Proposed Drainage Plan

Appendices

- Appendix A – Stormwater Management Calculations
- Appendix B – Sanitary Calculations
- Appendix C – Water Demand Calculations
- Appendix D – Supporting Documentation

1.0 INTRODUCTION

KWA Site Development Consulting Inc. (KWA) has been retained by 12100 Creditview Developments Limited to prepare a detailed Functional Servicing and Stormwater Management Report along with a corresponding grading and servicing design in support of the Site Plan Amendment (SPA) for the proposed development. The subject property is located at the northwest corner of Mayfield Road and Creditview Road at municipal addresses 12100 Creditview Road in the Town of Caledon, Refer to **Figure 1.1** below.

This report will:

- Provide background information regarding the subject property;
- Summarize the existing site conditions;
- Provide information regarding the proposed development conditions;
- Outline the proposed grading for the development; and
- Outline the existing and proposed municipal servicing.

The recommended servicing has been developed in accordance with the applicable design criteria and requirements of the Town of Caledon (the Town), the Region of Peel (the Region) and the Toronto Region Conservation Authority (TRCA).



Figure 1-1: Location Plan



1.1 PROJECT BACKGROUND

The total property is approximately 25.6ha in area at municipal address 12100 Creditview Road in the Town of Caledon and is currently vacant and agricultural land. The proposed commercial development (the subject site) is within the southeastern portion of the site and is approximately 14.15ha in area. The remaining lands that are not part of this application and its ultimate land uses are expected to be determined through a future Secondary Plan planning process.

The subject site is bound by Creditview Road to the northeast, Mayfield Road to the southeast, and existing vacant and agricultural land to the northwest and southwest. The site is currently occupied by an existing dwelling and farm in the north corner of the site.

The existing topography of the site has a gentle slope from west to east, towards the ditch located at Creditview and Mayfield Road with elevation differences of approximately 5.0-6.0m across the length of the site.

1.2 PROPOSED DEVELOPMENT


The proposed development of the site includes the construction of nine retail buildings with a total footprint of 27,200m². The largest retail building will be an anchor tenant (identified as Retail A) which has additional tenant specific requirements which includes additional parking and will be accommodated by two at-grade parking lots located south and west of the building. The development will also have a proposed gas station located to the southeast of Retail A. Refer to Figure 1-2 for the proposed development plan.

1.3 SITE ACCESS

The site's main vehicular accesses will be through two entrances along Creditview Road, one off Mayfield Road, and one off future road named Street A in this application. The proposed vehicular accesses to the site will require driveway culverts underneath the roadway entrances in order to maintain existing ditch flows while providing site vehicular access.

1.4 UTILITIES

As the proposed development is located within a developing area of Caledon, all utilities including telephone, cable, electricity and gas are readily available to service the subject property.



**ROBERT
PARKINSON
DR.**

MAYFIELD RD.

CREDITVIEW RD.



KWA SITE DEVELOPMENT
CONSULTING INC. 2453
AUCKLAND DRIVE
BURLINGTON, ON L7L 7A9

**PROPOSED
DEVELOPMENT**

SCALE:	1:4000
DATE:	JULY 2024
DESIGNED BY:	TF/TG
CHECKED BY:	TF/RA

PROJECT No.	24045
FIGURE No.	F1-1



2.0 STORMWATER MANAGEMENT


2.1 EXISTING DRAINAGE CONDITIONS

The existing topography of the site has a gentle slope from west to east, with low points along the site perimeter at Creditview and Mayfield along the roadway ditches. Under existing conditions, it appears that some drainage external to the proposed development site enters the site from the north. Refer to **Figure 2-1** for the Existing Drainage Area Plan, and the existing drainage area plans and design sheets for the receiving sewers in **Appendix D**.

The existing site servicing details obtained from the Region of Peel, Town of Caledon, and City of Brampton and a topographical survey completed of the area, indicate that it was envisioned that a 900mm CONC. CWP STM pipe would be installed from the corner of Creditview and Mayfield Road running southeast along Creditview Road and connect into an existing swale. However, based on the Proposed Reconstruction Plan (drawing 78524-D, dated March 21st, 2023) completed by R.V Anderson Associates Limited for the Region of Peel, a 750mm HDPE culvert is proposed to be installed from the southeast corner of the subject site, running under Mayfield Road, to connect to a proposed storm manhole at the southwest corner of Creditview and Mayfield Road. Based on the Foundation Drain Collector Drainage Plan (drawing No. C1-9-1, dated Feb, 2020), 12.29ha of the 12100 Creditview property with a runoff coefficient of 0.25 has been allocated to discharge into the proposed 750mm storm culvert.

Based on the Proposed Reconstruction Plan (drawing 78523-D, dated March 21st, 2023) completed by R.V Anderson Associates Limited for the Region of Peel, a 900mm HDPE culvert is proposed to be installed from the south side of the site across from Robert Parkinson Road, running under Mayfield Road, connecting to proposed storm manhole 16A at the southeast corner of Robert Parkinson Road and Mayfield Road. It is to be noted that the proposed invert of the 900mm DIA HDPE culvert shown on the Proposed Reconstruction Plan is proposed at an invert too high to accommodate the subject site. Subsequent discussions will be held with the Region of Peel to revise invert such that the subject site can be accommodated. Furthermore, based on the C-1-9-1 plan, 13.01ha of the 12100 Creditview property with a runoff coefficient of 0.25 has been allocated to discharge into the proposed 900mm storm culvert on Mayfield Road.

The existing sewer infrastructure is shown on the Servicing Plan (S1). Refer to **Appendix D** for more information regarding this existing storm design allocation plan. Refer to **Figure 2-1** below for the Existing Drainage Plan.



EXISTING SITE ALLOCATED DRAINAGE AREA PER URBANTECH DWG C1-9-1, SHEET 306

EXISTING DRAINAGE AREA FLOWING NORTH AND EAST

9.0ha
0.25

CATCHMENT AREA 1
TOTAL PRE-DEV DRAINAGE AREA
13.01HA

13.01ha
0.25

CATCHMENT AREA 2
TOTAL PRE-DEV DRAINAGE AREA
12.29HA

12.29ha
0.25

CONTROL 100YR POST TO PRE DEVELOPMENT FLOWS TO 900mm CWP

CONTROL 100YR POST TO PRE DEVELOPMENT FLOWS TO 600mm CWP

TOTAL EXISTING 100-YR FLOW = 654.3 L/S
900mm STORM SEWER CAPACITY = 1470 L/S

TOTAL EXISTING 100-YR FLOW = 681.1 L/S
825mm STORM SEWER CAPACITY = 1015 L/S

LEGEND

- 0.8ha
xx DRAINAGE AREA
- RUNOFF COEFFICIENT
- DRAINAGE BOUNDARY
- ➔ DRAINAGE OUTLET

File: \\lwa-d02\Comm\Projects\24045_Feldgate\24045_Existing Drainage Plan.dwg, Layout: F2-1 Date: Sep 30, 2024 - 11:15am, Edit By: Luan



KWA SITE DEVELOPMENT CONSULTING INC. 2453 AUCKLAND DRIVE BURLINGTON, ON L7L 7A9

PRE-DEVELOPMENT DRAINAGE AREA PLAN

SCALE:	1:4000
DATE:	JULY 2024
DESIGNED BY:	TF/TG
CHECKED BY:	TF/RA

PROJECT No.	24045
FIGURE No.	F2-1



2.2 STORMWATER MANAGEMENT DESIGN CRITERIA


The proposed stormwater management design is based on the MOE 2003 Stormwater Management Planning & Design (SWMPD), The Town of Caledon Development Standards Manual (2019), and The Toronto Region Conservation Authority “Stormwater Management Criteria” (August 2012).

- **Stormwater Outlet:** Stormwater drainage systems shall discharge to municipal storm sewer system where feasible. In cases where this is not possible, stormwater drainage systems may discharge to natural watercourses.
- **Quantity Control:** Post-development 100-year peak flows to the pre-development 100-year peak flow at a runoff coefficient of 0.25, as prescribed in the drainage area plan for the respective receiving sewer as per the C-1-9-1 plan.
- **Water Balance:** An annual water budget shall be prepared for the development site as described in the MOE SWMPD Manual. Infiltration facilities shall be designed to ensure that under post-development conditions, infiltration volumes match the pre-development condition.
- **Quality Control:** Stormwater quality control measures will be provided to achieve, as a minimum, the Enhanced level of protection (i.e. 80% TSS removal) as described in the MOE SWMPD manual.
- **Construction Erosion and Sediment Control:** All applicants must include an Erosion and Sediment Control plan demonstrating that fish habitat and water quality are not affected by sediment from the property during or following site construction.

2.3 PROPOSED STORMWATER OUTFALL

There will be two proposed storm connections; one outlet will be for drainage area Block A and Block B and the other for drainage area Block C and ROW. The proposed storm connection for drainage area Block A and Block will be made to the future 750mm DIA HDPE culvert that runs perpendicular to Mayfield Road, at the southeast corner of the subject site. Drainage area Block C and ROW will be controlled by a storm connection into the future 900mm HDPE culvert across from Robert Parkinson Drive. The 750mm and 900mm HDPE culverts have an allocation to receive 12.29ha and 13.01ha of drainage, respectively, from the subject property based on the drainage area plan C-1-9-1 prepared by Urbantech. To discharge to these storm sewers, the proposed development sites will be required to match the post-development 100-year storm flows at a runoff coefficient of 0.90 to the pre-development 100-year storm flows at a runoff coefficient of 0.25 of its respective drainage areas and outfalls as outlined in the drainage area plan by Urbantech.


The proposed sewer infrastructure is shown on the Servicing Plan (S1). Refer to **Appendix D** for more information regarding this existing storm design allocation plan. Refer to **Figure 2-2** below for the Proposed Drainage Plan.



LOT 19, CONCESSION 4, WEST OF HURONTARIO STREET

EXISTING DRAINAGE AREA FLOWING NORTH AND EAST

EXISTING SITE ALLOCATED DRAINAGE AREA PER URBANTECH DWG C1-9-1, SHEET 306



BLOCK A
7.27Ha
0.90

BLOCK C
2.78Ha
0.90

BLOCK B
2.45Ha
0.90

BLOCK C ALLOWABLE / EXISTING
100-YR FLOW = 139.8 L/S

BLOCK A ALLOWABLE / EXISTING
100-YR FLOW = 402 L/S

BLOCK B ALLOWABLE / EXISTING
100-YR FLOW = 136 L/S

BLOCK A/B COMBINED ALLOWABLE / EXISTING
100-YR FLOW = 538 L/S

TOTAL EXISTING 100-YR FLOW = 654.3 L/S
900mm STORM SEWER CAPACITY = 1470 L/S

CONTROL 100YR POST TO PRE DEVELOPMENT FLOWS TO 900mm HDPE CULVERT

TOTAL EXISTING 100-YR FLOW = 681.1 L/S
750mm STORM SEWER CAPACITY = 787.2 L/S

CONTROL 100YR POST TO PRE DEVELOPMENT FLOWS TO 750mm HDPE CULVERT

LEGEND

- 0.8ha
xx DRAINAGE AREA
- RUNOFF COEFFICIENT
- DRAINAGE BOUNDARY
- ➔ DRAINAGE OUTLET

ROBERT PARKINSON DR.

MAYFIELD RD.

CREDITVIEW RD.

File: \\lwa-d02\Common\Projects\24045 - PROPOSED DRAINAGE PLAN.dwg, Layout: F2-2, Date: Sep 30, 2024, 11:18am, Edit By: Luan



KWA SITE DEVELOPMENT CONSULTING INC. 2453 AUCKLAND DRIVE BURLINGTON, ON L7L 7A9

POST-DEVELOPMENT DRAINAGE AREA PLAN

SCALE:	1:4000
DATE:	JULY 2024
DESIGNED BY:	TF/TG
CHECKED BY:	TF/RA

PROJECT No.	24045
FIGURE No.	F2-2

2.4 PROPOSED STORMWATER MANAGEMENT DESIGN STRATEGY

The proposed stormwater management system will include the capture and conveyance of the entire commercial block development (14.15ha) by a series of catchbasins spread out across the site. The storm sewers will be sized to convey 100-year flow rates downstream into a stormwater storage element prior to release into its respective outfalls. An orifice will be designed at the outlet of each Cultec chamber to provide the necessary attenuation to maximize the storage volume and ultimately allow the site to release post-development flows from the site to allowable levels. Total suspended solids treatment will be achieved primarily using Stormceptor OGS units and Inlet Separator Rows from the Cultec system.

2.5 STORMWATER QUANTITY CONTROL

The proposed quantity controls are based on the drainage allocation of the subject site as defined in the as-constructed drainage area plan drawing C-1-9-1 by Urbantech as found in Appendix D. This drainage area plan identifies the receiving 750mm HDPE culvert on Creditview Road to receive 12.29ha and the 900mm HDPE culvert on Mayfield Road to receive 13.01ha for the 100-year storm event at a runoff coefficient of 0.25 from the 12100 Creditview property, most of which is made up of the commercial block development as shown in the proposed drainage area plan (Figure 2-2).

In determining the rainfall intensity for the 100-year storm event, the Airport Equation was used to calculate the time of concentration for the large drainage area (where runoff coefficients are less than 0.40), as the standard 10 minutes would not be an accurate representation of time of concentration in this scenario based on the length of the catchment and surface type.

Block A & B (East Site) – Outfall to 750mm HDPE Culvert

For existing Catchment Area #2, a time of concentration of 51.9 minutes was calculated and used to determine a rainfall intensity of 79.80mm/hr for the 100-year storm event.

In determining the allowable release rate for the subject site, the Rational Method equation was used. For existing Catchment Area #2, based on the allowable drainage area of 12.29ha, runoff coefficient of 0.25, and the 79.80mm/hr rainfall intensity, the allowable release rate was calculated to be 681.1L/s.

It is important to note that of this total 12.29ha, the subject lands allocated to this outfall is divided into two separate areas: Block A and Block B. Block A consists of a drainage area of 7.27ha (approximately 59% of the total drainage area) while Block B consists of a drainage area of 2.45ha (approximately 20% of the total drainage area). The remaining 21% of area is external to the site. The resultant allowable release rate for the subject lands is therefore estimated to be based on the area share of the subject lands to the total drainage area to this outfall, which was calculated to be 402L/s (59% of the total 681.1L/s) for Block A and 136L/S (20% of the total 681.1L/s) for Block B. Therefore, the combined/allowable 100-year release rate Block A and B is 538L/s.

It is assumed that all retail buildings will have rooftop controls, except for Retail A within Block A which has specific tenant requirements for no rooftop controls. With a post-development runoff coefficient of 0.90, it was calculated that the drainage area for Block A would require a total site storage volume of 3,249.1m³ to control the post-development release rate to the allowable 402L/s. Quantity controls will be achieved primarily using underground Cultec chambers within the parking lots, with supplementary storage provided through the controlled rooftops. Block A will be equipped with two separate underground Cultec chambers. The first (Cultec Chamber 1) underground chamber will be a Recharger 902HD system that can store 2,393.4m³ of water. The second (Cultec Chamber 2) underground chamber will be a Recharger 360HD system that can store 869m³ of water. In total, both underground chambers will store 3,262m³ of water. This will satisfy the required storage volume of 3,249.1m³ for Block A. Block A will also be equipped with a 380mm orifice just upstream from the control manhole, in order to achieve the attenuate site flows to the allowable release rate and achieve the required site storage

Block B would require a total site storage volume of 859m³ to control the post-development release rate to the allowable 136 L/s. A Recharger 902HD underground chamber (Cultec Chamber 3) will be equipped in Block B with a storage capacity of 907.6m³. Block B will also be equipped with a 240mm orifice upstream from the control manhole.

Block C (West Site) – Outfall to 900mm HDPE Culvert

For existing Catchment Area 1, a time of concentration of 59.2 minutes was calculated and used to determine a rainfall intensity of 72.42mm/hr for the 100-year storm event.

In determining the allowable release rate for the subject site, the Rational Method equation was used. For existing Catchment Area #1, based on the allowable drainage area of 13.01ha, runoff coefficient of 0.25, and the 72.42mm/hr rainfall intensity, the allowable release rate was calculated 654.3L/s.

It is important to note that of this total 13.01ha, the subject lands allocated to this outfall only makes up 2.78ha of the total 13.01ha (approximately 21% of the total drainage area). The resultant allowable release rate for the subject lands is therefore estimated to be based on the area share of the subject lands to the total drainage area to this outfall, which was calculated to be 139.81L/s (+/-21% of the total 654.3L/s).

Proposed drainage area Block C would require a total site storage volume of 923m³ to control the post-development release rate to the allowable 139.81 L/s. An underground Cultec chamber will be installed with a total storage volume of 929.2m³ provided. Block C will also be equipped with a 230mm orifice just upstream from the control manhole.

The ROW (Street) between Block C and Block A & B is not included as part of this design and will be completed by consultant TYLin.

2.6 WATER BALANCE

2.6.1 SITE CONSTRAINTS

At a minimum, it is expected that best efforts for water balance for the subject will be required. A hydrogeological investigation completed by Gemtec (dated September 30, 2024) rationalizes a rainfall retention of 12.3mm/event for the subject site in order to mitigate the annual infiltration deficit for the subject site from the pre-development scenario.

It should be noted that the subject site is also observed to have high groundwater levels throughout the course of the water level monitoring period between April 2024 and June 2024, which provides further constraint on siting infiltration galleries as a reasonable buffer from the high groundwater level to the bottom of the infiltration practice is required (typically and ideally 1.0m).

Given that the subject site is also required to match into existing surrounding grades while minimizing earthworks, raising the site to provide sufficient vertical clearances and covers are also limited.

2.6.2 INFILTRATION STRATEGY

For Block A, the developable area is 7.27ha. A volume of 894.2m³ would be required to meet the 12.3mm retention requirement. Block B, with a developable area of 2.49ha would require a volume of 306.3m³ for infiltration. Block C with a developable area of 2.78ha, would require a volume of 341.9m³ for infiltration. This totals 1542.4m³ for the total site.

As per the Hydrogeological Investigation Report completed by Gemtec, the infiltration rate for the Clayey Silt/Silty Clay Till on site is 32mm/hr. With a safety correction factor of 2.5, the design infiltration rate is taken as 12.8 mm/hr.

As discussed previously in this report, there is high groundwater elevations surrounding the site, which constrains and limits the locations and areas available for suitable infiltration of stormwater. To achieve the total water balance volume objective of 1542.4m³ for the entire site, each Block will be provided with its own infiltration chamber, and strategically placed in locations where reasonable buffer between the infiltration bottom and high groundwater levels can be met.

Block A will be served by two infiltration chambers (Gallery 1 and 2), combining for a total infiltration volume of 935.5m³. Block B will be served by two infiltration chambers (Gallery 3 and 4), combining for a total infiltration volume

of 324.7m³. Block C will be served by a single infiltration chamber (Gallery 5) for a total infiltration volume of 341.9m³. The infiltration chambers will be Cultec Contactor 100HD units with a total system depth of 775mm (inclusive of the stone bedding and backfill depths).

In order to ensure that the adequate volumes are retained, a weir wall installed at the downstream manhole of each infiltration chamber is installed with a weir elevation set to the stage elevation at which the retention volume is achieved. This ensures that only rainfall events beyond the 12.3mm event will bypass the infiltration chambers and continue conveying downstream to the storm system. Furthermore, infiltration calculations were completed to verify that the water retained within the depth in the system can be cleared within the recommended maximum allowable drawdown time of 72hours. Based on a design infiltration rate of 12.8mm/hr, a system void ratio of 40%, and the depth of the entire chamber system (the weir wall is set such that all water in the tank will be infiltrated), the calculated drawdown time for all systems is 24.2hrs, which meets the maximum drawdown requirement.

Lastly, it should also be noted that while the infiltration chambers have been sized to achieve the 12.3mm volume for the total site area, there are some drainage areas that cannot functionally drain into the infiltration chambers due to the aforementioned constraints. Therefore, the infiltration galleries have been designed to overcompensate on shortfalls from these areas that cannot be captured into the infiltration galleries. The overcompensation rainfall depth for the captured areas was calculated to be 24.7mm.

In total, between all three proposed Chambers, a total of 1608.5m³ of infiltration is provided across the subject site. For Chamber sizing, water balance and drawdown times, please refer to **Appendix A**.

2.7 STORMWATER QUALITY CONTROL

The quality control objective is to provide an enhanced protection level, which corresponds to the removal of minimum 80% TSS. Although runoff from the rooftops and landscaped areas can be considered clean, all runoff on site, including rooftops, parking lots, and drive aisles, will be treated by the separator row within the CULTEC chamber. This provides a removal of 80%. Refer to **Appendix A** for CULTEC design calculations for quality control and the ETV verification statement.

Additionally, quality control is provided via infiltration. As per the requirements in Table 3.2 of the MOE SWMPD Manual (2003), a site with an overall 85% imperviousness must infiltrate a minimum of 40 m³/ha in order to achieve an enhanced level of water quality treatment through infiltration practices. This results in a required infiltration volume of 290.8 m³ for the developed areas of Block A (7.27 ha), 99.6 m³ for the developed areas of Block B (2.49 ha), and 111.2 m³ for the developed areas of Block C (2.78 ha). This amounts to a total of 501.6 m³ of required infiltration across the entire developed site.

As stated in Section 2.8, an infiltration volume 660.4 m³ is provided within the Infiltration Chambers (1,2, and 4), exceeding the required volume for infiltration to achieve **Level 1 Enhanced TSS Removal of 80%**.

Based on the requirements of the MOE, stormwater quality is required to achieve an average of 80% long-term removal of total suspended solids based on an annual loading basis from all runoffs leaving the site.

Much of the site is rooftop or parking lot asphalt. Runoff from rooftop areas is generally considered clean water. The rest of the site, which primarily consists of pavement, has the potential to generate contaminated runoff and would require further quality treatment to achieve the 80% long-term TSS removal. An analysis was completed using the New Jersey Department of Environmental Protection (NJDEP) to determine the total TSS removal rate.

Additional stormwater quality controls will be provided through a treatment train approach using technologies holding Environmental Technology Verification (ETV). ISO 14034:2016 specifies principles, procedures and requirements for environmental technology verification (ETV) and was developed and published by the International Organization for Standardization (ISO). The objective of the ETV is to provide credible, reliable and independent verification of the performance of environmental technologies. An environmental technology is a technology that result in an

environmental added value of measures parameters that indicate an environmental impact. Such technologies have an increasingly important role in addressing environmental challenges and achieving sustainable development.

Cultec storage chambers have been proposed which typically contains an inlet row, called the Separator Row that provides for initial pretreatment and TSS removal prior to entering the main chambers. This ensures that sediment loading takes place in the first row which can be easily flushed and maintained without having to clear the entire system.

Additionally, a Stormceptor OGS unit will be provided at the storm fallout of each Block. Flows from Block A will enter a Stormceptor EF012 unit which will provide 81% TSS removal with the ability to capture and treat more than 90% of the runoff volume. Flows from Block B and C will enter a Stormceptor EF08 unit which will provide 81% and 80% TSS removal, respectively, with the ability to capture and treat more than 90% of the runoff volume. All three OGS units have been sized for a “fine” particle size distribution. Refer to **Appendix A** for Stormceptor OGS unit sizing calculations.

With the use of a Stormceptor OGS units, the total TSS removal for the subject site is over 80%. This, in combination with the Separator Row within the Cultec storage chambers, and the infiltration galleries, would meet and surpass the MOE requirement of 80% TSS removal.

2.8 CONSTRUCTION EROSION AND SEDIMENT CONTROL

Best practices are implemented to control erosion and sedimentation during construction and prior to build-out of stormwater quantity and quality control measures. All measures will be designed in accordance with the TRCA “Erosion and Sediment Control Guideline for Urban Construction” 2019, and Township of Caledon’s design criteria.

Erosion and sediment control measures during the topsoil stripping and pregrading stages of the site have been designed by TYLin (dated August 2024). As per the TYLin ESC design, the following ESC features will be established during these stages under the site alteration permit:

- Silt fencing installed around the site perimeter.
- A construction access (mud mat) is provided at the entrance off Creditview Road.
- Filling of existing headwater drainage features within the site
- A secured topsoil stockpile from the topsoil stripping is located at the west end of the site, complete with double silt fence.
- Cutoff swales to convey construction site drainage to a temporary ESC pond.
- The ESC pond is sized with a perforated vertical riser (hickenbottom) and orifice that will control the active pool to the existing 500mm CSP culvert located at the northwest corner of Creditview and Mayfield.

Following topsoil stripping and pregrading works, ESC measures during the site servicing and building construction stages will include the maintenance of all above ESC measures and as per the requirements outlined by TYLin. During servicing construction, catchbasins and other drainage structures that are capable of receiving runoff in and adjacent to the site will be equipped with a Terrafix 240R non-woven geotextile to filter out silt-laden runoff, as they are being constructed. These ESC measures should be regularly inspected and maintained to ensure they are operating as designed.

The ESC drawings and report by TYLin can be found in **Appendix D**.



2.9 STORMWATER MANAGEMENT SUMMARY

In summary the subject development will achieve or exceed all required wet weather flow management guidelines requirements. Refer to Table 2-1: Stormwater Management Summary below for a summary.

Table 2-1: Stormwater Management Summary

Existing Drainage Area ID	Catchment Area 2		Catchment Area 1	
Prop Drainage Area ID	Block C	Block A	Block B	
Outfall	900mm CWP @ Robert Parkinson/Mayfield	750mm CWP @ Mayfield/Crestview Road		
Allowable Release Rate (L/s)	139.8	538		
Orifice Diameter (mm)	230mm Plate	380mm Plate	240mm Plate	
Storage Required (m³)	923	3,249.1	859	
Storage Provided (m³)	929.2	3,262	907.6	
TSS Removal Required/Achieved	80%+	80%+	80%+	
Water Balance Volume Provided (m³)	341.9	894.2	306.3	
Water Balance Volume Provided (m³)	348.3	935.5	324.7	



3.0 SANITARY SERVICING

3.1 EXISTING SANITARY SERVICING

The existing site servicing details obtained from The Region of Peel engineering plan and profiles and a topographical survey completed of the area indicate that there is sanitary sewer infrastructure in the vicinity of the site. The following sanitary infrastructure is adjacent to the subject site;

- A 250mm sanitary sewer located within the Robert Parkinson Drive right-of-way that flows southeast.

As the existing site is greenfield, the site area is anticipated to only generate extraneous flows to nearby sanitary sewers. Based on the infiltration allowance of $0.0002\text{m}^3/\text{s}/\text{ha}$ by the Region of Peel, this amounts to an existing flow of 1.94L/s and 0.56L/s for the east (Site A+B) and west (Site C) sites, respectively.

Refer to the Servicing Drawing (S1) for the existing sanitary sewer infrastructure and proposed sanitary service design.

3.2 PROPOSED SANITARY SERVICING

A comparative analysis was undertaken to determine peak flows under the existing conditions in comparison with projected peak flows based on the proposed re-development of the site. Design flows for the proposed development has been calculated using the Region of Peel Public Works Design, Specifications & Procedures Manual.

The total peak sanitary flow for the proposed development has been calculated as 3.43L/s for the east site (Site A+B) and 1.09L/s for the west site (Site C), inclusive of the infiltration allowance. This is an estimated peak increase of 1.49L/s and 0.53L/s for the east and west sites, from the existing sanitary flow rate of 1.94L/s and 0.56L/s for the east and west sites, respectively. Refer to Appendix B for details of the calculations.

Sanitary servicing for the proposed development will consist of a 200 mm diameter connection at a 0.5% slope. The connection will be made to a future sanitary sewer in the Street A (by TYLin and not part of this application) which is to be extended from the 250mm sanitary sewer within the upstream end of the Robert Parkinson Drive right-of-way.

3.3 DOWNSTREAM SANITARY ANALYSIS

Based on the available sanitary drainage area plan for the Paradise Homes development to the south (Block 51-1 – Phase 2), the subject site was not allocated sanitary drainage to the Robert Parkinson sewer. A review of the available, as-constructed sanitary sewer design sheets however, suggest that the addition of the proposed 4.56L/s flows from the subject development would increase the most upstream sanitary sewer leg (MH52A) from 17% to 23%, and last sanitary sewer leg of the Paradise Homes development (MH59A) from 23% to 26%, which is still within an acceptable limit. Therefore, no downstream sanitary sewer impacts are anticipated from the addition of the proposed sanitary flows of the subject site, based on the currently available information.

For the sanitary drainage area plan and design sheets for the Paradise Homes development, please refer to Appendix D.



4.0 WATER SERVICING

4.1 EXISTING WATER SERVICING

The existing site servicing details obtained from The Region of Peel engineering plan and profiles and a topographical survey completed of the area, indicate that there is watermain infrastructure in the vicinity of the site. The following watermain infrastructure is adjacent to the subject site;

- A 600mm diameter watermain on the southeast side of Mayfield Road,
- A 1050mm diameter watermain on the southeast side of Mayfield Road,
- Two existing fire hydrant one at on the southeast side of Mayfield Road and one on the southwest of Mayfield road located southeast of the site.

Refer to the Servicing Drawing (S1) for the location of the existing watermain infrastructure.

4.2 PROPOSED WATER SERVICING

The proposed water service connection for the two blocks will be made to a future watermain extended from the 600mm watermain located within the Mayfield Road right-of-way and into Street A. The connection will consist of a proposed 250mm main connection with 100mm domestic watermain branched at the property line and will be installed with a detector check valve in chamber at the property line and water meters to be installed within the mechanical rooms of each retail building as per Region of Peel standard drawing 1-8-5A.

Fire protection for the proposed development will be achieved through the existing and proposed hydrants surrounding the site and through internal sprinkler systems. The internal onsite water supply and distribution system will be design and specified to comply with the current standards and specifications of the Region of Peel and the Ontario Building Code and NFPA 13.

Under proposed conditions the development is anticipated to have a fire flow demand of 167L/s for the east site and 100L/s for the west site (based on the Fire Underwriters Survey). The anticipated maximum day and peak hour domestic demands for the development under proposed conditions has been calculated as 0.53L/s and 1.40L/s for the east site and 0.18L/s and 0.40L/s for the west site. It is expected that the 600 mm diameter watermain supply within Mayfield Road will adequately provide the required flow demands for the commercial block development.

A fire hydrant flow test was completed November 15, 2021 by Bruce Fire Engineering; see Appendix C for the complete report. Based on the results from the fire hydrant test, residual pressure within the watermain system will remain above the minimum pressure required of 20.3psi, both at the public main and up to the point of delivery to each of the blocks. A watermain of 300mm from the 600mm main will be extended into the 12100 Creditview property along Street A (designed by others), with a fire and domestic water branched service to each commercial block property of 250mm and 100mm, respectively.

The water demand calculations are shown in Appendix C and the proposed and existing watermain infrastructure are shown on the Servicing Drawing (S1).

4.3 FIRE HYDRANT COVERAGE

There are fire hydrants located along Mayfield Road which provides fire hydrant coverage to the site along Mayfield. It is currently unknown if Creditview has existing or future planned watermains and fire hydrants, as engineering drawings and mapping were not available from the Town of Caledon or Region of Peel at the time of this report.



5.0 CONCLUSION

The proposed development will see the construction of a twelve-building commercial development at 12100 Creditview Road in the Town of Caledon. The proposed development can be serviced utilizing the existing and proposed infrastructure outlined in the Servicing Drawing (S1). Our conclusions and recommendations for servicing of the proposed development is summarized as follows:

Stormwater Management Servicing:

- The proposed development will match its post-development 100-year flows to the pre- development 100-year flows, as prescribed for the site by the existing drainage area plan
- The proposed development site stormwater drainage will have no adverse impact to the downstream sewer infrastructure
- Stormwater quality will be achieved by a treatment train approach, primarily through an OGS filtration unit, and supplemented with Separator Rows and inlet quality controls
- Sediment and erosion control measures to be taken during construction have been presented in this report.
- Under post-development conditions it is expected that stormwater runoff will have had an improvement in quality and quantity as compared with predevelopment condition.

Sanitary Servicing:

- The anticipated peak sanitary peak flow for the proposed development is 3.43L/s for the east site and 1.09L/s for the west site.
- The downstream sewer infrastructure designed by Urbantech did not account for the subject site, however the sewer design sheets suggests there is sufficient capacity to service the development.
- The sanitary sewer on Robert Parkinson Drive is proposed to be extended into the private driveway within the 12100 Creditview property, with a 200 sanitary service provided to the subject site

Water Servicing:

- The calculated maximum day and peak hour demands were calculated as 0.53L/s and 1.40L/s for the east site and 0.18L/s and 0.40L/s for the west site.
- The fire flow was determined based on the largest building on each site and using the Fire Underwriters Survey, calculated as 167L/s for the east site and 100L/s for the west site.
- The watermain on Mayfield Road will be branched off and extended into the private driveway within the 12100 Creditview property, with a 250mm fire and 100mm domestic branch provided to the subject site.
- Under fire flow demand loading condition, water pressure will remain above the 20.3psi and 40psi minimum requirements during the max day+fire and peak hour scenarios. These residuals are maintained both at the source (i.e. at the public main on Mayfield Road) and to the point of delivery (i.e. to the building)
- Additional confirmation of the fire and domestic branch sizing and fire flow requirements should be provided by the Mechanical Consultant at the Building Permit stage of approval.



5.1 RECOMMENDATIONS:

The following recommendations are presented:

- The contractor shall locate and verify all dimensions, levels, inverts, and datums onsite and report any discrepancies or omissions to the engineer prior to construction.

In summary, the site can be adequately serviced in respect to water supply, sanitary drainage, stormwater drainage, and stormwater management. The stormwater quantity and quality controls can be implemented in accordance to The Toronto Region Conservation Authority “Stormwater Management Criteria” (August 2012).

Accordingly, we hereby recommend the adoption of this report as it relates to the provision of servicing works, and for the purposes of site plan application, and building permit application approvals. We trust that this Functional Servicing and Stormwater Management Report is sufficient for your purposes. If you have any questions or comments, please do not hesitate to contact the undersigned.

Yours very truly,

KWA Site Development Consulting Inc.

A handwritten signature in black ink, appearing to read 'Ted Fair'.

Ted Fair, P.Eng.

ted.fair@kwasitedev.com

Theodor Gheonea, E.I.T

theo.gheonea@kwasitedev.com





APPENDIX A

STORMWATER CALCULATIONS



Stormwater Calculation Sheet - Catchment Area 1

Project: 12100 Creditview Road <i>Total Existing/Allowable Flows</i> Flows to 900 CWP on Robert Parkinson Drive	Prepared by: TF Checked by: TF Project No: 24045 Date: 9/30/2024
--	---

Runoff Equation

$Q = 2.78CIA$ (l/s)
 C = runoff coefficient
 I = rainfall intensity (mm/hr)
 A = area (ha)
 2.78= conversion factor

$I = A(T+B)^C$
 I= Rainfall Intensity (mm/hr)
 T= Time of concentration (min)

Airport Equation for T

$$T_c = \frac{3.26(1.1-C)L^{0.5}}{S^{0.33}}$$

L = 360.56 Catchment Length
 S = 0.70 Catchment Slope
 Tc = 59.2 Time of Concentration

Total Area **C**
 130100 m² 0.25

Return Period	A	B	C	T	I	Q
2 year	1070	7.9	-0.8759	59.2	26.90 mm/hr	243.0 L/s
5 year	1593	11.0	-0.8789	59.2	37.98 mm/hr	343.1 L/s
10 year	2221	12.0	-0.9080	59.2	46.19 mm/hr	417.4 L/s
25 year	3158	15.0	-0.9335	59.2	56.68 mm/hr	512.2 L/s
50 year	3886	16.0	-0.9495	59.2	64.28 mm/hr	580.8 L/s
100 year	4688	17.0	-0.9624	59.2	72.42 mm/hr	654.3 L/s

Storm Sewer Capacity:

Diameter (mm)	Slope (%)	Velocity (m/s)	Full Flow Capacity (L/s)	Actual Flow (%)
900	0.66	2.31	1470.7	44%



Stormwater Calculation Sheet - Catchment Area 1

Project: 12100 Creditview Road <i>Site Existing/Allowable Flows - Block C</i> Flows to 900 CWP on Robert Parkinson Drive	Prepared by: TF Checked by: TF Project No: 24045 Date: 9/30/2024
---	---

Runoff Equation

$Q = 2.78CIA$ (l/s)
 C = runoff coefficient
 I = rainfall intensity (mm/hr)
 A = area (ha)
 2.78= conversion factor

$I = A(T+B)^c$
 I= Rainfall Intensity (mm/hr)
 T= Time of concentration (min)

Airport Equation for T

$$T_c = \frac{3.26(1.1-C)L^{0.5}}{Sw^{0.33}}$$

Block C Site Area	C
27800 m ²	0.25

L = 360.56 Catchment Length
 S = 0.70 Catchment Slope
 Tc = 59.2 Time of Concentration

Return Period	A	B	C	T	I	Q
2 year	1070	7.9	-0.8759	59.2	26.90 mm/hr	51.9 L/s
5 year	1593	11.0	-0.8789	59.2	37.98 mm/hr	73.3 L/s
10 year	2221	12.0	-0.9080	59.2	46.19 mm/hr	89.2 L/s
25 year	3158	15.0	-0.9335	59.2	56.68 mm/hr	109.4 L/s
50 year	3886	16.0	-0.9495	59.2	64.28 mm/hr	124.1 L/s
100 year	4688	17.0	-0.9624	59.2	72.42 mm/hr	139.8 L/s

	Area (m2)	Flows (L/s)
Site	27800	139.8
Total Catchment	130100	654.3
Percentage	21.4%	21.4% Fractional Percentage of overall catchment area



Stormwater Calculation Sheet - Catchment Area 2

Project: 12100 Creditview Road <i>Total Existing/Allowable Flows</i> Flows to 750mm HDPE culvert on Creditview Road	Prepared by: TF Checked by: TF Project No: 24045 Date: 9/30/2024
--	---

Runoff Equation

$Q = 2.78CIA$ (l/s)
 C = runoff coefficient
 I = rainfall intensity (mm/hr)
 A = area (ha)
 2.78= conversion factor

$I = A(T+B)^c$
 I= Rainfall Intensity (mm/hr)
 T= Time of concentration (min)

Airport Equation for T

$$T_c = \frac{3.26(1.1-C)L^{0.5}}{S_w^{0.33}}$$

Total Area **C**
 122900 m² 0.25

L = 350.571 Catchment Length
 S = 1.00 Catchment Slope
 Tc = 51.9 Time of Concentration

Return Period	A	B	C	T	I	Q
2 year	1070	7.9	-0.8759	51.9	29.76 mm/hr	254.0 L/s
5 year	1593	11.0	-0.8789	51.9	41.83 mm/hr	357.0 L/s
10 year	2221	12.0	-0.9080	51.9	50.96 mm/hr	435.0 L/s
25 year	3158	15.0	-0.9335	51.9	62.44 mm/hr	533.0 L/s
50 year	3886	16.0	-0.9495	51.9	70.83 mm/hr	604.6 L/s
100 year	4688	17.0	-0.9624	51.9	79.80 mm/hr	681.1 L/s

Storm Sewer Capacity:

Diameter (mm)	Slope (%)	Velocity (m/s)	Full Flow Capacity (L/s)	Actual Flow (%)
600	0.5	1.54	434.2	157%
750	0.5	1.78	787.2	87%
825	0.5	1.90	1015.0	67%
900	0.5	2.01	1280.1	53%



Stormwater Calculation Sheet - Catchment Area 2

Project: 12100 Creditview Road <i>Site Existing/Allowable Flows - Block A</i> Flows to 750mm HDPE culvert on Creditview Road	Prepared by: TF Checked by: TF Project No: 24045 Date: 9/30/2024
---	---

Runoff Equation

$Q = 2.78CIA$ (l/s)
 C = runoff coefficient
 I = rainfall intensity (mm/hr)
 A = area (ha)
 2.78 = conversion factor

$$I = A(T+B)^c$$

I = Rainfall Intensity (mm/hr)
 T = Time of concentration (min)

Airport Equation for T

$$T_c = \frac{3.26(1.1-C)L^{0.5}}{S^{0.33}}$$

Block A Site Area **C**
 72700 m² 0.25

L = 350.57 Catchment Length
 S = 1.00 Catchment Slope
 T_c = 51.9 Time of Concentration

Return Period	A	B	C	T	I	Q
2 year	1070	7.9	-0.8759	51.9	29.76 mm/hr	150.2 L/s
5 year	1593	11.0	-0.8789	51.9	41.83 mm/hr	211.2 L/s
10 year	2221	12.0	-0.9080	51.9	50.96 mm/hr	257.3 L/s
25 year	3158	15.0	-0.9335	51.9	62.44 mm/hr	315.3 L/s
50 year	3886	16.0	-0.9495	51.9	70.83 mm/hr	357.6 L/s
100 year	4688	17.0	-0.9624	51.9	79.80 mm/hr	402.9 L/s

	Area (m2)	Flows (L/s)
Site	72700	402.9
Total Catchment	122900	681.1
Percentage	59.2%	59.2% Fractional Percentage of overall catchment area



Stormwater Calculation Sheet - Catchment Area 2

Project: 12100 Creditview Road <i>Site Existing/Allowable Flows - Block B</i> Flows to 750mm HDPE culvert on Creditview Road	Prepared by: TF Checked by: TF Project No: 24045 Date: 9/30/2024
---	---

Runoff Equation

$Q = 2.78CIA$ (l/s)
 C = runoff coefficient
 I = rainfall intensity (mm/hr)
 A = area (ha)
 2.78 = conversion factor

$I = A(T+B)^c$
 I = Rainfall Intensity (mm/hr)
 T = Time of concentration (min)

Airport Equation for T

$T_c = \frac{3.26(1.1-C)L^{0.5}}{S^{0.33}}$
 L = 350.57 Catchment Length
 S = 1.00 Catchment Slope
 Tc = 51.9 Time of Concentration

Block B Site Area **C**
 24500 m² 0.25

Return Period	A	B	C	T	I	Q
2 year	1070	7.9	-0.8759	51.9	29.76 mm/hr	50.6 L/s
5 year	1593	11.0	-0.8789	51.9	41.83 mm/hr	71.2 L/s
10 year	2221	12.0	-0.9080	51.9	50.96 mm/hr	86.7 L/s
25 year	3158	15.0	-0.9335	51.9	62.44 mm/hr	106.2 L/s
50 year	3886	16.0	-0.9495	51.9	70.83 mm/hr	120.5 L/s
100 year	4688	17.0	-0.9624	51.9	79.80 mm/hr	135.8 L/s

Combined a/b 100-yr flows **538.7** L/s

	Area (m2)	Flows (L/s)
Site	24500	135.8
Total Catchment	122900	681.1
Percentage	19.9%	19.9% Fractional Percentage of overall catchment area



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

BLOCK C ALLOWABLE RELEASE FLOW

1. Pre, External & Post Development Uncontrolled Area:

Note: Post Dev. Controlled Area is shown in Orifice Calculations

Table 1. a) Total Uncontrolled Area

Type of Land	T (min)	Runoff Coef. (C)	Uncontrolled Area (m ²)			
			Pre Dev. Site (A)	Pre Dev. Incoming External (A)	Total Pre Dev. (A)	Post Dev. Uncontrolled (A)
Total Unrestricted Area			72700	-	72700	-
Combined T (min)					51.9	-
Combined Runoff Coefficient			0.25	-	0.25	-
Landscape	51.9	0.25	72700	0	72700	0
Impervious	51.9	0.90	0	0	0	0
Gravel	51.9	0.75	0	0	0	0

2. Formulas, Coefficients & Average Rainfall Intensity:

$i = a(T+b)^{-c}$, where i (mm/h) ; T (min)

$Q = A(i)C/3600$, where A (m²) ; i (mm/h)

Note: a,b,c = coefficients as per municipal standards

Description Units	Return Period (years)					
	2	5	10	25	50	100
a	1070	1593	2221	3158	3886	4688
b	7.85	11	12	15	16	17
c	0.8759	0.8789	0.908	0.9335	0.9495	0.9624
Total Unrestricted Area i (mm/h)	29.75	41.82	50.95	62.43	70.82	79.78
Total Allotment Area i (mm/h)	94.76	109.28	131.69	146.72	163.51	180.66

3. Pre Development Flow:

Description Units	Return Period (years)					
	2	5	10	25	50	100
Total Unrestricted Area Q (L/s)	150.20	211.13	257.23	315.17	357.53	402.77

Summary: The Pre Development Flow is Q2=150.2L/s, Q5=211.1L/s, Q10=257.2L/s, Q25=315.2L/s, Q50=357.5L/s, Q100=402.8L/s.

4. Post Development Uncontrolled Flow:

Description Units	Return Period (years)					
	2	5	10	25	50	100
Total Unrestricted Area Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Restricted Flat Roof (42L/s/ha) Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Restricted Green Roof (42L/s/ha) Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Cumulative Flow Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00

Summary: The Post Development Uncontrolled Flow is Q2=0L/s, Q5=0L/s, Q10=0L/s, Q25=0L/s, Q50=0L/s, Q100=0L/s.

5. Allowable Flow:

Description Units	Return Period (years)					
	2	5	10	25	50	100
Pre Development Flow Q (L/s)	150.20	211.13	257.23	315.17	357.53	402.77
Allowable Release Flow Q (L/s)	150.20	211.13	257.23	315.17	357.53	402.77
Post Development Uncontrolled Flow Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Uncontrolled Release Flow Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Remaining Release Flow for Orifice Q (L/s)	150.20	211.13	257.23	315.17	357.53	402.77

100-Year Pre-Dev allowable flow = **402.8 L/s**



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

BLOCK C - ORIFICE CALCULATIONS - POST DEV. CONTROLLED FLOWS

6. Summary Table of Allowable Flow:

Description	Units	Return Period (years)					
		2	5	10	25	50	100
Allowable Release Flow	Q (L/s)	150.20	211.13	257.23	315.17	357.53	402.77
Uncontrolled Release Flow	Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Remaining Release Flow for Orifice	Q (L/s)	150.20	211.13	257.23	315.17	357.53	402.77

Summary: The remaining release flow for the orifice is Q100=402.8L/s.

7. Total Post Development Area:

Types of Land	T (min)	Runoff Coef. (C)	Area (m ²)			TSS Removal Rate without treatment	TSS Removal Rate with Oil Grit Separator
			Post Dev. Uncontrolled (A)	Post Dev. Controlled (A)	Total Post Dev. (A)		
Total Area			-	72700	72700		
Combined T (min)			-	51.9	51.9		
Combined Runoff Coefficient			-	0.9	0.9		
Total Area (Unrestricted)			-	72700	72700		
Combined T (min) (Unrestricted)			-	51.9	51.9		
Combined Runoff Coefficient (Unrestricted)			-	0.9	0.9		
Landscape	51.9	0.25	0	0	0	100%	100%
Impervious	51.9	0.9	0	72700	72700	0%	80%
Restricted Flat Roof (42L/s/ha)	51.9	0.9	0	0	0	90%	98%
Total						0%	80%

Note: Max. treatment inflow = 3573L/s.

Summary: The maximum storage facility inflow (Q) = 3573L/s.

Summary: The TSS removal rate without treatment < 80%, therefore an Oil Grit Separator is required to be constructed upstream of the storage facility to provide a TSS removal rate of 80%.

8. Orifice Design:

Orifice Details:	
Post Development Return Period to be Controlled	= 100 year
Pre Development Return Period to Control to	= 100 year
Orifice Discharge Coefficient (C)	= 0.62 Plate
Orifice Inside Diameter	= 390 mm
Orifice Area	= 0.119 m ²
High Water Head from invert (h)	= 1.5 m
Allowable Orifice Flow (Q)	= 402.77 L/s
Actual Orifice Flow (Q)	= CA(2gh) ^{1/2}
	= 401.59 L/s

Summary: The Orifice is a Plate with an Inside Diameter of 390mm.

Summary: The Actual Orifice Flow is Q100=401.6L/s.



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

BLOCK C - ORIFICE CALCULATIONS - POST DEV. CONTROLLED FLOWS

9. Storage Facility Design:

Storage Facility	=	Cultec System
Storage Volume Required (V _r)	=	3249.1 m ³ (Storage Calc's)
<u>Cultec System Elevations:</u>		
Surface Elevation	=	263.78 m
Top of Cultec System Elevation	=	263.41 m
High Water Level (HWL)	=	263.41 m
Orifice Invert Elevation	=	261.91 m
Bottom of Cultec System Elevation	=	261.91 m
Effective Cultec System Depth (h ₂)	=	1.5 m

Cultec System Details:

Freeboard Height	=	0 m
High Water Head from invert (h)	=	1.5 m

Cultec System Volume:

Quantity Storage Volume Provided	=	3262.1 m ³
Retention Volume Provided	=	369.8 m ³
Total Cultec System Volume	=	3631.9 m ³

Storm Service Connection:

Diameter (mm)	Slope (%)	Velocity (m/s)	Full Flow Capacity (L/s)	Actual Flow (%)
450	0.3	0.98	156.2	257%
525	0.3	1.09	235.6	170%
600	0.3	1.19	336.3	119%
675	0.3	1.29	460.4	87%

Total Unrestricted Area	A =	72700 m ²
Storm Event to be Captured	E =	5 mm

Total Retained Volume	=	363.5 m ³
Total Volume for Chamber	=	363.5 m ³



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

STORAGE CALCULATIONS

10. Storage Calculations

Note: Restricted Flat Roof & Restricted Green Roof are controlled to 42L/s/ha.

Controlling the 100 Year Post Development Flow to the 100 Year Pre Development Flow.

$i = a[(T+b)/60]^c$, where i (mm/h) ; T (min)
 $Q = A(i)C/3600$, where A (m²) ; i (mm/h)
 $a = 4688$
 $b = 17$
 $c = 0.9624$

i = average rainfall intensity (mm/h)
 a, b, c = coefficients as per municipal standards
 T = time of concentration (min)
 Q = flow (m³/s)
 A = area (m²)
 C = runoff coefficient

	Total Site	Cultec System	Restricted Flat Roof	Restricted Green Roof
Area (m ²)	72700	72700	-	-
Runoff Coef.	0.90	0.90	-	-
Q _{controlled} (m ³ /s)	0.40277	0.40159	-	-

Note: 'Cultec System' Inflow calculation = 100 year flow + 'restricted flat roof' flow (0m³/s) + 'Green Roof' flow (0m³/s)
 Note: Max. 'Cultec System' Inflow = 3.573m³/s

Time (min)	i (mm/h)	Total Site Storage			Cultec System Storage			Restricted Flat Roof Storage			Restricted Green Roof Storage			
		Inflow, Q (m ³ /s)	Flow Stored, Q (m ³ /s)	Req. Storage, V (m ³)	Inflow, Q ₁ (m ³ /s)	Flow Stored, Q ₁ (m ³ /s)	Req. Storage, V ₁ (m ³)	Inflow, Q ₂ (m ³ /s)	Flow Stored, Q ₂ (m ³ /s)	Req. Storage, V ₂ (m ³)	Inflow, Q ₃ (m ³ /s)	Flow Stored, Q ₃ (m ³ /s)	Req. Storage, V ₃ (m ³)	
Maximum	-	-	-	3246.0	3.573	-	3249.1	-	-	-	0.0	-	-	0.0
10	196.54	3.572	3.169	1901.568	3.572	3.170	1902.276	0.000	0.000	0.000	0.000	0.000	0.000	0.000
11	189.78	3.449	3.046	2010.637	3.449	3.048	2011.416	0.000	0.000	0.000	0.000	0.000	0.000	0.000
12	183.47	3.335	2.932	2110.953	3.335	2.933	2111.803	0.000	0.000	0.000	0.000	0.000	0.000	0.000
13	177.58	3.228	2.825	2203.372	3.228	2.826	2204.293	0.000	0.000	0.000	0.000	0.000	0.000	0.000
14	172.07	3.127	2.725	2288.641	3.127	2.726	2289.633	0.000	0.000	0.000	0.000	0.000	0.000	0.000
15	166.89	3.033	2.630	2367.416	3.033	2.632	2368.478	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20	145.13	2.638	2.235	2681.911	2.638	2.236	2683.327	0.000	0.000	0.000	0.000	0.000	0.000	0.000
25	128.46	2.335	1.932	2898.023	2.335	1.933	2899.793	0.000	0.000	0.000	0.000	0.000	0.000	0.000
30	115.28	2.095	1.692	3046.457	2.095	1.694	3048.581	0.000	0.000	0.000	0.000	0.000	0.000	0.000
35	104.59	1.901	1.498	3146.267	1.901	1.499	3148.745	0.000	0.000	0.000	0.000	0.000	0.000	0.000
40	95.75	1.740	1.337	3209.918	1.740	1.339	3212.750	0.000	0.000	0.000	0.000	0.000	0.000	0.000
45	88.31	1.605	1.202	3245.913	1.605	1.203	3249.099	0.000	0.000	0.000	0.000	0.000	0.000	0.000
60	71.69	1.303	0.900	3240.384	1.303	0.901	3244.632	0.000	0.000	0.000	0.000	0.000	0.000	0.000
70	63.74	1.158	0.756	3173.760	1.158	0.757	3178.716	0.000	0.000	0.000	0.000	0.000	0.000	0.000
80	57.40	1.043	0.640	3074.356	1.043	0.642	3080.020	0.000	0.000	0.000	0.000	0.000	0.000	0.000
90	52.23	0.949	0.546	2951.021	0.949	0.548	2957.393	0.000	0.000	0.000	0.000	0.000	0.000	0.000
120	41.17	0.748	0.346	2487.895	0.748	0.347	2496.391	0.000	0.000	0.000	0.000	0.000	0.000	0.000
150	34.03	0.618	0.216	1941.313	0.618	0.217	1951.933	0.000	0.000	0.000	0.000	0.000	0.000	0.000
180	29.03	0.528	0.125	1347.678	0.528	0.126	1360.422	0.000	0.000	0.000	0.000	0.000	0.000	0.000

SWM Measure	Value
Allowable Release Rate	402.77 L/s
Uncontrolled Release Flow (Q)	0 L/s
Actual Orifice Flow	401.59 L/s
Orifice Size	390 mm
Total Quantity Storage Required	3246.0 m ³
Rooftop Storage Provided	0.0 m ³
Underground Quantity Storage Provided	3262.113848 m ³
Total Quantity Storage Provided	3262.1 m ³
TSS Removal Rate without treatment	0%
TSS Removal with treatment (Max. Inflow = 3573L/s)	80%
Water Balance Volume Required	363.5 m ³
Total Chamber Volume	3625.613848 m ³



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

BLOCK B ALLOWABLE RELEASE FLOW

1. Pre, External & Post Development Uncontrolled Area:

Note: Post Dev. Controlled Area is shown in Orifice Calculations

Table 1. a) Total Uncontrolled Area

Type of Land	T (min)	Runoff Coef. (C)	Uncontrolled Area (m ²)			
			Pre Dev. Site (A)	Pre Dev. Incoming External (A)	Total Pre Dev. (A)	Post Dev. Uncontrolled (A)
Total Unrestricted Area			24900	-	24900	-
Combined T (min)					51.9	-
Combined Runoff Coefficient			0.25	-	0.25	-
Landscape	51.9	0.25	24900	0	24900	0
Impervious	51.9	0.90	0	0	0	0
Gravel	51.9	0.75	0	0	0	0

2. Formulas, Coefficients & Average Rainfall Intensity:

$i = a(T+b)^{-c}$, where i (mm/h) ; T (min)

$Q = A(i)C/3600$, where A (m²) ; i (mm/h)

Note: a,b,c = coefficients as per municipal standards

Description Units	Return Period (years)					
	2	5	10	25	50	100
a	1070	1593	2221	3158	3886	4688
b	7.85	11	12	15	16	17
c	0.8759	0.8789	0.908	0.9335	0.9495	0.9624
Total Unrestricted Area i (mm/h)	29.75	41.82	50.95	62.43	70.82	79.78
Total Allotment Area i (mm/h)	94.76	109.28	131.69	146.72	163.51	180.66

3. Pre Development Flow:

Description Units	Return Period (years)					
	2	5	10	25	50	100
Total Unrestricted Area Q (L/s)	51.44	72.31	88.10	107.95	122.46	137.95

Summary: The Pre Development Flow is Q2=51.4L/s, Q5=72.3L/s, Q10=88.1L/s, Q25=107.9L/s, Q50=122.5L/s, Q100=138L/s.

4. Post Development Uncontrolled Flow:

Description Units	Return Period (years)					
	2	5	10	25	50	100
Total Unrestricted Area Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Restricted Flat Roof (42L/s/ha) Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Restricted Green Roof (42L/s/ha) Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Cumulative Flow Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00

Summary: The Post Development Uncontrolled Flow is Q2=0L/s, Q5=0L/s, Q10=0L/s, Q25=0L/s, Q50=0L/s, Q100=0L/s.

5. Allowable Flow:

Description Units	Return Period (years)					
	2	5	10	25	50	100
Pre Development Flow Q (L/s)	51.44	72.31	88.10	107.95	122.46	137.95
Allowable Release Flow Q (L/s)	51.44	72.31	88.10	107.95	122.46	137.95
Post Development Uncontrolled Flow Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Uncontrolled Release Flow Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Remaining Release Flow for Orifice Q (L/s)	51.44	72.31	88.10	107.95	122.46	137.95

100-Year Pre-Dev allowable flow = **138.0 L/s**



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

BLOCK B - ORIFICE CALCULATIONS - POST DEV. CONTROLLED FLOWS

6. Summary Table of Allowable Flow:

Description	Units	Return Period (years)					
		2	5	10	25	50	100
Allowable Release Flow	Q (L/s)	51.44	72.31	88.10	107.95	122.46	137.95
Uncontrolled Release Flow	Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Remaining Release Flow for Orifice	Q (L/s)	51.44	72.31	88.10	107.95	122.46	137.95

Summary: The remaining release flow for the orifice is Q100=138L/s.

7. Total Post Development Area:

Types of Land	T (min)	Runoff Coef. (C)	Area (m ²)			TSS Removal Rate without treatment	TSS Removal Rate with Oil Grit Separator
			Post Dev. Uncontrolled (A)	Post Dev. Controlled (A)	Total Post Dev. (A)		
Total Area			-	24900	24900		
Combined T (min)			-	51.9	51.9		
Combined Runoff Coefficient			-	0.9	0.9		
Total Area (Unrestricted)			-	19078	19078		
Combined T (min) (Unrestricted)			-	51.9	51.9		
Combined Runoff Coefficient (Unrestricted)			-	0.9	0.9		
Landscape	51.9	0.25	0	0	0	100%	100%
Impervious	51.9	0.9	0	19078	19078	0%	80%
Restricted Flat Roof (42L/s/ha)	51.9	0.9	0	5822	5822	90%	98%
Total						21%	84%

Note: Max. treatment inflow = 962L/s.

Summary: The maximum storage facility inflow (Q) = 962L/s.

Summary: The TSS removal rate without treatment < 80%, therefore an Oil Grit Separator is required to be constructed upstream of the storage facility to provide a TSS removal rate of 84%.

8. Orifice Design:

Orifice Details:	
Post Development Return Period to be Controlled	= 100 year
Pre Development Return Period to Control to	= 100 year
Orifice Discharge Coefficient (C)	= 0.62 Plate
Orifice Inside Diameter	= 220 mm
Orifice Area	= 0.038 m ²
High Water Head from invert (h)	= 1.5 m
Allowable Orifice Flow (Q)	= 137.95 L/s
Actual Orifice Flow (Q)	= CA(2gh) ^{1/2}
	= 127.79 L/s

Summary: The Orifice is a Plate with an Inside Diameter of 220mm.

Summary: The Actual Orifice Flow is Q100=127.8L/s.



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

BLOCK B - ORIFICE CALCULATIONS - POST DEV. CONTROLLED FLOWS

9. Storage Facility Design:

Storage Facility	=	Cultec System
Storage Volume Required (V _r)	=	858.9 m ³ (Storage Calc's)
<u>Cultec System Elevations:</u>		
Surface Elevation	=	264.6 m
Top of Cultec System Elevation	=	264 m
High Water Level (HWL)	=	264 m
Orifice Invert Elevation	=	262.5 m
Bottom of Cultec System Elevation	=	262.5 m
Effective Cultec System Depth (h ₂)	=	1.5 m

Cultec System Details:

Freeboard Height	=	0 m
High Water Head from invert (h)	=	1.5 m

Cultec System Volume:

Quantity Storage Volume Provided	=	907.6 m ³
Retention Volume Provided	=	139.8 m ³

Total Cultec System Volume = **1047.4** m³

Storm Service Connection:

Diameter (mm)	Slope (%)	Velocity (m/s)	Full Flow Capacity (L/s)	Actual Flow (%)
450	0.3	0.98	156.2	82%
525	0.3	1.09	235.6	54%
600	0.3	1.19	336.3	38%
750	0.3	1.38	609.8	21%

Total Unrestricted Area	A =	24900 m ²
Storm Event to be Captured	E =	5 mm

Total Retained Volume	=	124.5 m ³
Total Volume for Chamber	=	124.5 m ³



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

STORAGE CALCULATIONS

10. Storage Calculations

Note: Restricted Flat Roof & Restricted Green Roof are controlled to 42L/s/ha.

Controlling the 100 Year Post Development Flow to the 100 Year Pre Development Flow.

$i = a[(T+b)/60]^c$, where i (mm/h) ; T (min)
 $Q = A(i)C/3600$, where A (m²) ; i (mm/h)
 $a = 4688$
 $b = 17$
 $c = 0.9624$

i = average rainfall intensity (mm/h)
 a, b, c = coefficients as per municipal standards
 T = time of concentration (min)
 Q = flow (m³/s)
 A = area (m²)
 C = runoff coefficient

	Total Site	Cultec System	Restricted Flat Roof	Restricted Green Roof
Area (m ²)	24900	19078	5822	-
Runoff Coef.	0.90	0.90	0.90	-
Q _{controlled} (m ³ /s)	0.13795	0.12779	0.0244524	-

Note: 'Cultec System' Inflow calculation = 100 year flow + 'restricted flat roof' flow (0.0245m³/s) + 'Green Roof' flow (0m³/s).
 Note: Max. 'Cultec System' Inflow = 0.962m³/s

Time (min)	i (mm/h)	Total Site Storage			Cultec System Storage			Restricted Flat Roof Storage			Restricted Green Roof Storage			
		Inflow, Q (m ³ /s)	Flow Stored, Q (m ³ /s)	Req. Storage, V (m ³)	Inflow, Q ₁ (m ³ /s)	Flow Stored, Q ₁ (m ³ /s)	Req. Storage, V ₁ (m ³)	Inflow, Q ₂ (m ³ /s)	Flow Stored, Q ₂ (m ³ /s)	Req. Storage, V ₂ (m ³)	Inflow, Q ₃ (m ³ /s)	Flow Stored, Q ₃ (m ³ /s)	Req. Storage, V ₃ (m ³)	
Maximum	-	-	-	1111.8	0.962	-	858.9	-	-	-	287.6	-	-	0.0
10	196.54	1.223	1.085	651.294	0.962	0.834	500.426	0.286	0.262	156.964	0.000	0.000	0.000	0.000
11	189.78	1.181	1.043	688.650	0.930	0.802	529.189	0.276	0.252	166.167	0.000	0.000	0.000	0.000
12	183.47	1.142	1.004	723.009	0.900	0.772	555.656	0.267	0.243	174.668	0.000	0.000	0.000	0.000
13	177.58	1.105	0.968	754.663	0.871	0.744	580.050	0.258	0.234	182.538	0.000	0.000	0.000	0.000
14	172.07	1.071	0.933	783.868	0.845	0.717	602.568	0.250	0.226	189.834	0.000	0.000	0.000	0.000
15	166.89	1.039	0.901	810.848	0.820	0.693	623.381	0.243	0.218	196.611	0.000	0.000	0.000	0.000
20	145.13	0.903	0.765	918.564	0.717	0.589	706.619	0.211	0.187	224.137	0.000	0.000	0.000	0.000
25	128.46	0.800	0.662	992.583	0.637	0.509	764.038	0.187	0.163	243.785	0.000	0.000	0.000	0.000
30	115.28	0.718	0.580	1043.422	0.574	0.446	803.698	0.168	0.143	258.012	0.000	0.000	0.000	0.000
35	104.59	0.651	0.513	1077.608	0.523	0.396	830.597	0.152	0.128	268.346	0.000	0.000	0.000	0.000
40	95.75	0.596	0.458	1099.408	0.481	0.353	848.008	0.139	0.115	275.784	0.000	0.000	0.000	0.000
45	88.31	0.550	0.412	1111.737	0.446	0.318	858.161	0.129	0.104	281.008	0.000	0.000	0.000	0.000
60	71.69	0.446	0.308	1109.843	0.366	0.239	858.832	0.104	0.080	287.587	0.000	0.000	0.000	0.000
70	63.74	0.397	0.259	1087.024	0.328	0.201	842.763	0.093	0.068	286.933	0.000	0.000	0.000	0.000
80	57.40	0.357	0.219	1052.978	0.298	0.170	818.092	0.084	0.059	283.654	0.000	0.000	0.000	0.000
90	52.23	0.325	0.187	1010.735	0.274	0.146	787.141	0.076	0.052	278.458	0.000	0.000	0.000	0.000
120	41.17	0.256	0.118	852.114	0.221	0.093	669.851	0.060	0.035	255.415	0.000	0.000	0.000	0.000
150	34.03	0.212	0.074	664.908	0.187	0.059	530.660	0.050	0.025	225.687	0.000	0.000	0.000	0.000
180	29.03	0.181	0.043	461.585	0.163	0.035	379.122	0.042	0.018	192.192	0.000	0.000	0.000	0.000

SWM Measure	Value
Allowable Release Rate	137.95 L/s
Uncontrolled Release Flow (Q)	0 L/s
Actual Orifice Flow	127.79 L/s
Orifice Size	220 mm
Total Quantity Storage Required	1111.8 m ³
Rooftop Storage Provided	287.6 m ³
Underground Quantity Storage Provided	907.6349169 m ³
Total Quantity Storage Provided	1195.2 m ³
TSS Removal Rate without treatment	21%
TSS Removal with treatment (Max. Inflow = 962L/s)	84%
Water Balance Volume Required	124.5 m ³
Total Chamber Volume	1032.134917 m ³



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

BLOCK C ALLOWABLE RELEASE FLOW

1. Pre, External & Post Development Uncontrolled Area:

Note: Post Dev. Controlled Area is shown in Orifice Calculations

Table 1. a) Total Uncontrolled Area

Type of Land	T (min)	Runoff Coef. (C)	Uncontrolled Area (m ²)			
			Pre Dev. Site (A)	Pre Dev. Incoming External (A)	Total Pre Dev. (A)	Post Dev. Uncontrolled (A)
Total Unrestricted Area			27800	-	27800	-
Combined T (min)					59.2	-
Combined Runoff Coefficient			0.25	-	0.25	-
Landscape	59.2	0.25	27800	0	27800	0
Impervious	59.2	0.90	0	0	0	0
Gravel	59.2	0.75	0	0	0	0

2. Formulas, Coefficients & Average Rainfall Intensity:

$i = a(T+b)^{-c}$, where i (mm/h) ; T (min)

$Q = A(i)C/3600$, where A (m²) ; i (mm/h)

Note: a,b,c = coefficients as per municipal standards

Description Units	Return Period (years)					
	2	5	10	25	50	100
a	1070	1593	2221	3158	3886	4688
b	7.85	11	12	15	16	17
c	0.8759	0.8789	0.908	0.9335	0.9495	0.9624
Total Unrestricted Area i (mm/h)	26.89	37.97	46.18	56.67	64.27	72.41
Total Allotment Area i (mm/h)	93.17	107.15	129.05	143.52	159.88	176.57

3. Pre Development Flow:

Description Units	Return Period (years)					
	2	5	10	25	50	100
Total Unrestricted Area Q (L/s)	51.92	73.31	89.16	109.41	124.08	139.79

Summary: The Pre Development Flow is Q2=51.9L/s, Q5=73.3L/s, Q10=89.2L/s, Q25=109.4L/s, Q50=124.1L/s, Q100=139.8L/s.

4. Post Development Uncontrolled Flow:

Description Units	Return Period (years)					
	2	5	10	25	50	100
Total Unrestricted Area Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Restricted Flat Roof (42L/s/ha) Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Restricted Green Roof (42L/s/ha) Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Cumulative Flow Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00

Summary: The Post Development Uncontrolled Flow is Q2=0L/s, Q5=0L/s, Q10=0L/s, Q25=0L/s, Q50=0L/s, Q100=0L/s.

5. Allowable Flow:

Description Units	Return Period (years)					
	2	5	10	25	50	100
Pre Development Flow Q (L/s)	51.92	73.31	89.16	109.41	124.08	139.79
Allowable Release Flow Q (L/s)	51.92	73.31	89.16	109.41	124.08	139.79
Post Development Uncontrolled Flow Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Uncontrolled Release Flow Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Remaining Release Flow for Orifice Q (L/s)	51.92	73.31	89.16	109.41	124.08	139.79

100-Year Pre-Dev allowable flow = **139.8 L/s**



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

BLOCK C - ORIFICE CALCULATIONS - POST DEV. CONTROLLED FLOWS

6. Summary Table of Allowable Flow:

Description	Units	Return Period (years)					
		2	5	10	25	50	100
Allowable Release Flow	Q (L/s)	51.92	73.31	89.16	109.41	124.08	139.79
Uncontrolled Release Flow	Q (L/s)	0.00	0.00	0.00	0.00	0.00	0.00
Remaining Release Flow for Orifice	Q (L/s)	51.92	73.31	89.16	109.41	124.08	139.79

Summary: The remaining release flow for the orifice is Q100=139.8L/s.

7. Total Post Development Area:

Types of Land	T (min)	Runoff Coef. (C)	Area (m ²)			TSS Removal Rate without treatment	TSS Removal Rate with Oil Grit Separator
			Post Dev. Uncontrolled (A)	Post Dev. Controlled (A)	Total Post Dev. (A)		
Total Area			-	27800	27800		
Combined T (min)			-	59.2	59.2		
Combined Runoff Coefficient			-	0.9	0.9		
Total Area (Unrestricted)			-	20359	20359		
Combined T (min) (Unrestricted)			-	59.2	59.2		
Combined Runoff Coefficient (Unrestricted)			-	0.9	0.9		
Landscape	59.2	0.25	0	0	0	100%	100%
Impervious	59.2	0.9	0	20359	20359	0%	80%
Restricted Flat Roof (42L/s/ha)	59.2	0.9	0	7441	7441	90%	98%
Total						24%	85%

Note: Max. treatment inflow = 1032L/s.

Summary: The maximum storage facility inflow (Q) = 1032L/s.

Summary: The TSS removal rate without treatment < 80%, therefore an Oil Grit Separator is required to be constructed upstream of the storage facility to provide a TSS removal rate of 85%.

8. Orifice Design:

<u>Orifice Details:</u>	
Post Development Return Period to be Controlled	= 100 year
Pre Development Return Period to Control to	= 100 year
Orifice Discharge Coefficient (C)	= 0.62 Plate
Orifice Inside Diameter	= 230 mm
Orifice Area	= 0.042 m ²
High Water Head from invert (h)	= 1.5 m
Allowable Orifice Flow (Q)	= 139.79 L/s
Actual Orifice Flow (Q)	= CA(2gh) ^{1/2}
	= 139.67 L/s

Summary: The Orifice is a Plate with an Inside Diameter of 230mm.

Summary: The Actual Orifice Flow is Q100=139.7L/s.



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

BLOCK C - ORIFICE CALCULATIONS - POST DEV. CONTROLLED FLOWS

9. Storage Facility Design:

Storage Facility	=	Cultec System
Storage Volume Required (V _r)	=	923.2 m ³ (Storage Calc's)
<u>Cultec System Elevations:</u>		
Surface Elevation	=	264.6 m
Top of Cultec System Elevation	=	264 m
High Water Level (HWL)	=	264 m
Orifice Invert Elevation	=	262.5 m
Bottom of Cultec System Elevation	=	262.5 m
Effective Cultec System Depth (h ₂)	=	1.5 m

Cultec System Details:

Freeboard Height	=	0 m
High Water Head from invert (h)	=	1.5 m

Cultec System Volume:

Quantity Storage Volume Provided	=	929.2 m ³
Retention Volume Provided	=	150.8 m ³

Total Cultec System Volume = 1080.1 m³

Storm Service Connection:

Diameter (mm)	Slope (%)	Velocity (m/s)	Full Flow Capacity (L/s)	Actual Flow (%)
450	0.3	0.98	156.2	89%
525	0.3	1.09	235.6	59%
600	0.3	1.19	336.3	42%
675	0.3	1.29	460.4	30%
750	0.3	1.38	609.8	23%

Total Unrestricted Area	A =	27800 m ²
Storm Event to be Captured	E =	5 mm

Total Retained Volume	=	139.0 m ³
Total Volume for Chamber	=	139.0 m ³



Project Name: 12100 Creditview Road	
Project #: 24045	Prepared by: TG/TF
Date: 9/30/2024	Checked by: TF

STORAGE CALCULATIONS

10. Storage Calculations

Note: Restricted Flat Roof & Restricted Green Roof are controlled to 42L/s/ha.

Controlling the 100 Year Post Development Flow to the 100 Year Pre Development Flow.

$i = a[(T+b)/60]^c$, where i (mm/h) ; T (min)
 $Q = A(i)C/3600$, where A (m²) ; i (mm/h)
 $a = 4688$
 $b = 17$
 $c = 0.9624$

i = average rainfall intensity (mm/h)
 a, b, c = coefficients as per municipal standards
 T = time of concentration (min)
 Q = flow (m³/s)
 A = area (m²)
 C = runoff coefficient

	Total Site	Cultec System	Restricted Flat Roof	Restricted Green Roof
Area (m ²)	27800	20359	7441	-
Runoff Coef.	0.90	0.90	0.90	-
Q _{controlled} (m ³ /s)	0.13979	0.13967	0.0312522	-

Note: 'Cultec System' Inflow calculation = 100 year flow + 'restricted flat roof' flow (0.0313m³/s) + 'Green Roof' flow (0m³/s).
 Note: Max. 'Cultec System' Inflow = 1.032m³/s

Time (min)	i (mm/h)	Total Site Storage			Cultec System Storage			Restricted Flat Roof Storage			Restricted Green Roof Storage			
		Inflow, Q (m ³ /s)	Flow Stored, Q (m ³ /s)	Req. Storage, V (m ³)	Inflow, Q ₁ (m ³ /s)	Flow Stored, Q ₁ (m ³ /s)	Req. Storage, V ₁ (m ³)	Inflow, Q ₂ (m ³ /s)	Flow Stored, Q ₂ (m ³ /s)	Req. Storage, V ₂ (m ³)	Inflow, Q ₃ (m ³ /s)	Flow Stored, Q ₃ (m ³ /s)	Req. Storage, V ₃ (m ³)	
Maximum	-	-	-	1290.4	1.032	-	923.2	-	-	-	367.6	-	-	0.0
10	196.54	1.366	1.226	735.683	1.032	0.892	535.142	0.366	0.334	200.613	0.000	0.000	0.000	0.000
11	189.78	1.319	1.179	778.244	0.997	0.857	565.949	0.353	0.322	212.375	0.000	0.000	0.000	0.000
12	183.47	1.275	1.135	817.458	0.965	0.825	594.304	0.341	0.310	223.241	0.000	0.000	0.000	0.000
13	177.58	1.234	1.094	853.652	0.935	0.795	620.447	0.330	0.299	233.298	0.000	0.000	0.000	0.000
14	172.07	1.196	1.056	887.112	0.907	0.767	644.589	0.320	0.289	242.624	0.000	0.000	0.000	0.000
15	166.89	1.160	1.020	918.088	0.881	0.741	666.911	0.310	0.279	251.285	0.000	0.000	0.000	0.000
20	145.13	1.009	0.869	1042.617	0.770	0.630	756.295	0.270	0.239	286.466	0.000	0.000	0.000	0.000
25	128.46	0.893	0.753	1129.525	0.685	0.545	818.128	0.239	0.208	311.577	0.000	0.000	0.000	0.000
30	115.28	0.801	0.661	1190.553	0.618	0.478	861.008	0.214	0.183	329.761	0.000	0.000	0.000	0.000
35	104.59	0.727	0.587	1232.988	0.564	0.424	890.271	0.195	0.163	342.969	0.000	0.000	0.000	0.000
40	95.75	0.665	0.526	1261.595	0.519	0.379	909.408	0.178	0.147	352.475	0.000	0.000	0.000	0.000
45	88.31	0.614	0.474	1279.628	0.481	0.341	920.801	0.164	0.133	359.151	0.000	0.000	0.000	0.000
60	71.69	0.498	0.358	1290.317	0.396	0.256	923.189	0.133	0.102	367.560	0.000	0.000	0.000	0.000
70	63.74	0.443	0.303	1273.376	0.356	0.216	907.156	0.119	0.087	366.724	0.000	0.000	0.000	0.000
80	57.40	0.399	0.259	1243.901	0.323	0.184	881.944	0.107	0.076	362.533	0.000	0.000	0.000	0.000
90	52.23	0.363	0.223	1205.275	0.297	0.157	850.030	0.097	0.066	355.893	0.000	0.000	0.000	0.000
120	41.17	0.286	0.146	1053.786	0.241	0.101	728.209	0.077	0.045	326.441	0.000	0.000	0.000	0.000
150	34.03	0.236	0.097	870.385	0.204	0.065	583.018	0.063	0.032	288.447	0.000	0.000	0.000	0.000
180	29.03	0.202	0.062	668.990	0.179	0.039	424.649	0.054	0.023	245.637	0.000	0.000	0.000	0.000

SWM Measure	Value
Allowable Release Rate	139.79 L/s
Uncontrolled Release Flow (Q)	0 L/s
Actual Orifice Flow	139.67 L/s
Orifice Size	230 mm
Total Quantity Storage Required	1290.4 m ³
Rooftop Storage Provided	367.6 m ³
Underground Quantity Storage Provided	929.2448639 m ³
Total Quantity Storage Provided	1296.8 m ³
TSS Removal Rate without treatment	24%
TSS Removal with treatment (Max. Inflow = 1032L/s)	85%
Water Balance Volume Required	139 m ³
Total Chamber Volume	1068.244864 m ³



CULTEC Stormwater Design Calculator

Date: September 30, 2024

Project Information:

Calculations Performed By:

RECHARGER 902HD



Recharger 902HD Chamber Specifications	
Height	1219 mm
Width	1981 mm
Length	1.25 meters
Installed Length	1.12 meters
Bare Chamber Volume	1.80 cu. meters
Installed Chamber Volume	2.99 cu. meters

Breakdown of Storage Provided by Recharger 902HD Stormwater System	
Stone Porosity	40.0 %
Within Chambers	1,404.79 cu. meters
Within Stone	988.59 cu. meters
Total Storage Provided	2,393.4 cu. meters
Total Storage Required	2330.00 cu. meters

Materials List

Recharger 902HD		
Total Number of Chambers Required	768	pieces
Separator Row Chambers	32	pieces
Chamber Units	768	pieces
End Caps	48	pieces
HVLV FC-48 Feed Connectors	46	pieces
CULTEC No. 410 Non-Woven Geotextile	5459	sq. meters
CULTEC AFAB-HPF Woven Geotextile	146	meters
Stone	2471	cu. meters

Separator Row Qty Included in Total


Based on 2 Internal Manifolds

Bed Detail



Bed Layout Information		
Number of Rows Wide	24	pieces
Number of Chambers Long	32	pieces
Chamber Row Width	52.81	meters
Chamber Row Length	36.98	meters
Bed Width	53.42	meters
Bed Length	37.59	meters
Bed Area Required	2008.02	sq. meters
Length of Separator Row	36.98	meters

Bed detail for reference only. Not project specific. Not to scale.



Conceptual graphic only. Not job specific.

Cross Section Table Reference		
A	Depth of Stone Base	400 mm
B	Chamber Height	1219 mm
C	Depth of Stone Above Units	305 mm
D	Depth of 95% Compacted Fill	305 mm
E	Max. Depth Allowed Above the Chamber	2.54 meters
F	Chamber Width	1981 mm
G	Center to Center Spacing	2.21 meters
H	Effective Depth	1.93 meters
I	Bed Depth	2.24 meters



CULTEC Stage-Storage Calculations

Date: September 30, 2024

Project Information:

Project Number:
0

Chamber Model -			Recharger 902HD		
Number of Rows -		24	units		
Total Number of Chambers -		768	units		
Stone Void -		40	%		
Stone Base -		400	mm		
Stone Above Units -		305	mm		
Area -		2008.02	m2		
Base of Stone Elevation -		260.67			

Recharger 902HD Incremental Storage Volumes

Height of System		Chamber Volume		HVLV Feed Connector Volume		Stone Volume		Cumulative Storage Volume		Total Cumulative Storage Volume		Stage / Area		Elevation	
in	mm	ft ³	m ³	ft3	m3	ft ²	m ²	ft ²	m ²	ft ³	m ³	ft ²	m ²	ft	m
76.0	1930	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	84540.74	2393.92	8645.67	803.18	267.00	262.60
75.0	1905	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	83820.27	2373.52	8645.67	803.18	266.92	262.58
74.0	1880	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	83099.80	2353.12	8645.67	803.18	266.84	262.55
73.0	1854	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	82379.32	2332.72	8645.67	803.18	266.75	262.52
72.0	1829	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	81658.85	2312.32	8645.67	803.18	266.67	262.50
71.0	1803	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	80938.38	2291.92	8645.67	803.18	266.59	262.47
70.0	1778	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	80217.91	2271.51	8645.67	803.18	266.50	262.45
69.0	1753	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	79497.43	2251.11	8645.67	803.18	266.42	262.42
68.0	1727	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	78776.96	2230.71	8645.67	803.18	266.34	262.40
67.0	1702	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	78056.49	2210.31	8645.67	803.18	266.25	262.37
66.0	1676	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	77336.02	2189.91	8645.67	803.18	266.17	262.35
65.0	1651	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	76615.55	2169.51	8645.67	803.18	266.09	262.32
64.0	1626	57.3	1.6	0.0	0.0	697.6	19.8	754.840	21.4	75895.07	2149.11	9058.08	841.50	266.00	262.30
63.0	1600	142.2	4.0	0.0	0.0	663.6	18.8	805.816	22.8	75140.23	2127.73	9669.79	898.32	265.92	262.27
62.0	1575	199.0	5.6	0.0	0.0	640.9	18.1	839.896	23.8	74334.42	2104.91	10078.75	936.32	265.84	262.24
61.0	1549	340.3	9.6	0.0	0.0	584.3	16.5	924.664	26.2	73494.52	2081.13	11095.97	1030.82	265.75	262.22
60.0	1524	453.4	12.8	0.0	0.0	539.1	15.3	992.536	28.1	72569.86	2054.95	11910.43	1106.48	265.67	262.19
59.0	1499	567.0	16.1	0.0	0.0	493.7	14.0	1,060.696	30.0	71577.32	2026.84	12728.35	1182.46	265.59	262.17
58.0	1473	624.3	17.7	0.0	0.0	470.7	13.3	1,095.064	31.0	70516.62	1996.81	13140.77	1220.78	265.50	262.14
57.0	1448	681.1	19.3	0.0	0.0	448.0	12.7	1,129.144	32.0	69421.56	1965.80	13549.73	1258.77	265.42	262.12
56.0	1422	766.6	21.7	0.0	0.0	413.8	11.7	1,180.408	33.4	68292.42	1933.82	14164.90	1315.92	265.34	262.10
55.0	1397	876.0	24.7	0.0	0.0	371.7	10.6	1,248.916	35.2	67112.01	1900.40	14168.35	1316.24	265.25	262.07
54.0	1372	984.3	27.8	0.0	0.0	330.7	9.4	1,314.832	37.0	65931.31	1866.96	14580.77	1354.55	265.17	262.04
53.0	1346	1,085.0	30.6	0.0	0.0	300.0	8.4	1,379.840	38.8	64761.25	1832.56	14786.98	1373.71	265.09	262.02
52.0	1321	1,182.1	33.4	0.0	0.0	270.0	7.6	1,443.920	40.4	63484.00	1797.66	14996.64	1393.19	265.00	261.99
51.0	1295	1,275.4	35.9	0.0	0.0	240.0	6.8	1,498.000	41.9	62234.28	1762.28	15409.06	1431.50	264.92	261.97
50.0	1270	1,365.0	38.4	0.0	0.0	210.0	6.0	1,552.080	43.3	60950.19	1725.91	15618.72	1450.98	264.84	261.94
49.0	1245	1,450.0	40.8	0.0	0.0	180.0	5.2	1,606.160	44.5	59648.63	1689.06	15831.84	1470.78	264.75	261.91
48.0	1219	1,531.0	42.9	0.0	0.0	150.0	4.4	1,659.240	45.7	58329.31	1651.70	15838.75	1471.42	264.67	261.89
47.0	1194	1,608.0	45.2	0.0	0.0	120.0	3.6	1,711.320	46.8	57009.41	1614.32	16048.42	1490.90	264.59	261.86
46.0	1168	1,682.0	47.5	0.0	0.0	90.0	2.8	1,762.400	47.8	55672.05	1576.45	16254.63	1510.05	264.50	261.84
45.0	1143	1,753.0	49.6	0.0	0.0	60.0	2.0	1,811.600	48.7	54317.49	1538.10	16464.29	1529.53	264.42	261.81
44.0	1118	1,821.0	51.6	0.0	0.0	30.0	1.2	1,859.200	49.5	52945.47	1499.25	16673.95	1549.01	264.34	261.79
43.0	1092	1,886.0	53.4	0.0	0.0	0.0	0.0	1,905.600	50.0	51555.97	1459.90	16677.41	1549.33	264.25	261.76
42.0	1067	1,948.0	55.2	0.0	0.0	0.0	0.0	1,950.400	50.0	50166.19	1420.55	16887.07	1568.81	264.17	261.74
41.0	1041	1,991.0	56.7	0.0	0.0	0.0	0.0	1,993.600	50.0	48758.93	1380.70	16890.53	1569.13	264.09	261.71
40.0	1016	1,978.0	56.1	0.0	0.0	0.0	0.0	1,972.800	49.5	47351.39	1340.84	17096.74	1588.29	264.00	261.69
39.0	991	1,974.0	55.8	0.0	0.0	0.0	0.0	1,925.200	48.5	45926.66	1300.50	17103.65	1588.93	263.92	261.66
38.0	965	1,975.0	55.6	0.0	0.0	0.0	0.0	1,825.600	47.0	44501.36	1260.14	17107.11	1589.25	263.84	261.64
37.0	940	1,943.0	54.7	0.0	0.0	0.0	0.0	1,742.000	45.5	43075.76	1219.77	17316.77	1608.73	263.75	261.61
36.0	914	1,904.0	53.1	0.0	0.0	0.0	0.0	1,644.352	43.9	41632.70	1178.90	17320.23	1609.05	263.67	261.58
35.0	889	1,805.8	51.0	0.0	0.0	0.0	0.0	1,443.928	40.9	40189.35	1138.03	17327.14	1609.69	263.59	261.56
34.0	864	1,734.4	49.0	0.0	0.0	0.0	0.0	1,461.112	41.4	38745.42	1097.15	17533.35	1628.85	263.50	261.53
33.0	838	1,634.9	46.1	0.0	0.0	0.0	0.0	1,461.400	41.4	37284.31	1055.77	17536.80	1629.17	263.42	261.51
32.0	813	1,526.3	42.7	0.0	0.0	0.0	0.0	1,478.584	41.9	35822.91	1014.39	17743.01	1648.33	263.34	261.48
31.0	787	1,404.0	39.8	0.0	0.0	0.0	0.0	1,479.160	41.9	34344.32	972.52	17749.92	1648.97	263.25	261.46
30.0	762	1,293.1	36.6	0.0	0.0	0.0	0.0	1,496.344	42.4	32865.16	930.64	17956.13	1668.12	263.17	261.43
29.0	737	1,293.6	36.6	0.0	0.0	0.0	0.0	1,496.632	42.4	31368.82	888.26	17959.59	1668.45	263.09	261.41
28.0	711	1,294.1	36.6	0.1	0.0	0.0	0.0	1,497.003	42.4	29872.19	845.88	17964.04	1668.86	263.00	261.38
27.0	686	1,294.6	36.7	1.1	0.0	0.0	0.0	1,497.850	42.4	28375.18	803.49	17974.20	1669.80	262.92	261.36
26.0	660	1,323.7	37.5	2.1	0.1	0.0	0.0	1,515.922	42.9	26877.33	761.08	18191.07	1689.95	262.84	261.33
25.0	635	1,324.2	37.5	2.5	0.1	189.8	5.4	1,516.479	42.9	25361.41	718.15	18197.75	1690.57	262.75	261.31
24.0	610	1,325.1	37.5	2.8	0.1	189.3	5.4	1,517.221	43.0	23844.93	675.21	18206.65	1691.40	262.67	261.28
23.0	584	1,325.6	37.5	2.9	0.1	189.1	5.4	1,517.592	43.0	22327.71	632.25	18211.10	1691.81	262.59	261.25
22.0	559	1,354.2	38.3	3.1	0.1	177.5	5.0	1,534.859	43.5	20810.12	589.28	18418.30	1711.06	262.50	261.23
21.0	533	1,354.7	38.4	3.2	0.1	177.3	5.0	1,535.229	43.5	19275.26	545.81	18422.75	1711.47	262.42	261.20
20.0	508	1,382.9	39.2	3.3	0.1	166.0	4.7	1,552.167	44.0	17740.03	502.34	18626.00	1730.36	262.34	261.18
19.0	483	1,383.4	39.2	3.3	0.1	165.8	4.7	1,552.496	44.0	16187.86	458.39	18629.95	1730.72	262.25	261.15
18.0	457	1,383.8	39.2	3.4	0.1	165.6	4.7	1,552.826	44.0	14635.37	414.43	18633.91	1731.09	262.17	261.13
17.0	432	1,387.2	39.3	3.7	0.1	164.1	4.6	1,554.986	44.0	13082.54	370.46	18659.84	1733.50	262.09	261.10
16.0	406	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	11527.56	326.42	8645.67	803.18	262.00	261.08
15.0	381	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	10807.08	306.02	8645.67	803.18	261.92	261.05
14.0	356	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	10086.61	285.62	8645.67	803.18	261.84	261.03
13.0	330	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	9366.14	265.22	8645.67	803.18	261.75	261.00
12.0	305	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	8645.67	244.82	8645.67	803.18	261.67	260.97
11.0	279	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	7925.19	224.42	8645.67	803.18	261.59	260.95
10.0	254	0.0	0.0	0.0	0.0	720.5	20.4	720.472	20.4	7204.72	204.01	8645.67	803.18	261.50	260.92
9.0	229	0.0	0.0	0.0	0.0	720.5	20.4	720.4							



CULTEC Stormwater Design Calculator

Date: September 30, 2024

Project Information:

Calculations Performed By:

RECHARGER 360HD



Recharger 360HD Chamber Specifications		
Height	914	mm
Width	1524	mm
Length	1.27	meters
Installed Length	1.12	meters
Bare Chamber Volume	1.04	cu. meters
Installed Chamber Volume	1.70	cu. meters

Breakdown of Storage Provided by Recharger 360HD Stormwater System		
Stone Porosity	40.0	%
Within Chambers	518.31	cu. meters
Within Stone	350.41	cu. meters
Total Storage Provided	868.7	cu. meters
Total Storage Required	856.00	cu. meters

Materials List

Recharger 360HD		
Total Number of Chambers Required	495	pieces
Separator Row Chambers	45	pieces
Chamber Units	495	pieces
End Caps	22	pieces
HVLV FC-48 Feed Connectors	20	pieces
CULTEC No. 410 Non-Woven Geotextile	2786	sq. meters
CULTEC AFAB-HPF Woven Geotextile	93	meters
Stone	876	cu. meters

Separator Row Qty Included in Total


Based on 2 Internal Manifolds

Bed Detail



Bed Layout Information		
Number of Rows Wide	11	pieces
Number of Chambers Long	45	pieces
Chamber Row Width	19.05	meters
Chamber Row Length	51.10	meters
Bed Width	19.66	meters
Bed Length	51.71	meters
Bed Area Required	1016.58	sq. meters
Length of Separator Row	51.10	meters

Bed detail for reference only. Not project specific. Not to scale.



Conceptual graphic only. Not job specific.

Cross Section Table Reference		
A	Depth of Stone Base	300 mm
B	Chamber Height	914 mm
C	Depth of Stone Above Units	152 mm
D	Depth of 95% Compacted Fill	305 mm
E	Max. Depth Allowed Above the Chamber	3.66 meters
F	Chamber Width	1524 mm
G	Center to Center Spacing	1.75 meters
H	Effective Depth	1.37 meters
I	Bed Depth	1.68 meters



CULTEC Stormwater Design Calculator

Date: September 30, 2024

Project Information:

Calculations Performed By:

RECHARGER 902HD



Recharger 902HD Chamber Specifications	
Height	1219 mm
Width	1981 mm
Length	1.25 meters
Installed Length	1.12 meters
Bare Chamber Volume	1.80 cu. meters
Installed Chamber Volume	3.09 cu. meters

Breakdown of Storage Provided by Recharger 902HD Stormwater System	
Stone Porosity	40.0 %
Within Chambers	493.82 cu. meters
Within Stone	413.81 cu. meters
Total Storage Provided	907.6 cu. meters
Total Storage Required	859.00 cu. meters

Materials List

Recharger 902HD		
Total Number of Chambers Required	260	pieces
Separator Row Chambers	10	pieces
Chamber Units	260	pieces
End Caps	52	pieces
HV LV FC-48 Feed Connectors	50	pieces
CULTEC No. 410 Non-Woven Geotextile	2240	sq. meters
CULTEC AFAB-HPF Woven Geotextile	129	meters
Stone	1035	cu. meters

Separator Row Qty Included in Total


Based on 2 Internal Manifolds

Bed Detail



Bed Layout Information		
Number of Rows Wide	26	pieces
Number of Chambers Long	10	pieces
Chamber Row Width	57.23	meters
Chamber Row Length	12.40	meters
Bed Width	57.84	meters
Bed Length	13.00	meters
Bed Area Required	752.14	sq. meters
Length of Separator Row	12.40	meters

Bed detail for reference only. Not project specific. Not to scale.



Conceptual graphic only. Not job specific.

Cross Section Table Reference			
A	Depth of Stone Base	500	mm
B	Chamber Height	1219	mm
C	Depth of Stone Above Units	305	mm
D	Depth of 95% Compacted Fill	305	mm
E	Max. Depth Allowed Above the Chamber	2.54	meters
F	Chamber Width	1981	mm
G	Center to Center Spacing	2.21	meters
H	Effective Depth	2.03	meters
I	Bed Depth	2.34	meters



CULTEC Stage-Storage Calculations

Date: September 30, 2024

Project Information:

Project Number: 0

Chamber Model - Recharger 902HD
Number of Rows - 26 units
Total Number of Chambers - 260 units
Stone Void - 40 %
Stone Base - 500 mm
Stone Above Units - 305 mm
Area - 752.14 m2
Base of Stone Elevation - 260.33

Recharger 902HD Incremental Storage Volumes

Table with 8 main columns: Height of System, Chamber Volume, HVLV Feed Connector Volume, Stone Volume, Cumulative Storage Volume, Total Cumulative Storage Volume, Stage / Area, and Elevation. It contains detailed data for each height increment from 0.0 to 80.0 units.



CULTEC Stormwater Design Calculator

Date: September 30, 2024

Project Information:

Calculations Performed By:

RECHARGER 902HD



Recharger 902HD Chamber Specifications	
Height	1219 mm
Width	1981 mm
Length	1.25 meters
Installed Length	1.12 meters
Bare Chamber Volume	1.80 cu. meters
Installed Chamber Volume	3.09 cu. meters

Breakdown of Storage Provided by Recharger 902HD Stormwater System	
Stone Porosity	40.0 %
Within Chambers	523.74 cu. meters
Within Stone	405.51 cu. meters
Total Storage Provided	929.2 cu. meters
Total Storage Required	923.00 cu. meters

Materials List

Recharger 902HD		
Total Number of Chambers Required	288	pieces
Separator Row Chambers	48	pieces
Chamber Units	288	pieces
End Caps	12	pieces
HV LV FC-48 Feed Connectors	10	pieces
CULTEC No. 410 Non-Woven Geotextile	2243	sq. meters
CULTEC AFAB-HPF Woven Geotextile	85	meters
Stone	1014	cu. meters

Separator Row Qty Included in Total


Based on 2 Internal Manifolds

Bed Detail



Bed Layout Information		
Number of Rows Wide	6	pieces
Number of Chambers Long	48	pieces
Chamber Row Width	13.03	meters
Chamber Row Length	54.86	meters
Bed Width	13.64	meters
Bed Length	55.47	meters
Bed Area Required	756.65	sq. meters
Length of Separator Row	54.86	meters

Bed detail for reference only. Not project specific. Not to scale.



Conceptual graphic only. Not job specific.

Cross Section Table Reference			
A	Depth of Stone Base	500	mm
B	Chamber Height	1219	mm
C	Depth of Stone Above Units	305	mm
D	Depth of 95% Compacted Fill	305	mm
E	Max. Depth Allowed Above the Chamber	2.54	meters
F	Chamber Width	1981	mm
G	Center to Center Spacing	2.21	meters
H	Effective Depth	2.03	meters
I	Bed Depth	2.34	meters



CULTEC Stage-Storage Calculations

Date: September 30, 2024

Project Information:

Project Number: 0

Chamber Model - Recharger 902HD
 Number of Rows - 6 units
 Total Number of Chambers - 288 units
 Stone Void - 40 %
 Stone Base - 500 mm
 Stone Above Units - 305 mm
 Area - 756.65 m2
 Base of Stone Elevation - 261.00

Recharger 902HD Incremental Storage Volumes															
Height of System		Chamber Volume		HVLV Feed Connector Volume		Stone Volume		Cumulative Storage Volume		Total Cumulative Storage Volume		Stage / Area		Elevation	
in	mm	ft ³	m ³	ft3	m3	ft ²	m ²	ft ²	m ²	ft ³	m ³	ft ²	m ²	ft	m
80.0	2032	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	32820.14	929.36	3257.80	302.65	267.67	263.03
79.0	2007	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	32548.65	921.67	3257.80	302.65	267.58	263.01
78.0	1981	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	32277.17	913.99	3257.80	302.65	267.50	262.98
77.0	1956	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	32005.69	906.30	3257.80	302.65	267.42	262.96
76.0	1930	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	31734.20	898.61	3257.80	302.65	267.33	262.93
75.0	1905	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	31462.72	890.92	3257.80	302.65	267.25	262.91
74.0	1880	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	31191.24	883.24	3257.80	302.65	267.17	262.88
73.0	1854	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	30919.75	875.55	3257.80	302.65	267.08	262.85
72.0	1829	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	30648.27	867.86	3257.80	302.65	267.00	262.83
71.0	1803	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	30376.79	860.17	3257.80	302.65	266.92	262.80
70.0	1778	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	30105.30	852.49	3257.80	302.65	266.83	262.78
69.0	1753	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	29833.82	844.80	3257.80	302.65	266.75	262.75
68.0	1727	21.4	0.6	0.0	0.0	262.9	7.4	284.299	8.1	29562.34	837.11	3411.59	316.94	266.67	262.73
67.0	1702	53.2	1.5	0.0	0.0	250.2	7.1	303.379	8.6	29278.04	829.06	3640.55	338.21	266.58	262.70
66.0	1676	74.4	2.1	0.0	0.0	241.7	6.8	316.123	9.0	28974.66	820.47	3793.48	352.41	266.50	262.68
65.0	1651	127.3	3.6	0.0	0.0	220.6	6.2	347.875	9.9	28658.53	811.52	4174.50	387.81	266.42	262.65
64.0	1626	169.7	4.8	0.0	0.0	203.6	5.8	373.291	10.6	28310.66	801.67	4479.50	416.15	266.33	262.63
63.0	1600	212.2	6.0	0.0	0.0	186.6	5.3	398.779	11.3	27937.37	791.10	4785.35	444.56	266.25	262.60
62.0	1575	233.5	6.6	0.0	0.0	178.1	5.0	411.595	11.7	27538.59	779.80	4939.14	458.85	266.17	262.57
61.0	1549	254.8	7.2	0.0	0.0	169.6	4.8	424.339	12.0	27126.99	768.15	5092.07	473.05	266.08	262.55
60.0	1524	286.7	8.1	0.0	0.0	156.8	4.4	443.491	12.6	26702.65	756.13	5321.90	494.40	266.00	262.52
59.0	1499	286.8	8.1	0.0	0.0	156.8	4.4	443.563	12.6	26259.16	743.58	5322.76	494.48	265.92	262.50
58.0	1473	308.2	8.7	0.0	0.0	148.2	4.2	456.379	12.9	25815.60	731.02	5476.55	508.77	265.83	262.47
57.0	1448	318.8	9.0	0.0	0.0	143.9	4.1	462.787	13.1	25359.22	718.09	5553.45	515.92	265.75	262.45
56.0	1422	329.6	9.3	0.0	0.0	139.6	4.0	469.267	13.3	24896.43	704.99	5631.21	523.14	265.67	262.42
55.0	1397	351.0	9.9	0.0	0.0	131.1	3.7	482.083	13.7	24427.16	691.70	5785.00	537.43	265.58	262.40
54.0	1372	361.8	10.2	0.0	0.0	126.8	3.6	488.563	13.8	23945.08	678.05	5862.76	544.65	265.50	262.37
53.0	1346	372.7	10.6	0.0	0.0	122.4	3.5	495.115	14.0	23456.52	664.21	5941.38	551.95	265.42	262.35
52.0	1321	373.0	10.6	0.0	0.0	122.3	3.5	495.259	14.0	22961.40	650.19	5943.11	552.12	265.33	262.32
51.0	1295	383.8	10.9	0.0	0.0	118.0	3.3	501.739	14.2	22466.14	636.17	6020.87	559.34	265.25	262.30
50.0	1270	394.4	11.2	0.0	0.0	113.7	3.2	508.147	14.4	21964.40	621.96	6097.77	566.48	265.17	262.27
49.0	1245	405.2	11.5	0.0	0.0	109.4	3.1	514.627	14.6	21456.26	607.57	6175.53	573.71	265.08	262.24
48.0	1219	416.0	11.8	0.0	0.0	105.1	3.0	521.107	14.8	20941.63	593.00	6253.29	580.93	265.00	262.22
47.0	1194	416.2	11.8	0.0	0.0	105.0	3.0	521.179	14.8	20420.52	578.24	6254.15	581.01	264.92	262.19
46.0	1168	427.0	12.1	0.0	0.0	100.7	2.9	527.659	14.9	19899.34	563.49	6331.91	588.23	264.83	262.17
45.0	1143	427.1	12.1	0.0	0.0	100.7	2.9	527.731	14.9	19371.68	548.54	6332.78	588.31	264.75	262.14
44.0	1118	437.8	12.4	0.0	0.0	96.4	2.7	534.139	15.1	18843.95	533.60	6409.67	595.46	264.67	262.12
43.0	1092	438.0	12.4	0.0	0.0	96.3	2.7	534.283	15.1	18309.81	518.48	6411.40	595.62	264.58	262.09
42.0	1067	438.1	12.4	0.0	0.0	96.2	2.7	534.355	15.1	17775.53	503.35	6412.26	595.70	264.50	262.07
41.0	1041	448.9	12.7	0.0	0.0	91.9	2.6	540.835	15.3	17241.17	488.21	6490.02	602.92	264.42	262.04
40.0	1016	449.0	12.7	0.0	0.0	91.9	2.6	540.907	15.3	16700.34	472.90	6490.89	603.00	264.33	262.02
39.0	991	449.3	12.7	0.0	0.0	91.8	2.6	541.051	15.3	16159.43	457.58	6492.62	603.16	264.25	261.99
38.0	965	460.0	13.0	0.0	0.0	87.5	2.5	547.459	15.5	15618.38	442.26	6569.51	610.31	264.17	261.97
37.0	940	460.1	13.0	0.0	0.0	87.5	2.5	547.531	15.5	15070.92	426.76	6570.38	610.39	264.08	261.94
36.0	914	470.8	13.3	0.0	0.0	83.2	2.4	553.939	15.7	14523.39	411.26	6647.27	617.53	264.00	261.91
35.0	889	471.0	13.3	0.0	0.0	83.1	2.4	554.083	15.7	13969.45	395.57	6649.00	617.69	263.92	261.89
34.0	864	481.7	13.6	0.0	0.0	78.8	2.2	560.491	15.9	13415.37	379.88	6725.90	624.84	263.83	261.86
33.0	838	481.8	13.6	0.0	0.0	78.8	2.2	560.563	15.9	12854.87	364.01	6726.76	624.92	263.75	261.84
32.0	813	481.9	13.6	0.0	0.0	78.7	2.2	560.635	15.9	12294.31	348.14	6727.64	625.02	263.67	261.81
31.0	787	482.0	13.6	0.2	0.0	78.6	2.2	560.847	15.9	11733.66	332.26	6730.16	625.23	263.58	261.79
30.0	762	492.8	14.0	0.5	0.0	74.2	2.1	567.457	16.1	11172.81	316.38	6809.49	632.60	263.50	261.76
29.0	737	493.0	14.0	0.5	0.0	74.1	2.1	567.588	16.1	10605.35	300.31	6811.05	632.75	263.42	261.74
28.0	711	493.2	14.0	0.6	0.0	74.0	2.1	567.768	16.1	10037.77	284.24	6813.21	632.95	263.33	261.71
27.0	686	493.3	14.0	0.6	0.0	73.9	2.1	567.858	16.1	9470.00	268.16	6814.29	633.05	263.25	261.69
26.0	660	504.0	14.3	0.7	0.0	69.6	2.0	574.284	16.3	8902.14	252.08	6891.41	640.21	263.17	261.66
25.0	635	504.1	14.3	0.7	0.0	69.6	2.0	574.374	16.3	8327.86	235.82	6892.49	640.31	263.08	261.64
24.0	610	514.7	14.6	0.7	0.0	65.3	1.8	580.719	16.4	7753.48	219.55	6968.63	647.39	263.00	261.61
23.0	584	514.8	14.6	0.7	0.0	65.3	1.8	580.800	16.4	7172.76	203.11	6969.60	647.48	262.92	261.58
22.0	559	514.9	14.6	0.7	0.0	65.2	1.8	580.881	16.4	6591.96	186.66	6970.57	647.57	262.83	261.56
21.0	533	515.8	14.6	0.8	0.0	64.9	1.8	581.416	16.5	6011.08	170.21	6977.00	648.16	262.75	261.53
20.0	508	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	5429.67	153.75	3257.80	302.65	262.67	261.51
19.0	483	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	5158.18	146.06	3257.80	302.65	262.58	261.48
18.0	457	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	4886.70	138.38	3257.80	302.65	262.50	261.46
17.0	432	0.0	0.0	0.0	0.0	271.5	7.7	271.483	7.7	4615.22	130.69	3257.80	302.65	262.42	261.43
16.0	406	0.0	0.0	0											

Recharger 902HD Incremental Storage Volumes

Height of System		Chamber Volume		HVLV Feed Connector Volume		Stone Volume		Cumulative Storage Volume		Total Cumulative Storage Volume		Stage / Area		Elevation	
in	mm	ft ³	m ³	ft ³	m ³	ft ³	m ³	ft ³	m ³	ft ³	m ³	ft ²	m ²	ft	m
-14.0															
-15.0															
-16.0															
-17.0															
-18.0															
-19.0															
-20.0															
-21.0															
-22.0															
-23.0															
-24.0															
-25.0															
-26.0															
-27.0															
-28.0															
-29.0															
-30.0															
-31.0															
-32.0															
-33.0															
-34.0															
-35.0															
-36.0															
-37.0															
-38.0															
-39.0															
-40.0															
-41.0															
-42.0															
-43.0															
-44.0															

Project: **Fieldgate Caledon**
 Project #: 24045
 Designed By: T.G
 Checked By: T.F
 Date: 8-Oct-2024

Infiltration Gallery - Infiltration Rate & Drawdown Time (Block A)

Infiltration Rate

Based on in-situ testing completed using a Guelph Permeameter, the measured field saturated hydraulic conductivity is approx 2.5×10^{-7} (Clayey Silt to Silty Clay)

From Gemtec Hydrogeological Investigation Report (dated June 19th) --> infiltration rate = 32 mm/hr

Design infiltration Rate has been used with a safety correction factor of 2.5

Design Infiltration Rate = 12.8 mm/hr

Infiltration Storage Required

Drainage Area 7.27 ha

Rainfall Depth (mm) 12.30 mm

Total Target Water Balance Volume 894.21 m³

	Vol of Infiltration (m ³)	Infiltration Rate (m/hr)	Area of Infiltration (m ²)	Infiltration Vol. Rate (m ³ /hr)	Drawdown Time (hrs)*	Effective Depth of Water (m)**	Weir Elevation (masl)***
Infiltration Gallery 1	782.68	0.0128	1959.96	25.09	24.2	0.31	264.27
Infiltration Gallery 2	152.83	0.0128	386.13	4.94	24.2	0.31	264.17
Total	935.50						

*Max allowable drawdown time = 72 hours (3 days)

**depth interpolated from Cultec stage-storage sheet and multiplied by void ratio (0.40)

***stage elevation at which infiltrated volume is achieved

Project: **Fieldgate Caledon**
 Project #: 24045
 Designed By: T.G
 Checked By: T.F
 Date: 8-Oct-2024

Infiltration Gallery - Infiltration Rate & Drawdown Time (Block B)

Infiltration Rate

Based on in-situ testing completed using a Guelph Permeameter, the measured field saturated hydraulic conductivity is approx 2.5×10^{-7} (Clayey Silt to Silty Clay)

From Gemtec Hydrogeological Investigation Report (dated June 19th) --> infiltration rate = 32 mm/hr

Design infiltration Rate has been used with a safety correction factor of 2.5

Design Infiltration Rate = 12.8 mm/hr

Infiltration Storage Required

Drainage Area 2.49 ha

Rainfall Depth (mm) 12.30 mm

Total Target Water Balance Volume 306.27 m³

	Vol of Infiltration (m ³)	Infiltration Rate (m/hr)	Area of Infiltration (m ²)	Infiltration Vol. Rate (m ³ /hr)	Drawdown Time (hrs)*	Effective Depth of Water (m)**	Weir Elevation (masl)***
Infiltration Gallery 3	192.90	0.0128	485.42	6.21	24.2	0.31	263.27
Infiltration Gallery 4	131.80	0.0128	332.13	4.25	24.2	0.31	263.27
Total	324.71						

*Max allowable drawdown time = 72 hours (3 days)

**depth interpolated from Cultec stage-storage sheet and multiplied by void ratio (0.40)

***stage elevation at which infiltrated volume is achieved

Project: **Fieldgate Caledon**
 Project #: 24045
 Designed By: T.G
 Checked By: T.F
 Date: 8-Oct-2024

Infiltration Gallery - Infiltration Rate & Drawdown Time (Block C)

Infiltration Rate

Based on in-situ testing completed using a Guelph Permeameter, the measured field saturated hydraulic conductivity is approx 2.5×10^{-7} (Clayey Silt to Silty Clay)

From Gemtec Hydrogeological Investigation Report (dated June 19th) --> infiltration rate = 32 mm/hr

Design infiltration Rate has been used with a safety correction factor of 2.5

Design Infiltration Rate = 12.8 mm/hr

Infiltration Storage Required

Drainage Area 2.78 ha

Rainfall Depth (mm) 12.30 mm

Total Target Water Balance Volume 341.94 m³

	Vol of Infiltration (m ³)	Infiltration Rate (m/hr)	Area of Infiltration (m ²)	Infiltration Vol. Rate (m ³ /hr)	Drawdown Time (hrs)*	Effective Depth of Water (m)**	Weir Elevation (masl)***
Infiltration Gallery 5	348.27	0.0128	873.87	11.19	24.2	0.31	264.77
Total	348.27						

*Max allowable drawdown time = 72 hours (3 days)

**depth interpolated from Cultec stage-storage sheet and multiplied by void ratio (0.40)

***stage elevation at which infiltrated volume is achieved

Project: **Fieldgate Caledon**
Project #: 24045
Designed By: L.P.
Checked By: T.F
Date: 8-Oct-2024

Overcompensating Shortfalls

	Total Area (ha)	Captured Area (ha)	Retained Volume (m3)	Required Retention Depth (mm)	Retention Depth of Captured Area (mm)
Block A	7.27	3.12	935.50	12.3	30.0
Block B	2.49	2.12	324.71	12.3	15.3
Block C	2.78	1.28	348.27	12.3	27.2
Total	12.54	6.52	1608.48	12.3	24.7




CULTEC Stormwater Design Calculator

Date:	October 08, 2024
Project Information:	

Calculations Performed By:	

CONTACTOR 100HD

Contactor 100HD Chamber Specifications		
Height	318	mm
Width	914	mm
Length	2.44	meters
Installed Length	2.29	meters
Bare Chamber Volume	0.40	cu. meters
Installed Chamber Volume	1.05	cu. meters



Breakdown of Storage Provided by Contactor 100HD Stormwater System		
Stone Porosity	40.0	%
Within Chambers	292.21	cu. meters
Within Stone	490.47	cu. meters
Total Storage Provided	782.7	cu. meters
Total Storage Required	730.00	cu. meters

Materials List

Contactor 100HD		
Total Number of Chambers Required	728	pieces
Separator Row Chambers	14	pieces
Starter Chambers	52	pieces
End Chambers	676	pieces
HVLV SFCx2 Feed Connectors	102	pieces
CULTEC No. 410 Non-Woven Geotextile	5079	sq. meters
CULTEC AFAB-HPF Woven Geotextile	153	meters
Stone	1226	cu. meters

Separator Row Qty Included in Total


Based on 2 Internal Manifolds

Bed Detail



Bed Layout Information		
Number of Rows Wide	52	pieces
Number of Chambers Long	14	pieces
Chamber Row Width	59.21	meters
Chamber Row Length	32.16	meters
Bed Width	59.82	meters
Bed Length	32.77	meters
Bed Area Required	1959.96	sq. meters
Length of Separator Row	32.16	meters

Bed detail for reference only. Not project specific. Not to scale.



Conceptual graphic only. Not job specific.

Cross Section Table Reference			
A	Depth of Stone Base	152	mm
B	Chamber Height	318	mm
C	Depth of Stone Above Units	300	mm
D	Depth of 95% Compacted Fill	203	mm
E	Max. Depth Allowed Above the Chamber	3.66	meters
F	Chamber Width	914	mm
G	Center to Center Spacing	1.14	meters
H	Effective Depth	0.77	meters
I	Bed Depth	0.98	meters



CULTEC Stage-Storage Calculations

Date: October 8, 2024

Project Information:

Project Number:
0

Chamber Model - **Contactor 100HD**
 Number of Rows - 52 units
 Total Number of Chambers - 728 units
 Stone Void - 40 %
 Stone Base - 152 mm
 Stone Above Units - 300 mm
 Area - 1959.96 m2
 Base of Stone Elevation - 263.50

Contactor 100HD Incremental Storage Volumes

Height of System		Chamber Volume		HVLV Feed Connector Volume		Stone Volume		Cumulative Storage Volume		Total Cumulative Storage Volume		Stage / Area		Elevation	
In	mm	ft³	m³	ft³	m³	ft²	m²	ft³	m³	ft³	m³	ft²	m²	ft	m
30.5	775	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	27650.33	782.97	8438.75	783.96	266.04	264.27
29.5	749	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	26947.10	763.06	8438.75	783.96	265.96	264.25
28.5	724	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	26243.87	743.14	8438.75	783.96	265.88	264.22
27.5	699	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	25540.64	723.23	8438.75	783.96	265.79	264.20
26.5	673	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	24837.41	703.32	8438.75	783.96	265.71	264.17
25.5	648	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	24134.18	683.40	8438.75	783.96	265.63	264.15
24.5	622	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	23430.95	663.49	8438.75	783.96	265.54	264.12
23.5	597	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	22727.72	643.58	8438.75	783.96	265.46	264.10
22.5	572	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	22024.49	623.66	8438.75	783.96	265.38	264.07
21.5	546	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	21321.27	603.75	8438.75	783.96	265.29	264.05
20.5	521	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	20618.04	583.84	8438.75	783.96	265.21	264.02
19.5	495	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	19914.81	563.92	8438.75	783.96	265.13	264.00
18.5	470	0.5	0.0	0.0	0.0	351.4	10.0	351.944	10.0	19211.58	544.01	4223.32	392.35	265.04	263.97
18.0	457	131.7	3.7	0.0	0.0	650.6	18.4	782.228	22.2	18859.63	534.04	9386.73	872.03	265.00	263.96
17.0	432	367.6	10.4	0.0	0.0	556.2	15.7	923.766	26.2	18077.41	511.89	11085.20	1029.81	264.92	263.93
16.0	406	603.5	17.1	0.0	0.0	461.8	13.1	1,065.305	30.2	17153.64	485.74	12783.66	1187.60	264.83	263.91
15.0	381	762.6	21.6	0.0	0.0	398.2	11.3	1,160.762	32.9	16088.34	455.57	13929.14	1294.02	264.75	263.88
14.0	356	872.3	24.7	0.0	0.0	354.3	10.0	1,226.639	34.7	14927.57	422.70	14719.67	1367.46	264.67	263.86
13.0	330	954.6	27.0	0.3	0.0	321.4	9.1	1,276.255	36.1	13700.93	387.97	15315.06	1422.77	264.58	263.83
12.0	305	1,009.4	28.6	1.0	0.0	299.5	8.5	1,309.929	37.1	12424.68	351.83	15719.14	1460.31	264.50	263.80
11.0	279	1,053.3	29.8	1.4	0.0	281.9	8.0	1,336.611	37.8	11114.75	314.73	16039.33	1490.05	264.42	263.78
10.0	254	1,113.7	31.5	1.5	0.0	257.8	7.3	1,372.959	38.9	9778.14	276.89	16475.50	1530.57	264.33	263.75
9.0	229	1,113.7	31.5	1.6	0.0	257.8	7.3	1,373.041	38.9	8405.18	238.01	16476.49	1530.67	264.25	263.73
8.0	203	1,113.7	31.5	1.7	0.0	257.8	7.3	1,373.122	38.9	7032.14	199.13	16477.46	1530.76	264.17	263.70
7.0	178	1,223.4	34.6	2.4	0.1	213.9	6.1	1,439.644	40.8	5659.02	160.25	17275.72	1604.91	264.08	263.68
6.0	152	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	4219.38	119.48	8438.75	783.96	264.00	263.65
5.0	127	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	3516.15	99.57	8438.75	783.96	263.92	263.63
4.0	102	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	2812.92	79.65	8438.75	783.96	263.83	263.60
3.0	76	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	2109.69	59.74	8438.75	783.96	263.75	263.58
2.0	51	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	1406.46	39.83	8438.75	783.96	263.67	263.55
1.0	25	0.0	0.0	0.0	0.0	703.2	19.9	703.229	19.9	703.23	19.91	8438.75	783.96	263.58	263.53
0.0	0	0.0	0.0	0.0	0.0	0.0	0.0	0.000	0.0	0.00	0.00	0.00	0.00	263.50	263.50
-1.0															
-2.0															
-3.0															
-4.0															
-5.0															
-6.0															
-7.0															
-8.0															
-9.0															
-10.0															
-11.0															
-12.0															
-13.0															
-14.0															
-15.0															
-16.0															
-17.0															
-18.0															
-19.0															
-20.0															
-21.0															
-22.0															
-23.0															
-24.0															
-25.0															
-26.0															
-27.0															
-28.0															
-29.0															
-30.0															
-31.0															
-32.0															
-33.0															
-34.0															
-35.0															
-36.0															
-37.0															
-38.0															
-39.0															
-40.0															
-41.0															
-42.0															
-43.0															
-44.0															
-45.0															
-46.0															
-47.0															
-48.0															
-49.0															
-50.0															
-51.0															
-52.0															
-53.0															
-54.0															
-55.0															
-56.0															
-57.0															
-58.0															
-59.0															
-60.0															
-61.0															
-62.0															
-63.0															
-64.0															
-65.0															




CULTEC Stormwater Design Calculator

Date:	October 08, 2024
Project Information:	

Calculations Performed By:	

CONTACTOR 100HD

Contactor 100HD Chamber Specifications		
Height	318	mm
Width	914	mm
Length	2.44	meters
Installed Length	2.29	meters
Bare Chamber Volume	0.40	cu. meters
Installed Chamber Volume	1.05	cu. meters



Breakdown of Storage Provided by Contactor 100HD Stormwater System		
Stone Porosity	40.0	%
Within Chambers	55.29	cu. meters
Within Stone	97.54	cu. meters
Total Storage Provided	152.8	cu. meters
Total Storage Required	150.00	cu. meters

Materials List

Contactor 100HD		
Total Number of Chambers Required	138	pieces
Separator Row Chambers	23	pieces
Starter Chambers	6	pieces
End Chambers	132	pieces
HVLV SFCx2 Feed Connectors	10	pieces
CULTEC No. 410 Non-Woven Geotextile	1083	sq. meters
CULTEC AFAB-HPF Woven Geotextile	70	meters
Stone	244	cu. meters

Separator Row Qty Included in Total


Based on 2 Internal Manifolds

Bed Detail



Bed Layout Information		
Number of Rows Wide	6	pieces
Number of Chambers Long	23	pieces
Chamber Row Width	6.63	meters
Chamber Row Length	52.73	meters
Bed Width	7.24	meters
Bed Length	53.34	meters
Bed Area Required	386.13	sq. meters
Length of Separator Row	52.73	meters

Bed detail for reference only. Not project specific. Not to scale.



Conceptual graphic only. Not job specific.

Cross Section Table Reference			
A	Depth of Stone Base	152	mm
B	Chamber Height	318	mm
C	Depth of Stone Above Units	300	mm
D	Depth of 95% Compacted Fill	203	mm
E	Max. Depth Allowed Above the Chamber	3.66	meters
F	Chamber Width	914	mm
G	Center to Center Spacing	1.14	meters
H	Effective Depth	0.77	meters
I	Bed Depth	0.98	meters



CULTEC Stage-Storage Calculations

Date: October 8, 2024

Project Information:

Project Number:
0

Chamber Model - **Contactor 100HD**
 Number of Rows - 6 units
 Total Number of Chambers - 138 units
 Stone Void - 40 %
 Stone Base - 152 mm
 Stone Above Units - 300 mm
 Area - 386.13 m2
 Base of Stone Elevation - 263.40

Contactor 100HD Incremental Storage Volumes

Height of System		Chamber Volume		HVLV Feed Connector Volume		Stone Volume		Cumulative Storage Volume		Total Cumulative Storage Volume		Stage / Area		Elevation	
In	mm	ft²	m²	ft³	m³	ft²	m²	ft²	m²	ft²	m²	ft²	m²	ft	m
30.5	775	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	5398.05	152.86	1662.50	154.45	265.94	264.17
29.5	749	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	5259.51	148.93	1662.50	154.45	265.86	264.15
28.5	724	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	5120.97	145.01	1662.50	154.45	265.78	264.12
27.5	699	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	4982.43	141.09	1662.50	154.45	265.69	264.10
26.5	673	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	4843.88	137.16	1662.50	154.45	265.61	264.07
25.5	648	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	4705.34	133.24	1662.50	154.45	265.53	264.05
24.5	622	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	4566.80	129.32	1662.50	154.45	265.44	264.02
23.5	597	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	4428.26	125.39	1662.50	154.45	265.36	264.00
22.5	572	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	4289.72	121.47	1662.50	154.45	265.28	263.97
21.5	546	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	4151.18	117.55	1662.50	154.45	265.19	263.95
20.5	521	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	4012.63	113.62	1662.50	154.45	265.11	263.92
19.5	495	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	3874.09	109.70	1662.50	154.45	265.03	263.90
18.5	470	0.1	0.0	0.0	0.0	69.2	2.0	69.333	2.0	3735.55	105.78	832.00	77.29	264.94	263.87
18.0	457	24.9	0.7	0.0	0.0	128.6	3.6	153.489	4.3	3665.22	103.82	1841.87	171.11	264.90	263.86
17.0	432	69.5	2.0	0.0	0.0	110.7	3.1	180.269	5.1	3512.73	99.47	2163.23	200.96	264.82	263.83
16.0	406	114.2	3.2	0.0	0.0	92.9	2.6	207.050	5.9	3332.46	94.36	2484.60	230.82	264.73	263.81
15.0	381	144.3	4.1	0.0	0.0	80.8	2.3	225.111	6.4	3125.41	88.50	2701.33	250.95	264.65	263.78
14.0	356	165.0	4.7	0.0	0.0	72.5	2.1	237.571	6.7	2900.30	82.13	2850.86	264.84	264.57	263.76
13.0	330	180.6	5.1	0.0	0.0	66.3	1.9	246.937	7.0	2662.73	75.40	2963.24	275.29	264.48	263.73
12.0	305	191.0	5.4	0.1	0.0	62.1	1.8	253.239	7.2	2415.79	68.41	3038.87	282.31	264.40	263.70
11.0	279	199.3	5.6	0.1	0.0	58.8	1.7	258.256	7.3	2162.55	61.24	3099.07	287.90	264.32	263.68
10.0	254	210.7	6.0	0.2	0.0	54.3	1.5	265.121	7.5	1904.30	53.92	3181.45	295.56	264.23	263.65
9.0	229	210.7	6.0	0.2	0.0	54.3	1.5	265.129	7.5	1639.18	46.42	3181.54	295.57	264.15	263.63
8.0	203	210.7	6.0	0.2	0.0	54.3	1.5	265.137	7.5	1374.05	38.91	3181.64	295.57	264.07	263.60
7.0	178	231.5	6.6	0.2	0.0	46.0	1.3	277.660	7.9	1108.91	31.40	3331.92	309.54	263.98	263.58
6.0	152	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	831.25	23.54	1662.50	154.45	263.90	263.55
5.0	127	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	692.71	19.62	1662.50	154.45	263.82	263.53
4.0	102	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	554.17	15.69	1662.50	154.45	263.73	263.50
3.0	76	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	415.63	11.77	1662.50	154.45	263.65	263.48
2.0	51	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	277.08	7.85	1662.50	154.45	263.57	263.45
1.0	25	0.0	0.0	0.0	0.0	138.5	3.9	138.542	3.9	138.54	3.92	1662.50	154.45	263.48	263.43
0.0	0	0.0	0.0	0.0	0.0	0.0	0.0	0.000	0.0	0.00	0.00	0.00	0.00	263.40	263.40
-1.0															
-2.0															
-3.0															
-4.0															
-5.0															
-6.0															
-7.0															
-8.0															
-9.0															
-10.0															
-11.0															
-12.0															
-13.0															
-14.0															
-15.0															
-16.0															
-17.0															
-18.0															
-19.0															
-20.0															
-21.0															
-22.0															
-23.0															
-24.0															
-25.0															
-26.0															
-27.0															
-28.0															
-29.0															
-30.0															
-31.0															
-32.0															
-33.0															
-34.0															
-35.0															
-36.0															
-37.0															
-38.0															
-39.0															
-40.0															
-41.0															
-42.0															
-43.0															
-44.0															
-45.0															
-46.0															
-47.0															
-48.0															
-49.0															
-50.0															
-51.0															
-52.0															
-53.0															
-54.0															
-55.0															
-56.0															
-57.0															
-58.0															
-59.0															
-60.0															
-61.0															
-62.0															
-63.0															
-64.0															
-65.0															




CULTEC Stormwater Design Calculator

Date:	October 08, 2024
Project Information:	

Calculations Performed By:	

CONTACTOR 100HD

Contactor 100HD Chamber Specifications		
Height	318	mm
Width	914	mm
Length	2.44	meters
Installed Length	2.29	meters
Bare Chamber Volume	0.40	cu. meters
Installed Chamber Volume	1.05	cu. meters



Breakdown of Storage Provided by Contactor 100HD Stormwater System		
Stone Porosity	40.0	%
Within Chambers	70.57	cu. meters
Within Stone	122.19	cu. meters
Total Storage Provided	192.8	cu. meters
Total Storage Required	181.00	cu. meters

Materials List

Contactor 100HD		
Total Number of Chambers Required	175	pieces
Separator Row Chambers	7	pieces
Starter Chambers	25	pieces
End Chambers	150	pieces
HVLV SFCx2 Feed Connectors	48	pieces
CULTEC No. 410 Non-Woven Geotextile	1302	sq. meters
CULTEC AFAB-HPF Woven Geotextile	75	meters
Stone	305	cu. meters

Separator Row Qty Included in Total


Based on 2 Internal Manifolds

Bed Detail



Bed Layout Information		
Number of Rows Wide	25	pieces
Number of Chambers Long	7	pieces
Chamber Row Width	28.35	meters
Chamber Row Length	16.15	meters
Bed Width	28.96	meters
Bed Length	16.76	meters
Bed Area Required	485.42	sq. meters
Length of Separator Row	16.15	meters

Bed detail for reference only. Not project specific. Not to scale.



Conceptual graphic only. Not job specific.

Cross Section Table Reference			
A	Depth of Stone Base	152	mm
B	Chamber Height	318	mm
C	Depth of Stone Above Units	300	mm
D	Depth of 95% Compacted Fill	203	mm
E	Max. Depth Allowed Above the Chamber	3.66	meters
F	Chamber Width	914	mm
G	Center to Center Spacing	1.14	meters
H	Effective Depth	0.77	meters
I	Bed Depth	0.98	meters



CULTEC Stage-Storage Calculations

Date: October 8, 2024

Project Information:

Project Number: 0

Chamber Model -	Contactor 100HD	
Number of Rows -	25	units
Total Number of Chambers -	175	units
Stone Void -	40	%
Stone Base -	152	mm
Stone Above Units -	300	mm
Area -	485.42	m2
Base of Stone Elevation -	262.50	

Contactor 100HD Incremental Storage Volumes

Height of System	Chamber Volume		HVLV Feed Connector Volume		Stone Volume		Cumulative Storage Volume		Total Cumulative Storage Volume		Stage / Area		Elevation			
	In	mm	ft²	m²	ft3	m3	ft²	m²	ft²	m²	ft²	m²	ft²	m²	ft	m
30.5	775	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	6812.27	192.90	2090.00	194.16	265.04	263.27	Top of Stone Elevation
29.5	749	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	6638.10	187.97	2090.00	194.16	264.96	263.25	
28.5	724	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	6463.93	183.04	2090.00	194.16	264.88	263.22	
27.5	699	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	6289.77	178.11	2090.00	194.16	264.79	263.20	
26.5	673	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	6115.60	173.17	2090.00	194.16	264.71	263.17	
25.5	648	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	5941.43	168.24	2090.00	194.16	264.63	263.15	
24.5	622	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	5767.27	163.31	2090.00	194.16	264.54	263.12	
23.5	597	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	5593.10	158.38	2090.00	194.16	264.46	263.10	
22.5	572	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	5418.93	153.45	2090.00	194.16	264.38	263.07	
21.5	546	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	5244.77	148.52	2090.00	194.16	264.29	263.05	
20.5	521	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	5070.60	143.58	2090.00	194.16	264.21	263.02	
19.5	495	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	4896.43	138.65	2090.00	194.16	264.13	263.00	
18.5	470	0.1	0.0	0.0	0.0	87.0	2.5	87.163	2.5	4722.27	133.72	1045.95	97.17	264.04	262.97	Top of Chamber Elevation
18.0	457	31.8	0.9	0.0	0.0	161.4	4.6	193.247	5.5	4635.11	131.25	2318.96	215.43	264.00	262.96	
17.0	432	88.8	2.5	0.0	0.0	138.7	3.9	227.432	6.4	4441.86	125.78	2729.18	253.54	263.92	262.93	
16.0	406	145.8	4.1	0.0	0.0	115.9	3.3	261.617	7.4	4214.43	119.34	3139.40	291.65	263.83	262.91	
15.0	381	184.2	5.2	0.0	0.0	100.5	2.8	284.672	8.1	3952.81	111.93	3416.06	317.35	263.75	262.88	
14.0	356	210.7	6.0	0.0	0.0	89.9	2.5	300.593	8.5	3668.14	103.87	3607.12	335.10	263.67	262.86	
13.0	330	230.6	6.5	0.1	0.0	81.9	2.3	312.632	8.9	3367.55	95.36	3751.58	348.52	263.58	262.83	
12.0	305	243.8	6.9	0.5	0.0	76.6	2.2	320.938	9.1	3054.91	86.51	3851.26	357.78	263.50	262.80	
11.0	279	254.4	7.2	0.7	0.0	72.4	2.1	327.463	9.3	2733.98	77.42	3925.55	365.06	263.42	262.78	
10.0	254	269.0	7.6	0.7	0.0	66.6	1.9	326.274	9.5	2406.51	68.14	4035.29	374.88	263.33	262.75	
9.0	229	269.0	7.6	0.8	0.0	66.6	1.9	336.312	9.5	2070.24	58.62	4035.75	374.92	263.25	262.73	
8.0	203	269.0	7.6	0.8	0.0	66.6	1.9	336.351	9.5	1733.93	49.10	4036.21	374.96	263.17	262.70	
7.0	178	295.5	8.4	1.1	0.0	56.0	1.6	352.575	10.0	1397.58	39.57	4230.90	393.05	263.08	262.68	
6.0	152	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	1045.00	29.59	2090.00	194.16	263.00	262.65	Bottom of Chamber Elevation
5.0	127	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	870.83	24.66	2090.00	194.16	262.92	262.63	
4.0	102	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	696.67	19.73	2090.00	194.16	262.83	262.60	
3.0	76	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	522.50	14.80	2090.00	194.16	262.75	262.58	
2.0	51	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	348.33	9.86	2090.00	194.16	262.67	262.55	
1.0	25	0.0	0.0	0.0	0.0	174.2	4.9	174.167	4.9	174.17	4.93	2090.00	194.16	262.58	262.53	
0.0	0	0.0	0.0	0.0	0.0	0.0	0.0	0.000	0.0	0.00	0.00	0.00	0.00	262.50	262.50	Bottom of Stone Elevation
-1.0																
-2.0																
-3.0																
-4.0																
-5.0																
-6.0																
-7.0																
-8.0																
-9.0																
-10.0																
-11.0																
-12.0																
-13.0																
-14.0																
-15.0																
-16.0																
-17.0																
-18.0																
-19.0																
-20.0																
-21.0																
-22.0																
-23.0																
-24.0																
-25.0																
-26.0																
-27.0																
-28.0																
-29.0																
-30.0																
-31.0																
-32.0																
-33.0																
-34.0																
-35.0																
-36.0																
-37.0																
-38.0																
-39.0																
-40.0																
-41.0																
-42.0																
-43.0																
-44.0																
-45.0																
-46.0																
-47.0																
-48.0																
-49.0																
-50.0																
-51.0																
-52.0																
-53.0																
-54.0																
-55.0																
-56.0																
-57.0																
-58.0																
-59.0																
-60.0																
-61.0																
-62.0																
-63.0																
-64.0																
-65.0																



CULTEC Stormwater Design Calculator


Date: October 08, 2024

Project Information:

Calculations Performed By:

CONTACTOR 100HD

Contactor 100HD Chamber Specifications		
Height	318	mm
Width	914	mm
Length	2.44	meters
Installed Length	2.29	meters
Bare Chamber Volume	0.40	cu. meters
Installed Chamber Volume	1.05	cu. meters



Breakdown of Storage Provided by Contactor 100HD Stormwater System		
Stone Porosity	40.0	%
Within Chambers	47.99	cu. meters
Within Stone	83.72	cu. meters
Total Storage Provided	131.7	cu. meters
Total Storage Required	125.00	cu. meters

Materials List

Contactor 100HD		
Total Number of Chambers Required	119	pieces
Separator Row Chambers	7	pieces
Starter Chambers	17	pieces
End Chambers	102	pieces
HVLV SFCx2 Feed Connectors	32	pieces
CULTEC No. 410 Non-Woven Geotextile	901	sq. meters
CULTEC AFAB-HPF Woven Geotextile	57	meters
Stone	209	cu. meters

Separator Row Qty Included in Total


Based on 2 Internal Manifolds

Bed Detail



Bed Layout Information		
Number of Rows Wide	17	pieces
Number of Chambers Long	7	pieces
Chamber Row Width	19.20	meters
Chamber Row Length	16.15	meters
Bed Width	19.81	meters
Bed Length	16.76	meters
Bed Area Required	332.13	sq. meters
Length of Separator Row	16.15	meters

Bed detail for reference only. Not project specific. Not to scale.



Conceptual graphic only. Not job specific.

Cross Section Table Reference			
A	Depth of Stone Base	152	mm
B	Chamber Height	318	mm
C	Depth of Stone Above Units	300	mm
D	Depth of 95% Compacted Fill	203	mm
E	Max. Depth Allowed Above the Chamber	3.66	meters
F	Chamber Width	914	mm
G	Center to Center Spacing	1.14	meters
H	Effective Depth	0.77	meters
I	Bed Depth	0.98	meters



CULTEC Stage-Storage Calculations

Date: October 8, 2024

Project Information:

Project Number:
0

Chamber Model - **Contactor 100HD**
 Number of Rows - 17 units
 Total Number of Chambers - 119 units
 Stone Void - 40 %
 Stone Base - 152 mm
 Stone Above Units - 300 mm
 Area - 332.13 m2
 Base of Stone Elevation - 263.00

Contactor 100HD Incremental Storage Volumes

Height of System		Chamber Volume		HVLV Feed Connector Volume		Stone Volume		Cumulative Storage Volume		Total Cumulative Storage Volume		Stage / Area		Elevation		
In	mm	ft³	m³	ft³	m³	ft²	m²	ft³	m³	ft³	m³	ft²	m²	ft	m	
30.5	775	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	4654.65	131.80	1430.00	132.85	265.54	263.77	Top of Stone Elevation
29.5	749	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	4535.48	128.43	1430.00	132.85	265.46	263.75	
28.5	724	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	4416.31	125.06	1430.00	132.85	265.38	263.72	
27.5	699	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	4297.15	121.68	1430.00	132.85	265.29	263.70	
26.5	673	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	4177.98	118.31	1430.00	132.85	265.21	263.67	
25.5	648	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	4058.81	114.93	1430.00	132.85	265.13	263.65	
24.5	622	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	3939.65	111.56	1430.00	132.85	265.04	263.62	
23.5	597	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	3820.48	108.18	1430.00	132.85	264.96	263.60	
22.5	572	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	3701.31	104.81	1430.00	132.85	264.88	263.57	
21.5	546	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	3582.15	101.43	1430.00	132.85	264.79	263.55	
20.5	521	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	3462.98	98.06	1430.00	132.85	264.71	263.52	
19.5	495	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	3343.81	94.69	1430.00	132.85	264.63	263.50	
18.5	470	0.1	0.0	0.0	0.0	59.5	1.7	59.637	1.7	3224.65	91.31	715.65	66.48	264.54	263.47	Top of Chamber Elevation
18.0	457	21.6	0.6	0.0	0.0	110.5	3.1	132.141	3.7	3165.01	89.62	1585.69	147.31	264.50	263.46	
17.0	432	60.4	1.7	0.0	0.0	95.0	2.7	155.387	4.4	3032.87	85.88	1864.64	173.23	264.42	263.43	
16.0	406	99.1	2.8	0.0	0.0	79.5	2.3	178.633	5.1	2877.48	81.48	2143.59	199.14	264.33	263.41	
15.0	381	125.2	3.5	0.0	0.0	69.1	2.0	194.310	5.5	2698.85	76.42	2331.72	216.62	264.25	263.38	
14.0	356	143.3	4.1	0.0	0.0	61.9	1.8	205.136	5.8	2504.54	70.92	2461.64	228.69	264.17	263.36	
13.0	330	156.8	4.4	0.1	0.0	56.5	1.6	213.321	6.0	2299.40	65.11	2559.86	237.81	264.08	263.33	
12.0	305	165.8	4.7	0.3	0.0	52.9	1.5	218.965	6.2	2086.08	59.07	2627.58	244.10	264.00	263.30	
11.0	279	173.0	4.9	0.4	0.0	50.0	1.4	223.399	6.3	1867.12	52.87	2680.79	249.05	263.92	263.28	
10.0	254	182.9	5.2	0.5	0.0	46.0	1.3	229.990	6.5	1643.72	46.54	2752.68	255.72	263.83	263.25	
9.0	229	182.9	5.2	0.5	0.0	46.0	1.3	229.416	6.5	1414.33	40.05	2752.99	255.75	263.75	263.23	
8.0	203	182.9	5.2	0.5	0.0	46.0	1.3	229.441	6.5	1184.91	33.55	2753.29	255.78	263.67	263.20	
7.0	178	200.9	5.7	0.7	0.0	38.8	1.1	240.470	6.8	955.47	27.06	2885.63	268.08	263.58	263.18	
6.0	152	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	715.00	20.25	1430.00	132.85	263.50	263.15	Bottom of Chamber Elevation
5.0	127	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	595.83	16.87	1430.00	132.85	263.42	263.13	
4.0	102	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	476.67	13.50	1430.00	132.85	263.33	263.10	
3.0	76	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	357.50	10.12	1430.00	132.85	263.25	263.08	
2.0	51	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	238.33	6.75	1430.00	132.85	263.17	263.05	
1.0	25	0.0	0.0	0.0	0.0	119.2	3.4	119.167	3.4	119.17	3.37	1430.00	132.85	263.08	263.03	
0.0	0	0.0	0.0	0.0	0.0	0.0	0.0	0.000	0.0	0.00	0.00	0.00	0.00	263.00	263.00	Bottom of Stone Elevation
-1.0																
-2.0																
-3.0																
-4.0																
-5.0																
-6.0																
-7.0																
-8.0																
-9.0																
-10.0																
-11.0																
-12.0																
-13.0																
-14.0																
-15.0																
-16.0																
-17.0																
-18.0																
-19.0																
-20.0																
-21.0																
-22.0																
-23.0																
-24.0																
-25.0																
-26.0																
-27.0																
-28.0																
-29.0																
-30.0																
-31.0																
-32.0																
-33.0																
-34.0																
-35.0																
-36.0																
-37.0																
-38.0																
-39.0																
-40.0																
-41.0																
-42.0																
-43.0																
-44.0																
-45.0																
-46.0																
-47.0																
-48.0																
-49.0																
-50.0																
-51.0																
-52.0																
-53.0																
-54.0																
-55.0																
-56.0																
-57.0																
-58.0																
-59.0																
-60.0																
-61.0																
-62.0																
-63.0																
-64.0																
-65.0																




CULTEC Stormwater Design Calculator

Date:	October 08, 2024
Project Information:	

Calculations Performed By:	

CONTACTOR 100HD

Contactor 100HD Chamber Specifications		
Height	318	mm
Width	914	mm
Length	2.44	meters
Installed Length	2.29	meters
Bare Chamber Volume	0.40	cu. meters
Installed Chamber Volume	1.05	cu. meters



Breakdown of Storage Provided by Contactor 100HD Stormwater System		
Stone Porosity	40.0	%
Within Chambers	129.01	cu. meters
Within Stone	219.19	cu. meters
Total Storage Provided	348.2	cu. meters
Total Storage Required	342.00	cu. meters

Materials List

Contactor 100HD		
Total Number of Chambers Required	322	pieces
Separator Row Chambers	23	pieces
Starter Chambers	14	pieces
End Chambers	308	pieces
HVLV SFCx2 Feed Connectors	26	pieces
CULTEC No. 410 Non-Woven Geotextile	2320	sq. meters
CULTEC AFAB-HPF Woven Geotextile	88	meters
Stone	548	cu. meters

Separator Row Qty Included in Total


Based on 2 Internal Manifolds

Bed Detail



Bed Layout Information		
Number of Rows Wide	14	pieces
Number of Chambers Long	23	pieces
Chamber Row Width	15.77	meters
Chamber Row Length	52.73	meters
Bed Width	16.38	meters
Bed Length	53.34	meters
Bed Area Required	873.87	sq. meters
Length of Separator Row	52.73	meters

Bed detail for reference only. Not project specific. Not to scale.



Conceptual graphic only. Not job specific.

Cross Section Table Reference			
A	Depth of Stone Base	152	mm
B	Chamber Height	318	mm
C	Depth of Stone Above Units	300	mm
D	Depth of 95% Compacted Fill	203	mm
E	Max. Depth Allowed Above the Chamber	3.66	meters
F	Chamber Width	914	mm
G	Center to Center Spacing	1.14	meters
H	Effective Depth	0.77	meters
I	Bed Depth	0.98	meters



CULTEC Stage-Storage Calculations

Date: October 8, 2024

Project Information:

Project Number:
0

Chamber Model -	Contactor 100HD	
Number of Rows -	14	units
Total Number of Chambers -	322	units
Stone Void -	40	%
Stone Base -	152	mm
Stone Above Units -	300	mm
Area -	873.87	m2
Base of Stone Elevation -	264.00	

Contactor 100HD Incremental Storage Volumes

Height of System		Chamber Volume		HVLV Feed Connector Volume		Stone Volume		Cumulative Storage Volume		Total Cumulative Storage Volume		Stage / Area		Elevation	
In	mm	ft³	m³	ft3	m3	ft²	m²	ft²	m³	ft³	m³	ft²	m²	ft	m
30.5	775	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	12299.19	348.27	3762.50	349.54	266.54	264.77
29.5	749	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	11985.65	339.40	3762.50	349.54	266.46	264.75
28.5	724	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	11672.10	330.52	3762.50	349.54	266.38	264.72
27.5	699	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	11358.56	321.64	3762.50	349.54	266.29	264.70
26.5	673	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	11045.02	312.76	3762.50	349.54	266.21	264.67
25.5	648	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	10731.48	303.88	3762.50	349.54	266.13	264.65
24.5	622	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	10417.94	295.00	3762.50	349.54	266.04	264.62
23.5	597	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	10104.40	286.12	3762.50	349.54	265.96	264.60
22.5	572	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	9790.85	277.25	3762.50	349.54	265.88	264.57
21.5	546	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	9477.31	268.37	3762.50	349.54	265.79	264.55
20.5	521	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	9163.77	259.49	3762.50	349.54	265.71	264.52
19.5	495	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	8850.23	250.61	3762.50	349.54	265.63	264.50
18.5	470	0.2	0.0	0.0	0.0	156.7	4.4	156.916	4.4	8536.69	241.73	1882.99	174.93	265.54	264.47
18.0	457	58.1	1.6	0.0	0.0	290.3	8.2	348.418	9.9	8379.77	237.29	4181.02	388.42	265.50	264.46
17.0	432	162.3	4.6	0.0	0.0	248.6	7.0	410.906	11.6	8031.35	227.42	4930.87	458.08	265.42	264.43
16.0	406	266.4	7.5	0.0	0.0	207.0	5.9	473.934	13.4	7620.45	215.79	5680.72	527.74	265.33	264.41
15.0	381	336.7	9.5	0.0	0.0	178.9	5.1	515.536	14.6	7147.05	202.38	6186.44	574.72	265.25	264.38
14.0	356	385.1	10.9	0.0	0.0	159.5	4.5	544.612	15.4	6631.52	187.78	6539.35	607.13	265.17	264.36
13.0	330	421.4	11.9	0.1	0.0	145.0	4.1	566.472	16.0	6086.90	172.36	6797.66	631.50	265.08	264.33
12.0	305	445.6	12.6	0.3	0.0	135.3	3.8	581.197	16.5	5520.43	156.32	6974.36	647.92	265.00	264.30
11.0	279	465.0	13.2	0.4	0.0	127.5	3.6	592.911	16.8	4939.24	139.86	7114.94	660.98	264.92	264.28
10.0	254	491.7	13.9	0.4	0.0	116.9	3.3	608.932	17.2	4346.32	123.07	7307.19	678.84	264.83	264.25
9.0	229	491.7	13.9	0.4	0.0	116.9	3.3	608.953	17.2	3737.39	105.83	7307.44	678.86	264.75	264.23
8.0	203	491.7	13.9	0.4	0.0	116.9	3.3	608.974	17.2	3128.44	88.59	7307.69	678.88	264.67	264.20
7.0	178	540.1	15.3	0.6	0.0	97.5	2.8	638.214	18.1	2519.46	71.34	7658.57	711.48	264.58	264.18
6.0	152	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	1881.25	53.27	3762.50	349.54	264.50	264.15
5.0	127	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	1567.71	44.39	3762.50	349.54	264.42	264.13
4.0	102	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	1254.17	35.51	3762.50	349.54	264.33	264.10
3.0	76	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	940.63	26.64	3762.50	349.54	264.25	264.08
2.0	51	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	627.08	17.76	3762.50	349.54	264.17	264.05
1.0	25	0.0	0.0	0.0	0.0	313.5	8.9	313.542	8.9	313.54	8.88	3762.50	349.54	264.08	264.03
0.0	0	0.0	0.0	0.0	0.0	0.0	0.0	0.000	0.0	0.00	0.00	0.00	0.00	264.00	264.00
-1.0															
-2.0															
-3.0															
-4.0															
-5.0															
-6.0															
-7.0															
-8.0															
-9.0															
-10.0															
-11.0															
-12.0															
-13.0															
-14.0															
-15.0															
-16.0															
-17.0															
-18.0															
-19.0															
-20.0															
-21.0															
-22.0															
-23.0															
-24.0															
-25.0															
-26.0															
-27.0															
-28.0															
-29.0															
-30.0															
-31.0															
-32.0															
-33.0															
-34.0															
-35.0															
-36.0															
-37.0															
-38.0															
-39.0															
-40.0															
-41.0															
-42.0															
-43.0															
-44.0															
-45.0															
-46.0															
-47.0															
-48.0															
-49.0															
-50.0															
-51.0															
-52.0															
-53.0															
-54.0															
-55.0															
-56.0															
-57.0															
-58.0															
-59.0															
-60.0															
-61.0															
-62.0															
-63.0															
-64.0															
-65.0															

Stormceptor® EF Sizing Report

Imbrium® Systems

ESTIMATED NET ANNUAL SEDIMENT (TSS) LOAD REDUCTION

09/18/2024

Province:	Ontario
City:	Caledon
Nearest Rainfall Station:	TRENTON AP
Climate Station Id:	6158875
Years of Rainfall Data:	19

Project Name:	Fieldgate Caledon
Project Number:	24045
Designer Name:	Theodor Gheonea
Designer Company:	KWA Site Development Consulting Inc.
Designer Email:	theo.gheonea@kwasitedev.com
Designer Phone:	647-886-0146
EOR Name:	
EOR Company:	
EOR Email:	
EOR Phone:	

Site Name:	
------------	--

Drainage Area (ha):	7.27
---------------------	------

Runoff Coefficient 'c':	0.90
-------------------------	------

Particle Size Distribution:	Fine
-----------------------------	------

Target TSS Removal (%):	80.0
-------------------------	------

Required Water Quality Runoff Volume Capture (%):	
Estimated Water Quality Flow Rate (L/s):	191.39
Oil / Fuel Spill Risk Site?	Yes
Upstream Flow Control?	Yes
Upstream Orifice Control Flow Rate to Stormceptor (L/s):	402.00
Peak Conveyance (maximum) Flow Rate (L/s):	
Influent TSS Concentration (mg/L):	
Estimated Average Annual Sediment Volume (L/yr):	6773

Net Annual Sediment (TSS) Load Reduction Sizing Summary	
Stormceptor Model	TSS Removal Provided (%)
EFO4	35
EFO6	52
EFO8	63
EFO10	72
EFO12	81

Recommended Stormceptor EFO Model: **EFO12**

Estimated Net Annual Sediment (TSS) Load Reduction (%): **81**

Water Quality Runoff Volume Capture (%): **> 90**



Stormceptor® **EF** Sizing Report

THIRD-PARTY TESTING AND VERIFICATION

► Stormceptor® EF and Stormceptor® EFO are the latest evolutions in the Stormceptor® oil-grit separator (OGS) technology series, and are designed to remove a wide variety of pollutants from stormwater and snowmelt runoff. These technologies have been third-party tested in accordance with the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators** and performance has been third-party verified in accordance with the **ISO 14034 Environmental Technology Verification (ETV)** protocol.

PERFORMANCE

► Stormceptor® EF and EFO remove stormwater pollutants through gravity separation and floatation, and feature a patent-pending design that generates positive removal of total suspended solids (TSS) throughout each storm event, including high-intensity storms. Captured pollutants include sediment, free oils, and sediment-bound pollutants such as nutrients, heavy metals, and petroleum hydrocarbons. Stormceptor is sized to remove a high level of TSS from the frequent rainfall events that contribute the vast majority of annual runoff volume and pollutant load. The technology incorporates an internal bypass to convey excessive stormwater flows from high-intensity storms through the device without resuspension and washout (scour) of previously captured pollutants. Proper routine maintenance ensures high pollutant removal performance and protection of downstream waterways.

PARTICLE SIZE DISTRIBUTION (PSD)

► The Canadian ETV PSD shown in the table below was used, or in part, for this sizing. This is the identical PSD that is referenced in the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators** for both sediment removal testing and scour testing. The Canadian ETV PSD contains a wide range of particle sizes in the sand and silt fractions, and is considered reasonably representative of the particle size fractions found in typical urban stormwater runoff.

Particle Size (µm)	Percent Less Than	Particle Size Fraction (µm)	Percent
1000	100	500-1000	5
500	95	250-500	5
250	90	150-250	15
150	75	100-150	15
100	60	75-100	10
75	50	50-75	5
50	45	20-50	10
20	35	8-20	15
8	20	5-8	10
5	10	2-5	5
2	5	<2	5

Stormceptor®EF Sizing Report

Upstream Flow Controlled Results


Rainfall Intensity (mm / hr)	Percent Rainfall Volume (%)	Cumulative Rainfall Volume (%)	Flow Rate (L/s)	Flow Rate (L/min)	Surface Loading Rate (L/min/m²)	Removal Efficiency (%)	Incremental Removal (%)	Cumulative Removal (%)
0.50	8.6	8.6	9.09	546.0	44.0	100	8.6	8.6
1.00	20.8	29.4	18.19	1091.0	87.0	98	20.5	29.1
2.00	17.2	46.7	36.38	2183.0	175.0	87	15.0	44.1
3.00	12.9	59.5	54.57	3274.0	262.0	80	10.3	54.4
4.00	8.8	68.3	72.76	4365.0	349.0	76	6.7	61.1
5.00	6.6	74.9	90.95	5457.0	437.0	72	4.8	65.9
6.00	4.5	79.4	109.14	6548.0	524.0	68	3.1	69.0
7.00	4.2	83.6	127.33	7640.0	611.0	65	2.7	71.7
8.00	2.8	86.5	145.52	8731.0	698.0	64	1.8	73.5
9.00	1.7	88.2	163.71	9822.0	786.0	63	1.1	74.6
10.00	1.3	89.5	181.90	10914.0	873.0	63	0.8	75.4
11.00	1.0	90.5	200.08	12005.0	960.0	62	0.6	76.0
12.00	1.8	92.3	218.27	13096.0	1048.0	61	1.1	77.1
13.00	0.9	93.3	236.46	14188.0	1135.0	59	0.5	77.7
14.00	0.5	93.8	254.65	15279.0	1222.0	56	0.3	78.0
15.00	0.4	94.2	272.84	16371.0	1310.0	54	0.2	78.2
16.00	0.4	94.6	291.03	17462.0	1397.0	53	0.2	78.4
17.00	0.6	95.2	309.22	18553.0	1484.0	49	0.3	78.7
18.00	0.3	95.6	327.41	19645.0	1572.0	47	0.2	78.9
19.00	0.0	95.6	345.60	20736.0	1659.0	44	0.0	78.9
20.00	0.5	96.1	363.79	21827.0	1746.0	42	0.2	79.1
21.00	0.8	96.9	381.98	22919.0	1834.0	40	0.3	79.4
22.00	3.1	100.0	400.17	24010.0	1921.0	38	1.2	80.6
23.00	0.0	100.0	402.00	24120.0	1930.0	38	0.0	80.6
24.00	0.0	100.0	402.00	24120.0	1930.0	38	0.0	80.6
25.00	0.0	100.0	402.00	24120.0	1930.0	38	0.0	80.6
30.00	0.0	100.0	402.00	24120.0	1930.0	38	0.0	80.6
35.00	0.0	100.0	402.00	24120.0	1930.0	38	0.0	80.6
40.00	0.0	100.0	402.00	24120.0	1930.0	38	0.0	80.6
45.00	0.0	100.0	402.00	24120.0	1930.0	38	0.0	80.6
Estimated Net Annual Sediment (TSS) Load Reduction =								81 %

Climate Station ID: 6158875 Years of Rainfall Data: 19




Stormceptor® EF Sizing Report

RAINFALL DATA FROM TRENTON AP RAINFALL STATION



INCREMENTAL AND CUMULATIVE TSS REMOVAL FOR THE RECOMMENDED STORMCEPTOR® MODEL



Stormceptor® EF Sizing Report

Maximum Pipe Diameter / Peak Conveyance

Stormceptor EF / EFO	Model Diameter		Min Angle Inlet / Outlet Pipes	Max Inlet Pipe Diameter		Max Outlet Pipe Diameter		Peak Conveyance Flow Rate	
	(m)	(ft)		(mm)	(in)	(mm)	(in)	(L/s)	(cfs)
EF4 / EFO4	1.2	4	90	609	24	609	24	425	15
EF6 / EFO6	1.8	6	90	914	36	914	36	990	35
EF8 / EFO8	2.4	8	90	1219	48	1219	48	1700	60
EF10 / EFO10	3.0	10	90	1828	72	1828	72	2830	100
EF12 / EFO12	3.6	12	90	1828	72	1828	72	2830	100

SCOUR PREVENTION AND ONLINE CONFIGURATION


► Stormceptor® EF and EFO feature an internal bypass and superior scour prevention technology that have been demonstrated in third-party testing according to the scour testing provisions of the Canadian ETV Procedure for Laboratory Testing of Oil-Grit Separators, and the exceptional scour test performance has been third-party verified in accordance with the ISO 14034 ETV protocol. As a result, Stormceptor EF and EFO are approved for online installation, eliminating the need for costly additional bypass structures, piping, and installation expense.

DESIGN FLEXIBILITY


► Stormceptor® EF and EFO offers design flexibility in one simplified platform, accepting stormwater flow from a single inlet pipe or multiple inlet pipes, and/or surface runoff through an inlet grate. The device can also serve as a junction structure, accommodate a 90-degree inlet-to-outlet bend angle, and can be modified to ensure performance in submerged conditions.

OIL CAPTURE AND RETENTION

► While Stormceptor® EF will capture and retain oil from dry weather spills and low intensity runoff, Stormceptor® EFO has demonstrated superior oil capture and greater than 99% oil retention in third-party testing according to the light liquid re-entrainment testing provisions of the Canadian ETV Procedure for Laboratory Testing of Oil-Grit Separators. Stormceptor EFO is recommended for sites where oil capture and retention is a requirement.



Stormceptor® EF Sizing Report



INLET-TO-OUTLET DROP

Elevation differential between inlet and outlet pipe inverts is dictated by the angle at which the inlet pipe(s) enters the unit.

0° - 45° : The inlet pipe is 1-inch (25mm) higher than the outlet pipe.

45° - 90° : The inlet pipe is 2-inches (50mm) higher than the outlet pipe.

HEAD LOSS

The head loss through Stormceptor EF is similar to that of a 60-degree bend structure. The applicable K value for calculating minor losses through the unit is 1.1. For submerged conditions the applicable K value is 3.0.

Pollutant Capacity

Stormceptor EF / EFO	Model Diameter		Depth (Outlet Pipe Invert to Sump Floor)		Oil Volume		Recommended Sediment Maintenance Depth *		Maximum Sediment Volume *		Maximum Sediment Mass **	
	(m)	(ft)	(m)	(ft)	(L)	(Gal)	(mm)	(in)	(L)	(ft³)	(kg)	(lb)
EF4 / EFO4	1.2	4	1.52	5.0	265	70	203	8	1190	42	1904	5250
EF6 / EFO6	1.8	6	1.93	6.3	610	160	305	12	3470	123	5552	15375
EF8 / EFO8	2.4	8	2.59	8.5	1070	280	610	24	8780	310	14048	38750
EF10 / EFO10	3.0	10	3.25	10.7	1670	440	610	24	17790	628	28464	78500
EF12 / EFO12	3.6	12	3.89	12.8	2475	655	610	24	31220	1103	49952	137875

*Increased sump depth may be added to increase sediment storage capacity

** Average density of wet packed sediment in sump = 1.6 kg/L (100 lb/ft³)

Feature	Benefit	Feature Appeals To
Patent-pending enhanced flow treatment and scour prevention technology	Superior, verified third-party performance	Regulator, Specifying & Design Engineer
Third-party verified light liquid capture and retention for EFO version	Proven performance for fuel/oil hotspot locations	Regulator, Specifying & Design Engineer, Site Owner
Functions as bend, junction or inlet structure	Design flexibility	Specifying & Design Engineer
Minimal drop between inlet and outlet	Site installation ease	Contractor
Large diameter outlet riser for inspection and maintenance	Easy maintenance access from grade	Maintenance Contractor & Site Owner

STANDARD STORMCEPTOR EF/EFO DRAWINGS

For standard details, please visit <http://www.imbriumsystems.com/stormwater-treatment-solutions/stormceptor-ef>

STANDARD STORMCEPTOR EF/EFO SPECIFICATION

For specifications, please visit <http://www.imbriumsystems.com/stormwater-treatment-solutions/stormceptor-ef>

**STANDARD PERFORMANCE SPECIFICATION FOR
“OIL GRIT SEPARATOR” (OGS) STORMWATER QUALITY TREATMENT DEVICE**

PART 1 – GENERAL

1.1 WORK INCLUDED

This section specifies requirements for selecting, sizing, and designing an underground Oil Grit Separator (OGS) device for stormwater quality treatment, with third-party testing results and a Statement of Verification in accordance with ISO 14034 Environmental Management – Environmental Technology Verification (ETV).

1.2 REFERENCE STANDARDS & PROCEDURES

ISO 14034:2016 Environmental management – Environmental technology verification (ETV)

Canadian Environmental Technology Verification (ETV) Program’s **Procedure for Laboratory Testing of Oil-Grit Separators**

1.3 SUBMITTALS

1.3.1 All submittals, including sizing reports & shop drawings, shall be submitted upon request with each order to the contractor then forwarded to the Engineer of Record for review and acceptance. Shop drawings shall detail all OGS components, elevations, and sequence of construction.

1.3.2 Alternative devices shall have features identical to or greater than the specified device, including: treatment chamber diameter, treatment chamber wet volume, sediment storage volume, and oil storage volume.

1.3.3 Unless directed otherwise by the Engineer of Record, OGS stormwater quality treatment product substitutions or alternatives submitted within ten days prior to project bid shall not be accepted. All alternatives or substitutions submitted shall be signed and sealed by a local registered Professional Engineer, based on the exact same criteria detailed in Section 3, in entirety, subject to review and approval by the Engineer of Record.

PART 2 – PRODUCTS

2.1 OGS POLLUTANT STORAGE

The OGS device shall include a sump for sediment storage, and a protected volume for the capture and storage of petroleum hydrocarbons and buoyant gross pollutants. The minimum sediment & petroleum hydrocarbon storage capacity shall be as follows:

2.1.1	4 ft (1219 mm) Diameter OGS Units:	1.19 m ³ sediment / 265 L oil
	6 ft (1829 mm) Diameter OGS Units:	3.48 m ³ sediment / 609 L oil
	8 ft (2438 mm) Diameter OGS Units:	8.78 m ³ sediment / 1,071 L oil
	10 ft (3048 mm) Diameter OGS Units:	17.78 m ³ sediment / 1,673 L oil
	12 ft (3657 mm) Diameter OGS Units:	31.23 m ³ sediment / 2,476 L oil

PART 3 – PERFORMANCE & DESIGN

3.1 GENERAL

The OGS stormwater quality treatment device shall be verified in accordance with ISO 14034:2016 Environmental management – Environmental technology verification (ETV). The OGS stormwater quality treatment device shall



Stormceptor® EF Sizing Report

remove oil, sediment and gross pollutants from stormwater runoff during frequent wet weather events, and retain these pollutants during less frequent high flow wet weather events below the insert within the OGS for later removal during maintenance. The Manufacturer shall have at least ten (10) years of local experience, history and success in engineering design, manufacturing and production and supply of OGS stormwater quality treatment device systems, acceptable to the Engineer of Record.

3.2 SIZING METHODOLOGY

The OGS device shall be engineered, designed and sized to provide stormwater quality treatment based on treating a minimum of 90 percent of the average annual runoff volume and a minimum removal of an annual average 60% of the sediment (TSS) load based on the Particle Size Distribution (PSD) specified in the sizing report for the specified device. Sizing of the OGS shall be determined by use of a minimum ten (10) years of local historical rainfall data provided by Environment Canada. Sizing shall also be determined by use of the sediment removal performance data derived from the ISO 14034 ETV third-party verified laboratory testing data from testing conducted in accordance with the Canadian ETV protocol Procedure for Laboratory Testing of Oil-Grit Separators, as follows:

3.2.1 Sediment removal efficiency for a given surface loading rate and its associated flow rate shall be based on sediment removal efficiency demonstrated at the seven (7) tested surface loading rates specified in the protocol, ranging 40 L/min/m² to 1400 L/min/m², and as stated in the ISO 14034 ETV Verification Statement for the OGS device.

3.2.2 Sediment removal efficiency for surface loading rates between 40 L/min/m² and 1400 L/min/m² shall be based on linear interpolation of data between consecutive tested surface loading rates.

3.2.3 Sediment removal efficiency for surface loading rates less than the lowest tested surface loading rate of 40 L/min/m² shall be assumed to be identical to the sediment removal efficiency at 40 L/min/m². No extrapolation shall be allowed that results in a sediment removal efficiency that is greater than that demonstrated at 40 L/min/m².

3.2.4 Sediment removal efficiency for surface loading rates greater than the highest tested surface loading rate of 1400 L/min/m² shall assume zero sediment removal for the portion of flow that exceeds 1400 L/min/m², and shall be calculated using a simple proportioning formula, with 1400 L/min/m² in the numerator and the higher surface loading rate in the denominator, and multiplying the resulting fraction times the sediment removal efficiency at 1400 L/min/m².

The OGS device shall also have sufficient annual sediment storage capacity as specified and calculated in Section 2.1.

3.3 CANADIAN ETV or ISO 14034 ETV VERIFICATION OF SCOUR TESTING

The OGS device shall have Canadian ETV or ISO 14034 ETV Verification of third-party scour testing conducted in accordance with the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**.

3.3.1 To be acceptable for on-line installation, the OGS device must demonstrate an average scour test effluent concentration less than 10 mg/L at each surface loading rate tested, up to and including 2600 L/min/m².

3.4 LIGHT LIQUID RE-ENTRAINMENT SIMULATION TESTING

The OGS device shall have Canadian ETV or ISO 14034 ETV Verification of completed third-party Light Liquid Re-entrainment Simulation Testing in accordance with the Canadian ETV **Program's Procedure for Laboratory Testing of Oil-Grit Separators**, with results reported within the Canadian ETV or ISO 14034 ETV verification. This re-entrainment testing is conducted with the device pre-loaded with low density polyethylene (LDPE) plastic beads as a surrogate for light liquids such as oil and fuel. Testing is conducted on the same OGS unit tested for sediment removal to

Stormceptor® **EF** Sizing Report

assess whether light liquids captured after a spill are effectively retained at high flow rates.

3.4.1 For an OGS device to be an acceptable stormwater treatment device on a site where vehicular traffic occurs and the potential for an oil or fuel spill exists, the OGS device must have reported verified performance results of greater than 99% cumulative retention of LDPE plastic beads for the five specified surface loading rates (ranging 200 L/min/m² to 2600 L/min/m²) in accordance with the Light Liquid Re-entrainment Simulation Testing within the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**. However, an OGS device shall not be allowed if the Light Liquid Re-entrainment Simulation Testing was performed with screening components within the OGS device that are effective at retaining the LDPE plastic beads, but would not be expected to retain light liquids such as oil and fuel.

Stormceptor® EF Sizing Report

Imbrium® Systems

ESTIMATED NET ANNUAL SEDIMENT (TSS) LOAD REDUCTION

09/18/2024

Province:	Ontario
City:	Caledon
Nearest Rainfall Station:	TORONTO INTL AP
Climate Station Id:	6158731
Years of Rainfall Data:	20

Project Name:	Fieldgate Caledon - B
Project Number:	24045
Designer Name:	Theodor Gheonea
Designer Company:	KWA Site Development Consulting Inc.
Designer Email:	theo.gheonea@kwasitedev.com
Designer Phone:	647-886-0146
EOR Name:	
EOR Company:	
EOR Email:	
EOR Phone:	

Site Name:	
------------	--

Drainage Area (ha):	2.49
---------------------	------

Runoff Coefficient 'c':	0.90
-------------------------	------

Particle Size Distribution:	Fine
-----------------------------	------

Target TSS Removal (%):	80.0
-------------------------	------

Required Water Quality Runoff Volume Capture (%):	
Estimated Water Quality Flow Rate (L/s):	69.69
Oil / Fuel Spill Risk Site?	Yes
Upstream Flow Control?	Yes
Upstream Orifice Control Flow Rate to Stormceptor (L/s):	136.00
Peak Conveyance (maximum) Flow Rate (L/s):	
Influent TSS Concentration (mg/L):	
Estimated Average Annual Sediment Volume (L/yr):	2013

Net Annual Sediment (TSS) Load Reduction Sizing Summary	
Stormceptor Model	TSS Removal Provided (%)
EFO4	56
EFO6	72
EFO8	81
EFO10	87
EFO12	92

Recommended Stormceptor EFO Model: **EFO8**

Estimated Net Annual Sediment (TSS) Load Reduction (%): **81**

Water Quality Runoff Volume Capture (%): **> 90**



Stormceptor® **EF** Sizing Report

THIRD-PARTY TESTING AND VERIFICATION

► Stormceptor® EF and Stormceptor® EFO are the latest evolutions in the Stormceptor® oil-grit separator (OGS) technology series, and are designed to remove a wide variety of pollutants from stormwater and snowmelt runoff. These technologies have been third-party tested in accordance with the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators** and performance has been third-party verified in accordance with the **ISO 14034 Environmental Technology Verification (ETV)** protocol.

PERFORMANCE

► Stormceptor® EF and EFO remove stormwater pollutants through gravity separation and floatation, and feature a patent-pending design that generates positive removal of total suspended solids (TSS) throughout each storm event, including high-intensity storms. Captured pollutants include sediment, free oils, and sediment-bound pollutants such as nutrients, heavy metals, and petroleum hydrocarbons. Stormceptor is sized to remove a high level of TSS from the frequent rainfall events that contribute the vast majority of annual runoff volume and pollutant load. The technology incorporates an internal bypass to convey excessive stormwater flows from high-intensity storms through the device without resuspension and washout (scour) of previously captured pollutants. Proper routine maintenance ensures high pollutant removal performance and protection of downstream waterways.

PARTICLE SIZE DISTRIBUTION (PSD)

► The Canadian ETV PSD shown in the table below was used, or in part, for this sizing. This is the identical PSD that is referenced in the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators** for both sediment removal testing and scour testing. The Canadian ETV PSD contains a wide range of particle sizes in the sand and silt fractions, and is considered reasonably representative of the particle size fractions found in typical urban stormwater runoff.

Particle Size (µm)	Percent Less Than	Particle Size Fraction (µm)	Percent
1000	100	500-1000	5
500	95	250-500	5
250	90	150-250	15
150	75	100-150	15
100	60	75-100	10
75	50	50-75	5
50	45	20-50	10
20	35	8-20	15
8	20	5-8	10
5	10	2-5	5
2	5	<2	5

Stormceptor® EF Sizing Report

Upstream Flow Controlled Results


Rainfall Intensity (mm / hr)	Percent Rainfall Volume (%)	Cumulative Rainfall Volume (%)	Flow Rate (L/s)	Flow Rate (L/min)	Surface Loading Rate (L/min/m²)	Removal Efficiency (%)	Incremental Removal (%)	Cumulative Removal (%)
0.50	8.5	8.5	3.11	187.0	40.0	100	8.5	8.5
1.00	20.6	29.1	6.23	374.0	80.0	98	20.3	28.8
2.00	16.8	45.9	12.46	748.0	159.0	88	14.8	43.7
3.00	10.8	56.7	18.69	1121.0	239.0	82	8.8	52.4
4.00	8.5	65.2	24.92	1495.0	318.0	78	6.6	59.0
5.00	6.4	71.6	31.15	1869.0	398.0	74	4.8	63.8
6.00	5.5	77.0	37.38	2243.0	477.0	71	3.9	67.6
7.00	3.9	81.0	43.61	2617.0	557.0	67	2.6	70.3
8.00	2.9	83.9	49.84	2990.0	636.0	64	1.9	72.1
9.00	2.7	86.5	56.07	3364.0	716.0	64	1.7	73.9
10.00	2.2	88.7	62.30	3738.0	795.0	63	1.4	75.2
11.00	1.0	89.7	68.53	4112.0	875.0	63	0.6	75.8
12.00	1.7	91.3	74.76	4486.0	954.0	62	1.0	76.9
13.00	1.4	92.8	80.99	4859.0	1034.0	61	0.9	77.7
14.00	1.0	93.7	87.22	5233.0	1113.0	59	0.6	78.3
15.00	0.3	94.0	93.45	5607.0	1193.0	57	0.2	78.5
16.00	0.8	94.8	99.68	5981.0	1273.0	55	0.4	78.9
17.00	0.8	95.7	105.91	6355.0	1352.0	53	0.4	79.4
18.00	0.2	95.8	112.14	6728.0	1432.0	51	0.1	79.4
19.00	1.5	97.3	118.37	7102.0	1511.0	48	0.7	80.2
20.00	0.2	97.5	124.60	7476.0	1591.0	46	0.1	80.3
21.00	2.5	100.0	130.83	7850.0	1670.0	44	1.1	81.3
22.00	0.0	100.0	136.00	8160.0	1736.0	42	0.0	81.3
23.00	0.0	100.0	136.00	8160.0	1736.0	42	0.0	81.3
24.00	0.0	100.0	136.00	8160.0	1736.0	42	0.0	81.3
25.00	0.0	100.0	136.00	8160.0	1736.0	42	0.0	81.3
30.00	0.0	100.0	136.00	8160.0	1736.0	42	0.0	81.3
35.00	0.0	100.0	136.00	8160.0	1736.0	42	0.0	81.3
40.00	0.0	100.0	136.00	8160.0	1736.0	42	0.0	81.3
45.00	0.0	100.0	136.00	8160.0	1736.0	42	0.0	81.3
Estimated Net Annual Sediment (TSS) Load Reduction =								81 %

Climate Station ID: 6158731 Years of Rainfall Data: 20




Stormceptor® EF Sizing Report

RAINFALL DATA FROM TORONTO INTL AP RAINFALL STATION



INCREMENTAL AND CUMULATIVE TSS REMOVAL FOR THE RECOMMENDED STORMCEPTOR® MODEL



Stormceptor® **EF** Sizing Report

Maximum Pipe Diameter / Peak Conveyance

Stormceptor EF / EFO	Model Diameter		Min Angle Inlet / Outlet Pipes	Max Inlet Pipe Diameter		Max Outlet Pipe Diameter		Peak Conveyance Flow Rate	
	(m)	(ft)		(mm)	(in)	(mm)	(in)	(L/s)	(cfs)
EF4 / EFO4	1.2	4	90	609	24	609	24	425	15
EF6 / EFO6	1.8	6	90	914	36	914	36	990	35
EF8 / EFO8	2.4	8	90	1219	48	1219	48	1700	60
EF10 / EFO10	3.0	10	90	1828	72	1828	72	2830	100
EF12 / EFO12	3.6	12	90	1828	72	1828	72	2830	100

SCOUR PREVENTION AND ONLINE CONFIGURATION


► Stormceptor® EF and EFO feature an internal bypass and superior scour prevention technology that have been demonstrated in third-party testing according to the scour testing provisions of the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators**, and the exceptional scour test performance has been third-party verified in accordance with the ISO 14034 ETV protocol. As a result, Stormceptor EF and EFO are approved for online installation, eliminating the need for costly additional bypass structures, piping, and installation expense.

DESIGN FLEXIBILITY


► Stormceptor® EF and EFO offers design flexibility in one simplified platform, accepting stormwater flow from a single inlet pipe or multiple inlet pipes, and/or surface runoff through an inlet grate. The device can also serve as a junction structure, accommodate a 90-degree inlet-to-outlet bend angle, and can be modified to ensure performance in submerged conditions.

OIL CAPTURE AND RETENTION

► While Stormceptor® EF will capture and retain oil from dry weather spills and low intensity runoff, Stormceptor® EFO has demonstrated superior oil capture and greater than 99% oil retention in third-party testing according to the light liquid re-entrainment testing provisions of the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators**. Stormceptor EFO is recommended for sites where oil capture and retention is a requirement.



Stormceptor® EF Sizing Report



INLET-TO-OUTLET DROP

Elevation differential between inlet and outlet pipe inverts is dictated by the angle at which the inlet pipe(s) enters the unit.

0° - 45° : The inlet pipe is 1-inch (25mm) higher than the outlet pipe.

45° - 90° : The inlet pipe is 2-inches (50mm) higher than the outlet pipe.

HEAD LOSS

The head loss through Stormceptor EF is similar to that of a 60-degree bend structure.

The applicable K value for calculating minor losses through the unit is 1.1.

For submerged conditions the applicable K value is 3.0.

Pollutant Capacity

Stormceptor EF / EFO	Model Diameter		Depth (Outlet Pipe Invert to Sump Floor)		Oil Volume		Recommended Sediment Maintenance Depth *		Maximum Sediment Volume *		Maximum Sediment Mass **	
	(m)	(ft)	(m)	(ft)	(L)	(Gal)	(mm)	(in)	(L)	(ft³)	(kg)	(lb)
EF4 / EFO4	1.2	4	1.52	5.0	265	70	203	8	1190	42	1904	5250
EF6 / EFO6	1.8	6	1.93	6.3	610	160	305	12	3470	123	5552	15375
EF8 / EFO8	2.4	8	2.59	8.5	1070	280	610	24	8780	310	14048	38750
EF10 / EFO10	3.0	10	3.25	10.7	1670	440	610	24	17790	628	28464	78500
EF12 / EFO12	3.6	12	3.89	12.8	2475	655	610	24	31220	1103	49952	137875

*Increased sump depth may be added to increase sediment storage capacity

** Average density of wet packed sediment in sump = 1.6 kg/L (100 lb/ft³)

Feature	Benefit	Feature Appeals To
Patent-pending enhanced flow treatment and scour prevention technology	Superior, verified third-party performance	Regulator, Specifying & Design Engineer
Third-party verified light liquid capture and retention for EFO version	Proven performance for fuel/oil hotspot locations	Regulator, Specifying & Design Engineer, Site Owner
Functions as bend, junction or inlet structure	Design flexibility	Specifying & Design Engineer
Minimal drop between inlet and outlet	Site installation ease	Contractor
Large diameter outlet riser for inspection and maintenance	Easy maintenance access from grade	Maintenance Contractor & Site Owner

STANDARD STORMCEPTOR EF/EFO DRAWINGS

For standard details, please visit <http://www.imbriumsystems.com/stormwater-treatment-solutions/stormceptor-ef>

STANDARD STORMCEPTOR EF/EFO SPECIFICATION

For specifications, please visit <http://www.imbriumsystems.com/stormwater-treatment-solutions/stormceptor-ef>

**STANDARD PERFORMANCE SPECIFICATION FOR
“OIL GRIT SEPARATOR” (OGS) STORMWATER QUALITY TREATMENT DEVICE**

PART 1 – GENERAL

1.1 WORK INCLUDED

This section specifies requirements for selecting, sizing, and designing an underground Oil Grit Separator (OGS) device for stormwater quality treatment, with third-party testing results and a Statement of Verification in accordance with ISO 14034 Environmental Management – Environmental Technology Verification (ETV).

1.2 REFERENCE STANDARDS & PROCEDURES

ISO 14034:2016 Environmental management – Environmental technology verification (ETV)

Canadian Environmental Technology Verification (ETV) Program’s **Procedure for Laboratory Testing of Oil-Grit Separators**

1.3 SUBMITTALS

1.3.1 All submittals, including sizing reports & shop drawings, shall be submitted upon request with each order to the contractor then forwarded to the Engineer of Record for review and acceptance. Shop drawings shall detail all OGS components, elevations, and sequence of construction.

1.3.2 Alternative devices shall have features identical to or greater than the specified device, including: treatment chamber diameter, treatment chamber wet volume, sediment storage volume, and oil storage volume.

1.3.3 Unless directed otherwise by the Engineer of Record, OGS stormwater quality treatment product substitutions or alternatives submitted within ten days prior to project bid shall not be accepted. All alternatives or substitutions submitted shall be signed and sealed by a local registered Professional Engineer, based on the exact same criteria detailed in Section 3, in entirety, subject to review and approval by the Engineer of Record.

PART 2 – PRODUCTS

2.1 OGS POLLUTANT STORAGE

The OGS device shall include a sump for sediment storage, and a protected volume for the capture and storage of petroleum hydrocarbons and buoyant gross pollutants. The minimum sediment & petroleum hydrocarbon storage capacity shall be as follows:

2.1.1	4 ft (1219 mm) Diameter OGS Units:	1.19 m ³ sediment / 265 L oil
	6 ft (1829 mm) Diameter OGS Units:	3.48 m ³ sediment / 609 L oil
	8 ft (2438 mm) Diameter OGS Units:	8.78 m ³ sediment / 1,071 L oil
	10 ft (3048 mm) Diameter OGS Units:	17.78 m ³ sediment / 1,673 L oil
	12 ft (3657 mm) Diameter OGS Units:	31.23 m ³ sediment / 2,476 L oil

PART 3 – PERFORMANCE & DESIGN

3.1 GENERAL

The OGS stormwater quality treatment device shall be verified in accordance with ISO 14034:2016 Environmental management – Environmental technology verification (ETV). The OGS stormwater quality treatment device shall



Stormceptor® EF Sizing Report

remove oil, sediment and gross pollutants from stormwater runoff during frequent wet weather events, and retain these pollutants during less frequent high flow wet weather events below the insert within the OGS for later removal during maintenance. The Manufacturer shall have at least ten (10) years of local experience, history and success in engineering design, manufacturing and production and supply of OGS stormwater quality treatment device systems, acceptable to the Engineer of Record.

3.2 SIZING METHODOLOGY

The OGS device shall be engineered, designed and sized to provide stormwater quality treatment based on treating a minimum of 90 percent of the average annual runoff volume and a minimum removal of an annual average 60% of the sediment (TSS) load based on the Particle Size Distribution (PSD) specified in the sizing report for the specified device. Sizing of the OGS shall be determined by use of a minimum ten (10) years of local historical rainfall data provided by Environment Canada. Sizing shall also be determined by use of the sediment removal performance data derived from the ISO 14034 ETV third-party verified laboratory testing data from testing conducted in accordance with the Canadian ETV protocol Procedure for Laboratory Testing of Oil-Grit Separators, as follows:

3.2.1 Sediment removal efficiency for a given surface loading rate and its associated flow rate shall be based on sediment removal efficiency demonstrated at the seven (7) tested surface loading rates specified in the protocol, ranging 40 L/min/m² to 1400 L/min/m², and as stated in the ISO 14034 ETV Verification Statement for the OGS device.

3.2.2 Sediment removal efficiency for surface loading rates between 40 L/min/m² and 1400 L/min/m² shall be based on linear interpolation of data between consecutive tested surface loading rates.

3.2.3 Sediment removal efficiency for surface loading rates less than the lowest tested surface loading rate of 40 L/min/m² shall be assumed to be identical to the sediment removal efficiency at 40 L/min/m². No extrapolation shall be allowed that results in a sediment removal efficiency that is greater than that demonstrated at 40 L/min/m².

3.2.4 Sediment removal efficiency for surface loading rates greater than the highest tested surface loading rate of 1400 L/min/m² shall assume zero sediment removal for the portion of flow that exceeds 1400 L/min/m², and shall be calculated using a simple proportioning formula, with 1400 L/min/m² in the numerator and the higher surface loading rate in the denominator, and multiplying the resulting fraction times the sediment removal efficiency at 1400 L/min/m².

The OGS device shall also have sufficient annual sediment storage capacity as specified and calculated in Section 2.1.

3.3 CANADIAN ETV or ISO 14034 ETV VERIFICATION OF SCOUR TESTING

The OGS device shall have Canadian ETV or ISO 14034 ETV Verification of third-party scour testing conducted in accordance with the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**.

3.3.1 To be acceptable for on-line installation, the OGS device must demonstrate an average scour test effluent concentration less than 10 mg/L at each surface loading rate tested, up to and including 2600 L/min/m².

3.4 LIGHT LIQUID RE-ENTRAINMENT SIMULATION TESTING

The OGS device shall have Canadian ETV or ISO 14034 ETV Verification of completed third-party Light Liquid Re-entrainment Simulation Testing in accordance with the Canadian ETV **Program's Procedure for Laboratory Testing of Oil-Grit Separators**, with results reported within the Canadian ETV or ISO 14034 ETV verification. This re-entrainment testing is conducted with the device pre-loaded with low density polyethylene (LDPE) plastic beads as a surrogate for light liquids such as oil and fuel. Testing is conducted on the same OGS unit tested for sediment removal to

Stormceptor® EF Sizing Report

assess whether light liquids captured after a spill are effectively retained at high flow rates.

3.4.1 For an OGS device to be an acceptable stormwater treatment device on a site where vehicular traffic occurs and the potential for an oil or fuel spill exists, the OGS device must have reported verified performance results of greater than 99% cumulative retention of LDPE plastic beads for the five specified surface loading rates (ranging 200 L/min/m² to 2600 L/min/m²) in accordance with the Light Liquid Re-entrainment Simulation Testing within the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**. However, an OGS device shall not be allowed if the Light Liquid Re-entrainment Simulation Testing was performed with screening components within the OGS device that are effective at retaining the LDPE plastic beads, but would not be expected to retain light liquids such as oil and fuel.

Stormceptor® EF Sizing Report

Imbrium® Systems

ESTIMATED NET ANNUAL SEDIMENT (TSS) LOAD REDUCTION

09/18/2024

Province:	Ontario
City:	Caledon
Nearest Rainfall Station:	TORONTO INTL AP
Climate Station Id:	6158731
Years of Rainfall Data:	20

Project Name:	Fieldgate Caledon - C
Project Number:	24045
Designer Name:	Theodor Gheonea
Designer Company:	KWA Site Development Consulting Inc.
Designer Email:	theo.gheonea@kwasitedev.com
Designer Phone:	647-886-0146
EOR Name:	
EOR Company:	
EOR Email:	
EOR Phone:	

Site Name:

Drainage Area (ha): 2.78

Runoff Coefficient 'c': 0.90

Particle Size Distribution: Fine

Target TSS Removal (%): 80.0

Required Water Quality Runoff Volume Capture (%):	
Estimated Water Quality Flow Rate (L/s):	77.81
Oil / Fuel Spill Risk Site?	Yes
Upstream Flow Control?	Yes
Upstream Orifice Control Flow Rate to Stormceptor (L/s):	139.80
Peak Conveyance (maximum) Flow Rate (L/s):	
Influent TSS Concentration (mg/L):	
Estimated Average Annual Sediment Volume (L/yr):	2220

Net Annual Sediment (TSS) Load Reduction Sizing Summary	
Stormceptor Model	TSS Removal Provided (%)
EFO4	54
EFO6	70
EFO8	80
EFO10	86
EFO12	91

Recommended Stormceptor EFO Model: **EFO8**

Estimated Net Annual Sediment (TSS) Load Reduction (%): **80**

Water Quality Runoff Volume Capture (%): **> 90**



Stormceptor® **EF** Sizing Report

THIRD-PARTY TESTING AND VERIFICATION

► Stormceptor® EF and Stormceptor® EFO are the latest evolutions in the Stormceptor® oil-grit separator (OGS) technology series, and are designed to remove a wide variety of pollutants from stormwater and snowmelt runoff. These technologies have been third-party tested in accordance with the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators** and performance has been third-party verified in accordance with the **ISO 14034 Environmental Technology Verification (ETV)** protocol.

PERFORMANCE

► Stormceptor® EF and EFO remove stormwater pollutants through gravity separation and floatation, and feature a patent-pending design that generates positive removal of total suspended solids (TSS) throughout each storm event, including high-intensity storms. Captured pollutants include sediment, free oils, and sediment-bound pollutants such as nutrients, heavy metals, and petroleum hydrocarbons. Stormceptor is sized to remove a high level of TSS from the frequent rainfall events that contribute the vast majority of annual runoff volume and pollutant load. The technology incorporates an internal bypass to convey excessive stormwater flows from high-intensity storms through the device without resuspension and washout (scour) of previously captured pollutants. Proper routine maintenance ensures high pollutant removal performance and protection of downstream waterways.

PARTICLE SIZE DISTRIBUTION (PSD)

► The Canadian ETV PSD shown in the table below was used, or in part, for this sizing. This is the identical PSD that is referenced in the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators** for both sediment removal testing and scour testing. The Canadian ETV PSD contains a wide range of particle sizes in the sand and silt fractions, and is considered reasonably representative of the particle size fractions found in typical urban stormwater runoff.

Particle Size (µm)	Percent Less Than	Particle Size Fraction (µm)	Percent
1000	100	500-1000	5
500	95	250-500	5
250	90	150-250	15
150	75	100-150	15
100	60	75-100	10
75	50	50-75	5
50	45	20-50	10
20	35	8-20	15
8	20	5-8	10
5	10	2-5	5
2	5	<2	5

Stormceptor® EF Sizing Report

Upstream Flow Controlled Results


Rainfall Intensity (mm / hr)	Percent Rainfall Volume (%)	Cumulative Rainfall Volume (%)	Flow Rate (L/s)	Flow Rate (L/min)	Surface Loading Rate (L/min/m²)	Removal Efficiency (%)	Incremental Removal (%)	Cumulative Removal (%)
0.50	8.5	8.5	3.48	209.0	44.0	100	8.5	8.5
1.00	20.6	29.1	6.96	417.0	89.0	98	20.3	28.8
2.00	16.8	45.9	13.91	835.0	178.0	87	14.6	43.4
3.00	10.8	56.7	20.87	1252.0	266.0	80	8.6	52.1
4.00	8.5	65.2	27.82	1669.0	355.0	76	6.4	58.5
5.00	6.4	71.6	34.78	2087.0	444.0	72	4.6	63.1
6.00	5.5	77.0	41.73	2504.0	533.0	68	3.7	66.8
7.00	3.9	81.0	48.69	2921.0	622.0	64	2.5	69.4
8.00	2.9	83.9	55.64	3339.0	710.0	64	1.8	71.2
9.00	2.7	86.5	62.60	3756.0	799.0	63	1.7	72.9
10.00	2.2	88.7	69.56	4173.0	888.0	62	1.4	74.3
11.00	1.0	89.7	76.51	4591.0	977.0	62	0.6	74.9
12.00	1.7	91.3	83.47	5008.0	1066.0	60	1.0	75.9
13.00	1.4	92.8	90.42	5425.0	1154.0	58	0.8	76.7
14.00	1.0	93.7	97.38	5843.0	1243.0	56	0.5	77.2
15.00	0.3	94.0	104.33	6260.0	1332.0	54	0.2	77.4
16.00	0.8	94.8	111.29	6677.0	1421.0	52	0.4	77.8
17.00	0.8	95.7	118.24	7095.0	1510.0	48	0.4	78.2
18.00	0.2	95.8	125.20	7512.0	1598.0	46	0.1	78.3
19.00	1.5	97.3	132.16	7929.0	1687.0	44	0.7	78.9
20.00	2.7	100.0	139.11	8347.0	1776.0	41	1.1	80.0
21.00	0.0	100.0	140.00	8400.0	1787.0	41	0.0	80.0
22.00	0.0	100.0	140.00	8400.0	1787.0	41	0.0	80.0
23.00	0.0	100.0	140.00	8400.0	1787.0	41	0.0	80.0
24.00	0.0	100.0	140.00	8400.0	1787.0	41	0.0	80.0
25.00	0.0	100.0	140.00	8400.0	1787.0	41	0.0	80.0
30.00	0.0	100.0	140.00	8400.0	1787.0	41	0.0	80.0
35.00	0.0	100.0	140.00	8400.0	1787.0	41	0.0	80.0
40.00	0.0	100.0	140.00	8400.0	1787.0	41	0.0	80.0
45.00	0.0	100.0	140.00	8400.0	1787.0	41	0.0	80.0
Estimated Net Annual Sediment (TSS) Load Reduction =								80 %

Climate Station ID: 6158731 Years of Rainfall Data: 20




Stormceptor® EF Sizing Report

RAINFALL DATA FROM TORONTO INTL AP RAINFALL STATION



INCREMENTAL AND CUMULATIVE TSS REMOVAL FOR THE RECOMMENDED STORMCEPTOR® MODEL



Stormceptor® **EF** Sizing Report

Maximum Pipe Diameter / Peak Conveyance

Stormceptor EF / EFO	Model Diameter		Min Angle Inlet / Outlet Pipes	Max Inlet Pipe Diameter		Max Outlet Pipe Diameter		Peak Conveyance Flow Rate	
	(m)	(ft)		(mm)	(in)	(mm)	(in)	(L/s)	(cfs)
EF4 / EFO4	1.2	4	90	609	24	609	24	425	15
EF6 / EFO6	1.8	6	90	914	36	914	36	990	35
EF8 / EFO8	2.4	8	90	1219	48	1219	48	1700	60
EF10 / EFO10	3.0	10	90	1828	72	1828	72	2830	100
EF12 / EFO12	3.6	12	90	1828	72	1828	72	2830	100

SCOUR PREVENTION AND ONLINE CONFIGURATION


► Stormceptor® EF and EFO feature an internal bypass and superior scour prevention technology that have been demonstrated in third-party testing according to the scour testing provisions of the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators**, and the exceptional scour test performance has been third-party verified in accordance with the ISO 14034 ETV protocol. As a result, Stormceptor EF and EFO are approved for online installation, eliminating the need for costly additional bypass structures, piping, and installation expense.

DESIGN FLEXIBILITY


► Stormceptor® EF and EFO offers design flexibility in one simplified platform, accepting stormwater flow from a single inlet pipe or multiple inlet pipes, and/or surface runoff through an inlet grate. The device can also serve as a junction structure, accommodate a 90-degree inlet-to-outlet bend angle, and can be modified to ensure performance in submerged conditions.

OIL CAPTURE AND RETENTION

► While Stormceptor® EF will capture and retain oil from dry weather spills and low intensity runoff, Stormceptor® EFO has demonstrated superior oil capture and greater than 99% oil retention in third-party testing according to the light liquid re-entrainment testing provisions of the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators**. Stormceptor EFO is recommended for sites where oil capture and retention is a requirement.



Stormceptor® EF Sizing Report



INLET-TO-OUTLET DROP

Elevation differential between inlet and outlet pipe inverts is dictated by the angle at which the inlet pipe(s) enters the unit.

0° - 45° : The inlet pipe is 1-inch (25mm) higher than the outlet pipe.

45° - 90° : The inlet pipe is 2-inches (50mm) higher than the outlet pipe.

HEAD LOSS

The head loss through Stormceptor EF is similar to that of a 60-degree bend structure. The applicable K value for calculating minor losses through the unit is 1.1. For submerged conditions the applicable K value is 3.0.

Pollutant Capacity

Stormceptor EF / EFO	Model Diameter		Depth (Outlet Pipe Invert to Sump Floor)		Oil Volume		Recommended Sediment Maintenance Depth *		Maximum Sediment Volume *		Maximum Sediment Mass **	
	(m)	(ft)	(m)	(ft)	(L)	(Gal)	(mm)	(in)	(L)	(ft³)	(kg)	(lb)
EF4 / EFO4	1.2	4	1.52	5.0	265	70	203	8	1190	42	1904	5250
EF6 / EFO6	1.8	6	1.93	6.3	610	160	305	12	3470	123	5552	15375
EF8 / EFO8	2.4	8	2.59	8.5	1070	280	610	24	8780	310	14048	38750
EF10 / EFO10	3.0	10	3.25	10.7	1670	440	610	24	17790	628	28464	78500
EF12 / EFO12	3.6	12	3.89	12.8	2475	655	610	24	31220	1103	49952	137875

*Increased sump depth may be added to increase sediment storage capacity

** Average density of wet packed sediment in sump = 1.6 kg/L (100 lb/ft³)

Feature	Benefit	Feature Appeals To
Patent-pending enhanced flow treatment and scour prevention technology	Superior, verified third-party performance	Regulator, Specifying & Design Engineer
Third-party verified light liquid capture and retention for EFO version	Proven performance for fuel/oil hotspot locations	Regulator, Specifying & Design Engineer, Site Owner
Functions as bend, junction or inlet structure	Design flexibility	Specifying & Design Engineer
Minimal drop between inlet and outlet	Site installation ease	Contractor
Large diameter outlet riser for inspection and maintenance	Easy maintenance access from grade	Maintenance Contractor & Site Owner

STANDARD STORMCEPTOR EF/EFO DRAWINGS

For standard details, please visit <http://www.imbriumsystems.com/stormwater-treatment-solutions/stormceptor-ef>

STANDARD STORMCEPTOR EF/EFO SPECIFICATION

For specifications, please visit <http://www.imbriumsystems.com/stormwater-treatment-solutions/stormceptor-ef>

**STANDARD PERFORMANCE SPECIFICATION FOR
“OIL GRIT SEPARATOR” (OGS) STORMWATER QUALITY TREATMENT DEVICE**

PART 1 – GENERAL

1.1 WORK INCLUDED

This section specifies requirements for selecting, sizing, and designing an underground Oil Grit Separator (OGS) device for stormwater quality treatment, with third-party testing results and a Statement of Verification in accordance with ISO 14034 Environmental Management – Environmental Technology Verification (ETV).

1.2 REFERENCE STANDARDS & PROCEDURES

ISO 14034:2016 Environmental management – Environmental technology verification (ETV)

Canadian Environmental Technology Verification (ETV) Program’s **Procedure for Laboratory Testing of Oil-Grit Separators**

1.3 SUBMITTALS

1.3.1 All submittals, including sizing reports & shop drawings, shall be submitted upon request with each order to the contractor then forwarded to the Engineer of Record for review and acceptance. Shop drawings shall detail all OGS components, elevations, and sequence of construction.

1.3.2 Alternative devices shall have features identical to or greater than the specified device, including: treatment chamber diameter, treatment chamber wet volume, sediment storage volume, and oil storage volume.

1.3.3 Unless directed otherwise by the Engineer of Record, OGS stormwater quality treatment product substitutions or alternatives submitted within ten days prior to project bid shall not be accepted. All alternatives or substitutions submitted shall be signed and sealed by a local registered Professional Engineer, based on the exact same criteria detailed in Section 3, in entirety, subject to review and approval by the Engineer of Record.

PART 2 – PRODUCTS

2.1 OGS POLLUTANT STORAGE

The OGS device shall include a sump for sediment storage, and a protected volume for the capture and storage of petroleum hydrocarbons and buoyant gross pollutants. The minimum sediment & petroleum hydrocarbon storage capacity shall be as follows:

2.1.1	4 ft (1219 mm) Diameter OGS Units:	1.19 m ³ sediment / 265 L oil
	6 ft (1829 mm) Diameter OGS Units:	3.48 m ³ sediment / 609 L oil
	8 ft (2438 mm) Diameter OGS Units:	8.78 m ³ sediment / 1,071 L oil
	10 ft (3048 mm) Diameter OGS Units:	17.78 m ³ sediment / 1,673 L oil
	12 ft (3657 mm) Diameter OGS Units:	31.23 m ³ sediment / 2,476 L oil

PART 3 – PERFORMANCE & DESIGN

3.1 GENERAL

The OGS stormwater quality treatment device shall be verified in accordance with ISO 14034:2016 Environmental management – Environmental technology verification (ETV). The OGS stormwater quality treatment device shall



Stormceptor® EF Sizing Report

remove oil, sediment and gross pollutants from stormwater runoff during frequent wet weather events, and retain these pollutants during less frequent high flow wet weather events below the insert within the OGS for later removal during maintenance. The Manufacturer shall have at least ten (10) years of local experience, history and success in engineering design, manufacturing and production and supply of OGS stormwater quality treatment device systems, acceptable to the Engineer of Record.

3.2 SIZING METHODOLOGY

The OGS device shall be engineered, designed and sized to provide stormwater quality treatment based on treating a minimum of 90 percent of the average annual runoff volume and a minimum removal of an annual average 60% of the sediment (TSS) load based on the Particle Size Distribution (PSD) specified in the sizing report for the specified device. Sizing of the OGS shall be determined by use of a minimum ten (10) years of local historical rainfall data provided by Environment Canada. Sizing shall also be determined by use of the sediment removal performance data derived from the ISO 14034 ETV third-party verified laboratory testing data from testing conducted in accordance with the Canadian ETV protocol Procedure for Laboratory Testing of Oil-Grit Separators, as follows:

3.2.1 Sediment removal efficiency for a given surface loading rate and its associated flow rate shall be based on sediment removal efficiency demonstrated at the seven (7) tested surface loading rates specified in the protocol, ranging 40 L/min/m² to 1400 L/min/m², and as stated in the ISO 14034 ETV Verification Statement for the OGS device.

3.2.2 Sediment removal efficiency for surface loading rates between 40 L/min/m² and 1400 L/min/m² shall be based on linear interpolation of data between consecutive tested surface loading rates.

3.2.3 Sediment removal efficiency for surface loading rates less than the lowest tested surface loading rate of 40 L/min/m² shall be assumed to be identical to the sediment removal efficiency at 40 L/min/m². No extrapolation shall be allowed that results in a sediment removal efficiency that is greater than that demonstrated at 40 L/min/m².

3.2.4 Sediment removal efficiency for surface loading rates greater than the highest tested surface loading rate of 1400 L/min/m² shall assume zero sediment removal for the portion of flow that exceeds 1400 L/min/m², and shall be calculated using a simple proportioning formula, with 1400 L/min/m² in the numerator and the higher surface loading rate in the denominator, and multiplying the resulting fraction times the sediment removal efficiency at 1400 L/min/m².

The OGS device shall also have sufficient annual sediment storage capacity as specified and calculated in Section 2.1.

3.3 CANADIAN ETV or ISO 14034 ETV VERIFICATION OF SCOUR TESTING

The OGS device shall have Canadian ETV or ISO 14034 ETV Verification of third-party scour testing conducted in accordance with the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**.

3.3.1 To be acceptable for on-line installation, the OGS device must demonstrate an average scour test effluent concentration less than 10 mg/L at each surface loading rate tested, up to and including 2600 L/min/m².

3.4 LIGHT LIQUID RE-ENTRAINMENT SIMULATION TESTING

The OGS device shall have Canadian ETV or ISO 14034 ETV Verification of completed third-party Light Liquid Re-entrainment Simulation Testing in accordance with the Canadian ETV **Program's Procedure for Laboratory Testing of Oil-Grit Separators**, with results reported within the Canadian ETV or ISO 14034 ETV verification. This re-entrainment testing is conducted with the device pre-loaded with low density polyethylene (LDPE) plastic beads as a surrogate for light liquids such as oil and fuel. Testing is conducted on the same OGS unit tested for sediment removal to

Stormceptor® **EF** Sizing Report

assess whether light liquids captured after a spill are effectively retained at high flow rates.

3.4.1 For an OGS device to be an acceptable stormwater treatment device on a site where vehicular traffic occurs and the potential for an oil or fuel spill exists, the OGS device must have reported verified performance results of greater than 99% cumulative retention of LDPE plastic beads for the five specified surface loading rates (ranging 200 L/min/m² to 2600 L/min/m²) in accordance with the Light Liquid Re-entrainment Simulation Testing within the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**. However, an OGS device shall not be allowed if the Light Liquid Re-entrainment Simulation Testing was performed with screening components within the OGS device that are effective at retaining the LDPE plastic beads, but would not be expected to retain light liquids such as oil and fuel.



APPENDIX B

SANITARY CALCULATIONS



Sanitary Servicing Analysis - Site A + B

Project Name: 12100 Creditview
 Project Number: 24045
 Location: Caledon
 Date: 9/30/2024

Prepared By: LP
 Checked By: TF

Standards	Peel Region	Formulas	
		Peaking Factor (Harmon)	$= 1+14/[4+(P/1000)^{1/2}]$
		Peak Flow	$= p(q)M(\text{unit conversion}) + \text{infiltration}$

Existing Sanitary Design Flow

Land Type	Area (m ²)	# of Units / Floor Area	Density	Population (p)	Average Flow (q)	Peaking Factor (M)	Peak Flow (Q) (L/s)
Infiltration Allowance	97200				0.0002 m3/s/ha		1.94
Total	97200						1.94

Proposed Sanitary Design Flow

Land Type	Area (m ²)	# of Units / Floor Area	Density (ppha)	Population (p)	Average Flow (q)	Peaking Factor (M)	Peak Flow (Q) (L/s)
Infiltration Allowance	97200				0.0002 m3/s/ha		1.94
Retail A		15071 sq.m	50 ppha	76	302.8 L/cap/day	4.00	1.07
Retail B1		1283 sq.m	50 ppha	7	302.8 L/cap/day	4.00	0.10
Retail B2		1254 sq.m	50 ppha	7	302.8 L/cap/day	4.00	0.10
Retail B3		1142 sq.m	50 ppha	6	302.8 L/cap/day	4.00	0.08
Retail B4		1329 sq.m	50 ppha	7	302.8 L/cap/day	4.00	0.10
Retail B5		409 sq.m	50 ppha	3	302.8 L/cap/day	4.00	0.04
Total	97200	20488		106			3.43

Summary

Existing Sanitary Design Flow	1.94 L/s
Proposed Sanitary Design Flow	3.43 L/s
Increased Flow	1.49 L/s



Sanitary Servicing Analysis - Site C

Project Name: 12100 Creditview
 Project Number: 24045
 Location: Caledon
 Date: 9/30/2024

Prepared By: LP
 Checked By: TF

Standards	Peel Region	Formulas	
		Peaking Factor (Harmon)	= $1+14/[4+(P/1000)^{1/2}]$
		Peak Flow	= $p(q)M(\text{unit conversion}) + \text{infiltration}$

Existing Sanitary Design Flow

Land Type	Area (m ²)	# of Units / Floor Area	Density	Population (p)	Average Flow (q)	Peaking Factor (M)	Peak Flow (Q) (L/s)
Infiltration Allowance	27800				0.0002 m3/s/ha		0.56
Total	27800						0.56

Proposed Sanitary Design Flow

Land Type	Area (m ²)	# of Units / Floor Area	Density (ppha)	Population (p)	Average Flow (q)	Peaking Factor (M)	Peak Flow (Q) (L/s)
Infiltration Allowance	27800				0.0002 m3/s/ha		0.56
Retail C1		4366 sq.m	50 ppha	22	302.8 L/cap/day	4.00	0.31
Retail C2		1579 sq.m	50 ppha	8	302.8 L/cap/day	4.00	0.11
Retail C3		793 sq.m	50 ppha	4	302.8 L/cap/day	4.00	0.06
Retail C4		755 sq.m	50 ppha	4	302.8 L/cap/day	4.00	0.06
Total	27800	7493		38			1.09

Summary

Existing Sanitary Design Flow	0.56 L/s
Proposed Sanitary Design Flow	1.09 L/s
Increased Flow	0.53 L/s



Sanitary Servicing Analysis - Downstream

Project Name: 12100 Creditview

Project Number: 24045

Location: Caledon

Date: 9/30/2024

Prepared By: LP

Checked By: TF

Peak Flow

Site A+B 3.43 L/s

Site C 1.09 L/s

Total 4.52 L/s

Pipe	Diameter (m)	Slope (%)	Velocity (m/s)	Full Flow Capacity (L/s)	Pre-Dev. Total Flow (L/s)	Pre-Dev. % Full	Post-Dev % Full
Street A (by TYLin)	200	0.5	0.74	23.19	n/a	n/a	19%
*MH52A	250	1.64	1.55	76.16	13.20	17%	23%
**MH59A	300	1.73	1.80	127.19	28.70	23%	26%

*upstream leg of Paradise Homes subdivision

**downstream leg of Paradise Homes subdivision



APPENDIX C

WATER CALCULATIONS



Required Fire Flow - Retail A (Site A+B)

Project Name: 12100 Creditview
 Project Number: 24045
 Location: Caledon
 Date: 9/30/2024

Prepared By: LP
 Checked By: TF

as per Fire Underwriters Survey Water Supply for Public Fire Protection, 2020

1. Initial Required Fire Flow (Step A, B, C)

Construction Type = Type II Noncombustible Construction
 Construction Coefficient, C = 0.8
 Total Effective Area, A = 15071 m²

Required Fire Flow, RFF = 21606.46422 LPM
RFF, rounded = 22000 LPM

2. Occupancy and Contents Adjustment Factor (Step D)

Contents = Noncombustible contents
 Adjustment Factor = -25%
RFF = 16500 LPM

3. Automatic Sprinkler Protection (Step E)

Sprinkler Design	Designed	Building Coverage	Credit
Automatic sprinkler protection designed and installed in accordance with NFPA 13	Yes	100%	30%
Water supply is standard for both the system and Fire Department hose lines	Yes	100%	10%
Fully supervised	No	100%	0%
Total Sprinkler Credit =			40%

Reduction = 6600 LPM

4. Exposure Adjustment Charge (Step F)

Direction	Distance	Charge
North	Greater than 30m	0%
South	Greater than 30m	0%
East	Greater than 30m	0%
West	Greater than 30m	0%

Total Charge = 0%

Charge = 0 LPM

5. Final Required Fire Flow (Step G)

RFF = 16500 LPM
 Reduction = 6600 LPM
 Charge = 0 LPM
 RFF = 9900 LPM

Final RFF, rounded =	10000 LPM
	2642 GPM
	167 L/s



Domestic Demand (Site A+B)

Project Name: 12100 Creditview
 Project Number: 24045
 Location: Caledon
 Date: 9/30/2024

Prepared By: LP
 Checked By: TF

as per Peel Region Standards

Population = 109
 Per Capita Demand = 300 L/cap/day
 Average Daily Demand = 32700 L/day
 0.38 L/s

	Average Day	Minimum Hour	Peak Hour	Maximum Day	
Peaking Factor	n/a	n/a	3.00	1.40	
Demand	0.38	n/a	1.14	0.53	L/s
	6.00	n/a	18.00	8.40	GPM



Head Loss Calculations (Max Day + Fire) - Site A+B

Project Name: 12100 Creditview
 Project Number: 24045
 Location: Caledon
 Date: 9/30/2024

Prepared By: LP
 Checked By: TF

Fire Flow = 167 L/s
Max Day Flow = 0.53 L/s
Total Flow = 167.2 L/s

Major Losses (Hazen Williams Formula + Hardy Cross Methodology)

Pipe ID	Parallel / Series	Diameter	Area (m ²)	Length (m)	Adjusted Length* (m)	Flow (L/s)	Velocity (m/s)	Hydraulic Radius	S	Headloss (m)	Headloss (psi)
1	Series	600	0.2827	115	126.5	167.2	0.6	0.15	0.00	0.07	0.10
2	Series	300	0.0707	220	242	167.2	2.4	0.08	0.02	4.03	5.74
3	Series	250	0.0491	128	140.8	167	3.4	0.06	0.04	5.67	8.07
4	Parallel	250	0.0491	115	126.5	101	2.0	0.06	0.02	2.00	2.84
5	Parallel	250	0.0491	250	275	66	1.3	0.06	0.01	2.00	2.84

Total major loss (psi) = 16.75


*adjusted length includes a 10% surcharge to account for minor losses

Total Headloss = 16.75 psi

Flow Test Results & Servicing Hydraulic Analysis

Pressure (psi)	Flow (L/s)	
92	0	Static Pressure
86	83.0	
78	137.3	

Flow Requirement = **167** L/s
 Theoretical Pressure = **71.7** psi
 With Pressure Losses = **54.9** psi
 Minimum Required = **20.3** psi





Head Loss Calculations (Peak Hour) - Site A+B

Project Name: 12100 Creditview
 Project Number: 24045
 Location: Caledon
 Date: 9/30/2024

Prepared By: LP
 Checked By: TF

Max Day Flow = 1.14 L/s

Major Losses (Hazen Williams Formula + Hardy Cross Methodology)

Pipe ID	Parallel / Series	Diameter	Area (m ²)	Length (m)	Adjusted Length* (m)	Flow (L/s)	Velocity (m/s)	Hydraulic Radius	S	Headloss (m)	Headloss (psi)
1	Series	600	0.2827	115	126.5	1.1	0.0	0.15	0.00	0.00	0.00001
2	Series	300	0.0707	220	242	1.14	0.0	0.08	0.00	0.00	0.00055
3	Series	250	0.0491	128	140.8	1.14	0.0	0.06	0.00	0.00	0.00078
4	Parallel	250	0.0491	115	126.5	0.69	0.0	0.06	0.00	0.00	0.00028
5	Parallel	250	0.0491	250	275	0.45	0.0	0.06	0.00	0.00	0.00028
Total major loss (psi) =										0.00	


*adjusted length includes a 10% surcharge to account for minor losses

Total Headloss = 0.00 psi

Flow Test Results & Servicing Hydraulic Analysis

Pressure (psi)	Flow (L/s)	
92	0	Static Pressure
86	83.0	
78	137.3	

Flow Requirement = 1 L/s
 Theoretical Pressure = 92.1 psi
 With Pressure Losses = 92.1 psi
 Minimum Required = 20.3 psi





Required Fire Flow - Retail C1/C2 (Site C)

Project Name: 12100 Creditview
 Project Number: 24045
 Location: Caledon
 Date: 9/24/2024

Prepared By: LP
 Checked By: TF

as per Fire Underwriters Survey Water Supply for Public Fire Protection, 2020

1. Initial Required Fire Flow (Step A, B, C)

Construction Type = Type II Noncombustible Construction
 Construction Coefficient, C = 0.8
 Total Effective Area, A = 5945 m²

Required Fire Flow, RFF = 13570.27339 LPM
RFF, rounded = 14000 LPM

2. Occupancy and Contents Adjustment Factor (Step D)

Contents = Noncombustible contents
 Adjustment Factor = -25%
RFF = 10500 LPM

3. Automatic Sprinkler Protection (Step E)

Sprinkler Design	Designed	Building Coverage	Credit
Automatic sprinkler protection designed and installed in accordance with NFPA 13	Yes	100%	30%
Water supply is standard for both the system and Fire Department hose lines	Yes	100%	10%
Fully supervised	No	100%	0%
Total Sprinkler Credit =			40%

Reduction = 4200 LPM

4. Exposure Adjustment Charge (Step F)

Direction	Distance	Charge
North	Greater than 30m	0%
South	Greater than 30m	0%
East	Greater than 30m	0%
West	Greater than 30m	0%

Total Charge = 0%

Charge = 0 LPM

5. Final Required Fire Flow (Step G)

RFF = 10500 LPM
 Reduction = 4200 LPM
 Charge = 0 LPM
 RFF = 6300 LPM

Final RFF, rounded =	6000 LPM
	1585 GPM
	100 L/s



Domestic Demand (Site C)

Project Name: 12100 Creditview

Project Number: 24045

Prepared By: LP

Location: Caledon

Checked By: TF

Date: 9/24/2024

as per Peel Region Standards

Population = 38
 Per Capita Demand = 300 L/cap/day
 Average Daily Demand = 11400 L/day
 0.13 L/s

	Average Day	Minimum Hour	Peak Hour	Maximum Day	
Peaking Factor	n/a	n/a	3.00	1.40	
Demand	0.13	n/a	0.40	0.18	L/s
	2.09	n/a	6.27	2.93	GPM



Head Loss Calculations (Max Day + Fire) - Site C

Project Name: 12100 Creditview
 Project Number: 24045
 Location: Caledon
 Date: 9/24/2024

Prepared By: LP
 Checked By: TF

Fire Flow = 100 L/s
Max Day Flow = 0.18 L/s
Total Flow = 100.2 L/s

Major Losses (Hazen Williams Formula + Hardy Cross Methodology)

Pipe ID	Parallel / Series	Diameter	Area (m ²)	Length (m)	Adjusted Length* (m)	Flow (L/s)	Velocity (m/s)	Hydraulic Radius	S	Headloss (m)	Headloss (psi)
1	Series	600	0.2827	115	126.5	100.2	0.4	0.15	0.00	0.03	0.04
2	Series	300	0.0707	108	118.8	100.2	1.4	0.08	0.01	0.77	1.09
3	Series	250	0.0491	29	31.9	100	2.0	0.06	0.02	0.50	0.71
4	Parallel	250	0.0491	45	49.5	66	1.3	0.06	0.01	0.35	0.50
5	Parallel	250	0.0491	148	162.8	34	0.7	0.06	0.00	0.35	0.50

Total major loss (psi) = 2.34


*adjusted length includes a 10% surcharge to account for minor losses

Total Headloss = 2.34 psi

Flow Test Results & Servicing Hydraulic Analysis

Pressure (psi)	Flow (L/s)	
92	0	Static Pressure
86	83.0	
78	137.3	

Flow Requirement = **100** L/s
 Theoretical Pressure = **83.7** psi
 With Pressure Losses = **81.4** psi
 Minimum Required = **20.3** psi





Head Loss Calculations (Peak Hour) - Site C

Project Name: 12100 Creditview
 Project Number: 24045
 Location: Caledon
 Date: 9/24/2024

Prepared By: LP
 Checked By: TF

Max Day Flow = 0.40 L/s

Major Losses (Hazen Williams Formula + Hardy Cross Methodology)

Pipe ID	Parallel / Series	Diameter	Area (m ²)	Length (m)	Adjusted Length* (m)	Flow (L/s)	Velocity (m/s)	Hydraulic Radius	S	Headloss (m)	Headloss (psi)
1	Series	600	0.2827	115	126.5	0.4	0.0	0.15	0.00	0.00	0.00000
2	Series	300	0.0707	220	242	0.40	0.0	0.08	0.00	0.00	0.00008
3	Series	250	0.0491	128	140.8	0.40	0.0	0.06	0.00	0.00	0.00011
4	Parallel	250	0.0491	115	126.5	0.24	0.0	0.06	0.00	0.00	0.00004
5	Parallel	250	0.0491	250	275	0.16	0.0	0.06	0.00	0.00	0.00004
Total major loss (psi) =										0.00	


*adjusted length includes a 10% surcharge to account for minor losses

Total Headloss = 0.00 psi

Flow Test Results & Servicing Hydraulic Analysis

Pressure (psi)	Flow (L/s)	
92	0	Static Pressure
86	83.0	
78	137.3	


Flow Requirement = 0 L/s
 Theoretical Pressure = 92.1 psi
 With Pressure Losses = 92.1 psi
 Minimum Required = 20.3 psi






APPENDIX D

SUPPORTING DOCUMENTS



SERVICE DATA					
SERVICE	DATE	INIT.	SERVICE	DATE	INIT.
HYDRO ONE	SEP 28, 2017	S.S.	ALECTRA UTILITIES	JAN 18, 2019	S.S.
WATERMANS	NOV 15, 2017	S.S.	PSN	MAY 18, 2018	S.S.
GAS MAINS	SEP 28, 2017	S.S.	SAN SEWERS	MAY 24, 2018	S.S.
BELL U/G CABLE	OCT 20, 2017	S.S.			
HYDRO ONE U/G	NOV 11, 2017	S.S.			
ROGERS	OCT 4, 2017	S.S.			


REVISIONS		
DATE	DETAILS	INIT.
MARCH 21, 2023	ISSUED FOR TENDER	J.P.D.
APRIL 26, 2021	100% DESIGN SUBMISSION	J.P.D.
NOV 16, 2020	MFCP SUBMISSION	J.P.D.
MAY 05, 2020	CVC PERMIT	J.P.D.
APRIL 18, 2019	ISSUED FOR 90% REVIEW	J.P.D.
JULY 13, 2018	ISSUED FOR 60% REVIEW	J.P.D.
JAN 19, 2018	ISSUED FOR 30% REVIEW	J.P.D.



LEGEND:

- PROPOSED FRENCH DRAIN
- PROPOSED IMPRESSED COLORED CONCRETE
- PROPOSED CONCRETE SIDEWALK / CONCRETE BUS PAD
- PROPOSED STEEL BEAM GUIDE RAIL OPSD 912.186
- PROPOSED HIGHWAY FENCE OPSD 971.101
- PROPOSED MULTI-USE PATH
- 150mm TOPSOIL AND SOD
- EXISTING BELL PLANTS
- EXISTING GAS LINE
- EXISTING WATERMAIN
- PROPOSED INFILTRATION TRENCH
- ROCK FLOW CHECK DAM OPSD 219.210 OR OPSD 219.211
- STONE SIZE - 75 TO 150mm RIP-RAP

Arva
 R.V. Anderson Associates Limited
 engineering • environment • infrastructure 173653



General Notes

All Driveways Are ASPHALT Unless Otherwise Noted

All Water And Sanitary Service Locations Are Approximate And Must Be Located Accurately In The Field

All Horizontal And Vertical Bends Are In Degrees

All Pipes Size In mm

20C Existing Water Service, Size In mm

WS25 Proposed Water Service, Size In mm

B.M. No. PEEL 61 Elev. 256.162 m

Description: Location On The East Face At The North Of Yellow Brick Bungalow Located On The South Of Mayfield Road

The Contractor Is Responsible For Locating And Protecting All Existing Utilities Prior To And During Construction. Location Of Existing Utilities Approximate Only. To Be Verified In Field By Contractor.

NOTE: 1. Through Lane Before Merging Taper

Designed by: *Chid.* Approved by: _____

NOTICE TO CONTRACTOR

48 HOURS PRIOR TO COMMENCING WORK NOTIFY THE FOLLOWING

THE REGIONAL MUNICIPALITY OF PEEL
 CITY OF MISSISSAUGA WORKS DEPT.
 CITY OF BRAMPTON WORKS DEPT.
 TOWN OF CALEDON WORKS DEPT.
 BELL CANADA
 ENBRIDGE INCORPORATED-GAS DISTRIBUTION
 ONTARIO MINISTRY OF TRANSPORTATION
 ONTARIO CLEAN WATER AGENCY
 HYDRO ONE NETWORKS
 ENERSOURCE, HYDRO MISSISSAUGA
 HYDRO ONE BRAMPTON

CABLE TELEVISION/FIBROPTIC PROVIDERS:
 BELL CANADA
 ENERSOURCE TELECOM
 HYDRO ONE TELECOM
 ROGERS CABLE
 ALLSTREAM
 PSN (PUBLIC SECTOR NETWORK)
 FUTUREWAY (FCI BROADBAND)

10m 0 10 20 30m HORIZONTAL SCALE
 1m 0 1 2 3m VERTICAL SCALE

Region of Peel
 working with you


MAYFIELD ROAD
 (FROM MISSISSAUGA RD. TO CHINGUACOUSY RD.)

PROPOSED RECONSTRUCTION
 STA. 5+460 TO STA. 5+700

CAD Area	Area B-33, C-09	Project No.	15-4070
Checked by	K.A.C.	Drawn by	S.S.
Date	MAY 2020	Sheet	NC7 OF NC20
Plan No.	78523-D		

264.71	264.58	264.45	264.32	264.19	264.06	263.91	263.72	263.48	263.22	262.96	262.70	262.44	262.18	261.92	261.66	261.40	261.14	260.88	260.62	260.36	260.10	259.84	259.58	259.32	259.06	258.80	258.54	258.28	258.02	257.76	257.50	257.24	256.98	256.72	256.46	256.20	255.94	255.68	255.42	255.16	254.90	254.64	254.38	254.12	253.86	253.60	253.34	253.08	252.82	252.56	252.30	252.04	251.78	251.52	251.26	251.00	250.74	250.48	250.22	249.96	249.70	249.44	249.18	248.92	248.66	248.40	248.14	247.88	247.62	247.36	247.10	246.84	246.58	246.32	246.06	245.80	245.54	245.28	245.02	244.76	244.50	244.24	243.98	243.72	243.46	243.20	242.94	242.68	242.42	242.16	241.90	241.64	241.38	241.12	240.86	240.60	240.34	240.08	239.82	239.56	239.30	239.04	238.78	238.52	238.26	238.00	237.74	237.48	237.22	236.96	236.70	236.44	236.18	235.92	235.66	235.40	235.14	234.88	234.62	234.36	234.10	233.84	233.58	233.32	233.06	232.80	232.54	232.28	232.02	231.76	231.50	231.24	230.98	230.72	230.46	230.20	230.00
5+440	5+460	5+480	5+500	5+520	5+540	5+560	5+580	5+600	5+620	5+640	5+660	5+680	5+700	5+720	PROP. SWALE ELEV																				PROP. FINISHED GRADE																																																																																																						
																									CAD Area																				Area B-33, C-09																				Project No. 15-4070																																																																								
																									Checked by K.A.C.																				Drawn by S.S.																				Project No. 15-4070																																																																								
																									Date: MAY 2020																				Sheet: NC7 OF NC20																				Plan No. 78523-D																																																																								
																									ROAD CHAINAGE																																																																																																																

R:\0117\7853 - MayfieldRoadProject\Drawings\Trans\Drawings\Drawings\Plan and Profile 7.dwg
 5:46:43 PM
 2024-07-03
 R:\A\T\h\and\m



TOTAL
PRE-DEVELOPMENT
DRAINAGE AREA =
13.56ha

12.29ha
0.25

1.27ha
0.90


CONTROL POST DEVELOPMENT TO 100YR
PRE DEVELOPMENT FLOW AND CONNECT TO
CLEAN WATER PIPE ON CREDITVIEW ROAD

TOTAL
PRE-DEVELOPMENT
DRAINAGE AREA =
15.40ha

13.01ha
0.25

2.39ha
0.90

CONTROL POST DEVELOPMENT TO 100YR
PRE DEVELOPMENT FLOW AND CONNECT TO
CLEAN WATER PIPE WITHIN BLOCK 51-1



LEGEND

- CLEAN WATER PIPE MANHOLE
- CLEAN WATER PIPE SEWER & FLOW DIRECTION ARROW
- POST-DEVELOPMENT DRAINAGE AREA
RUNOFF COEFFICIENT
- PRE-DEVELOPMENT DRAINAGE AREA (ha)
RUNOFF COEFFICIENT
- DRAINAGE AREA BOUNDARY

NOTE

- EXTERNAL 15.4 DRAINAGE AREA, INCLUDING CALEDON AND MAYFIELD ROAD ROW, TO BE CONVEYED VIA SEPARATE CLEAN WATER PIPE THROUGH THE BLOCK 51-1 DEVELOPMENT TO THE EXISTING 600mm DIA CREDITVIEW ROAD CULVERT. EXISTING 600mm CREDITVIEW ROAD CULVERT TO BE REPLACED WITH A MANHOLE AND A STORM PIPE, AND CLEAN WATER TO BE TEMPORARILY DISCHARGED TO THE EXISTING SOUTH SWALE (EAST OF CREDITVIEW ROAD) AT GRADE.
- EXTERNAL 13.56ha DRAINAGE AREA, INCLUDING CALEDON AND MAYFIELD ROAD ROW, TO BE CONVEYED VIA SEPARATE CLEAN WATER PIPE WITHIN THE ULTIMATE CREDITVIEW ROAD ROW TO THE EXISTING 600mm DIA CREDITVIEW ROAD CULVERT. EXISTING 600mm CREDITVIEW ROAD CULVERT 2 TO BE REPLACED WITH A MANHOLE AND STORM PIPE, AND CLEAN WATER TO BE TEMPORARILY DISCHARGED TO THE EXISTING NORTH SWALE (EAST OF CREDITVIEW ROAD) AT GRADE.

BENCHMARK NOTE

ELEVATIONS ARE GEODETIC AND ARE REFERRED TO MTO BENCHMARK 00810668355. LARGE CONCRETE CULVERT CARRYING HWY 7 OVER SMALL CREEK, 5.4 KM WEST OF THE NORTH JCT OF HWYS 7 AND 10 AND 27 M EAST OF PEEL RD 1. TABLE IS SET VERTICALLY IN THE TOP OF THE NORTH END, 37 CM SOUTH 15 CM EAST OF THE N.W. CORNER AND 18.8 M NORTH OF CENTRELINE OF PAVEMENT.

AS-CONSTRUCTED

3	AS CONSTRUCTED	FEB 2020	J.G.
2	FINAL SUBMISSION	SEP 21, 2013	J.O.
1	PRE-SERVICING SUBMISSION	JULY 10, 2013	J.O.
No.	REVISION	DATE	BY

FLOWER CITY CITY OF BRAMPTON
PLANNING, DESIGN & DEVELOPMENT
BRAMPTON.CA MICHAEL WONG, P. Eng., DIRECTOR OF DEVELOPMENT ENGINEERING SERVICES

LICENSED PROFESSIONAL ENGINEER
J. ORMONDE
100089999
FEB 28, 2020
PROVINCE OF ONTARIO

CITY FILE No. **C04W17.002** PROJECT **11-368-PH.2**

urbantech
UrbanTech Consulting, a Division of URS Corporation
3760 4th Avenue, Suite 202, Markham, Ontario L3R 3T7
Tel: 905.944.9888 Fax: 905.944.0992
www.urbantech.com


City of Mount Pleasant

PARADISE HOMES NORTH WEST INC.
BLOCK 51-1 - PHASE 2

FOUNDATION DRAIN COLLECTOR DRAINAGE PLAN



REGION FILE No. **21T-100118a**

SURVEYED BY:	R.P.E.	DATE:	NOVEMBER, 2012	CONTRACT NO.
DRAWN BY:	M.L.	CHECKED BY:	J.O.	DRAWING NO.
DESIGNED BY:	M.Z.	CHECKED BY:	J.O.	C1-9-1
SCALE:	1:2000	DATE:	JAN 20, 2014	SHEET NO. 306



REFER TO DWG. 308

REFER TO DWG. 309



- LEGEND**
- SANITARY MANHOLE AND FLOW DIRECTION ARROW
 - DRAINAGE AREA (ha)
 - POPULATION
 - POPULATION PER Ha (P/Ha)
 - DRAINAGE AREA BOUNDARY
 - EXTERNAL DRAINAGE AREA BOUNDARY
 - DOUBLE HOUSE CONNECTION
 - SINGLE HOUSE CONNECTION

BENCHMARK NOTE
 ELEVATIONS ARE GEODETIC AND ARE REFERRED TO MTO BENCHMARK 00919668355. LARGE CONCRETE CULVERT CARRYING HWY 7 OVER SMALL CREEK, 5.4 KM WEST OF THE NORTH JCT OF HWYS 7 AND 10 AND 27 M EAST OF PEEL REG RD 1. TABLET IS SET VERTICALLY IN THE TOP OF THE NORTH END, 37 CM SOUTH 15 CM EAST OF THE N.W. CORNER AND 16.8 M NORTH OF CENTRELINE OF PAVEMENT.

AS-CONSTRUCTED

NO.	REVISION	DATE	BY
1	TASK CONSTRUCTED	FEB. 2020	J.G.
2	ADDITIONAL MAYFIELD ROAD WIDENING BLOCK 210	DEC 12, 2013	J.O.
3	FINAL SUBMISSION	SEP 27, 2013	J.O.
4	PRE-SERVICING SUBMISSION	JULY 30, 2013	J.O.

FLOWER CITY CITY OF BRAMPTON
 PLANNING, DESIGN & DEVELOPMENT
 BRAMPTON, ONT. MICHAEL WON, P. Eng., DIRECTOR OF DEVELOPMENT ENGINEERING SERVICES

CITY FILE No. **C04W17.002** PROJECT **11-368-PH.2**

PROFESSIONAL ENGINEER
 J. ORMONDE
 10089999
 REG. 28, 2010
 PROVINCE OF ONTARIO


urbantech
 UrbanTech Consulting, A Division of Englehart-De Leeuw
 3700 14th Avenue, Suite 202, Hamilton, Ontario L8R 2T7
 Tel: 905.946.9461 Fax: 905.946.9395
 www.urbantech.com

Mount Pleasant

PARADISE HOMES NORTH WEST INC.
 BLOCK 51-1 - PHASE 2

SANITARY DRAINAGE PLAN (PART 1)
 REGION FILE No. 21T-100118a


SURVEYED BY:	R.P.E.	DATE:	NOVEMBER, 2012	CONTRACT NO.	
DRAWN BY:	J.S.	CHECKED BY:	J.O.	DRAWING NO.	
DESIGNED BY:	J.O.	CHECKED BY:	J.O.	C1-4-5	SHEET NO. 307
SCALE:	1:1000	DATE:	JAN 20, 2014		



REFER TO DWG. 307

REFER TO DWG. 310

REFER TO AMBER FIELDS LIMITED,
PROJECT No.: 11916
BY COUNTERPOINT ENGINEERING INC.



- LEGEND**
- SANITARY MANHOLE AND FLOW DIRECTION ARROW
 - DRAINAGE AREA (ha)
 - POPULATION PER Ha (P/Ha)
 - DRAINAGE AREA BOUNDARY
 - EXTERNAL DRAINAGE AREA BOUNDARY
 - DOUBLE HOUSE CONNECTION
 - SINGLE HOUSE CONNECTION

BENCHMARK NOTE
ELEVATIONS ARE GEODETIC AND ARE REFERRED TO MTO BENCHMARK 00819668355. LARGE CONCRETE CULVERT CARRYING HWY 7 OVER SMALL CREEK, 5.4 KM WEST OF THE NORTH JCT OF HWYS 7 AND 10 AND 27 M EAST OF PEEL RD 1. TABLE IS SET VERTICALLY IN THE TOP OF THE NORTH END, 37 CM SOUTH 15 CM EAST OF THE N.W. CORNER AND 16.8 M NORTH OF CENTRELINE OF PAVEMENT.

AS-CONSTRUCTED

No.	REVISION	DATE	BY
1	AS CONSTRUCTED	FEB 2020	J.G.
2	FOOTING FOR MAYFIELD ROAD WIDENING BLOCK 210	DEC 12, 2013	J.O.
3	FINAL SUBMISSION	SEP 27, 2013	J.O.
4	PRE-SERVICING SUBMISSION	JULY 15, 2013	X.O.

CITY OF BRAMPTON
PLANNING, DESIGN & DEVELOPMENT
BRAMPTON.CA MICHAEL WON, P. Eng., DIRECTOR OF DEVELOPMENT ENGINEERING SERVICES

CITY FILE No. **C04W17.002** PROJECT **11-368-PH.2**

J. ORMONDE
100089999
FEB 24, 2020
PROVINCE OF ONTARIO
LICENSED PROFESSIONAL ENGINEER

urbantech
UrbanTech Consulting, A Division of Lightpoint-2ac Ltd.
1700 VAP Avenue, Suite 202, North York, Ontario M2H 3T7
Tel: 905.948.9461 Fax: 905.948.9992
www.urbantech.com

Mount Pleasant

PARADISE HOMES NORTH WEST INC.
BLOCK 51-1 - PHASE 2

SANITARY DRAINAGE PLAN (PART 3)

SURVEYED BY:		R.P.E.	DATE:	NOVEMBER, 2012	CONTRACT NO.
DRAWN BY:		J.S.	CHECKED BY:	J.O.	DRAWING NO.
DESIGNED BY:		J.O.	CHECKED BY:	J.O.	SHEET NO.
SCALE:		1:1000	DATE:	JAN 20, 2014	C1-4-7 309

File: P:\Projects\11-368-Phase 2\Drawings\As-Constructed\Drawings\00 - Drainage - Revised by CGL\JGHWB - Pl, Feb 28 2020 - 4:50pm

AS CONSTRUCTED - SANITARY SEWER DESIGN SHEET

Paradise Homes North West Inc. - Phase 2

Region of Peel

PROJECT DETAILS

Registered Plan No: 43M-1947/43M-1948/43M-1949
 City File No: C04W17.002B
 Region File No: 21T-10011Ba
 Project No: 11-368-PH2
 Date: 28-Feb-20
 Designed by: M.L.
 Checked by: J.O.

DESIGN CRITERIA

Min. Flow = 13 l/s
 Min Diameter = 250 mm
 Mannings 'n' = 0.013
 Min. Velocity = 0.75 m/s
 Max. Velocity = 3.50 m/s
 Factor of Safety = 0 %

Avg. Domestic Flow = 302.8 l/c/d
 Infiltration = 0.200 l/s/ha
 Max. Peaking Factor = 4.00
 Min. Peaking Factor = 1.50
 Domestic Sewage flow for < 1000 ppl = 0.013m³/s
 (Region of Peel Std. 2-5-2)

NOMINAL PIPE SIZE USED

STREET	FROM MH	TO MH	RESIDENTIAL						COMMERCIAL/INDUSTRIAL/INSTITUTIONAL						FLOW CALCULATIONS								PIPE DATA						
			AREA (ha)	ACC. AREA (ha)	UNITS (#)	DENSITY (P/ha)	DENSITY (P/unit)	POP	ACCUM. RES. POP.	AREA (ha)	ACC. AREA (ha)	EQUIV. POP. (p/ha)	FLOW RATE (l/s/ha)	EQUIV. POP.	ACCUM. EQUIV. POP.	INFILTRATION (l/s)	TOTAL ACCUM. POP.	PEAKING FACTOR	RES. FLOW (l/s)	MIN. RES. FLOW (l/s)	COMM. FLOW (l/s)	ACCUM. COMM. FLOW (l/s)	TOTAL FLOW (l/s)	SLOPE (%)	PIPE DIAMETER (mm)	PIPE LENGTH (m)	FULL FLOW CAPACITY (l/s)	FULL FLOW VELOCITY (m/s)	ACTUAL VELOCITY (m/s)
FUTURE ALLOA PUMP STATION	100A	1A																					0.66	250	10.7	48.3	0.98	0.26	
TRURO CIRCLE	1A	2A	0.56	0.56		70		40	40					0.1	40	4.00	0.6	13.0				13.1	1.00	250	109.8	59.5	1.21	0.96	22%
TRURO CIRCLE	2A	3A	0.03	0.59		70		40	40					0.1	40	4.00	0.6	13.0				13.1	1.56	250	14.1	74.3	1.51	1.13	18%
TRURO CIRCLE	3A	6A	0.64	1.23		70		45	85					0.2	85	4.00	1.2	13.0				13.2	0.55	250	115.2	44.1	0.90	0.78	30%
		6A	0.10	0.10		50		5	5					0.0	5	4.00	0.1	13.0				13.0							
TAURUS ROAD	9A-E	5A	0.14	0.14		70		10	10					0.0	10	4.00	0.1	13.0				13.0	2.19	250	70.4	88.0	1.79	1.29	15%
TAURUS ROAD		5A	0.17	0.17		50		9	9					0.0	9	4.00	0.1	13.0				13.0							
MONCEAU ROAD	4A	5A	0.44	0.44		70		31	31					0.1	31	4.00	0.4	13.0				13.1	1.45	250	76.5	71.6	1.46	1.09	18%
		5A	0.15	0.15		50		8	8					0.0	8	4.00	0.1	13.0				13.0							
TAURUS ROAD	5A	6A	0.24	1.14		70		17	75					0.2	75	4.00	1.1	13.0				13.2	0.57	250	70.7	44.9	0.91	0.78	29%
TAURUS ROAD	6A	53A-S	0.31	2.78		70		22	187					0.6	187	4.00	2.6	13.0				13.6	1.24	250	74.2	66.2	1.35	1.04	20%
ROBERT PARKINSON DRIVE	52A	53A-S	1.00	1.00		50		50	50					0.2	50	4.00	0.7	13.0				13.2	1.64	250	107.6	76.2	1.55	1.15	17%
ROBERT PARKINSON DRIVE	53A-S	54A	0.12	3.90					237					0.8	237	4.00	3.3	13.0				13.8	0.58	250	70.2	45.3	0.92	0.80	30%
TRURO CIRCLE	7A	8A	0.34	0.34		70		24	24					0.1	24	4.00	0.3	13.0				13.1	0.99	250	49.1	59.2	1.21	0.95	22%
TRURO CIRCLE	8A	9A-S	0.16	0.50		50		8	32					0.1	32	4.00	0.4	13.0				13.1	0.72	250	22.7	50.5	1.03	0.85	26%
		9A-S	0.03	0.03		70		3	3					0.0	3	4.00	0.0	13.0				13.0							
TRURO CIRCLE	9A-S	10A	0.40	0.93		50		20	55					0.2	55	4.00	0.8	13.0				13.2	0.43	250	60.1	39.0	0.79	0.69	34%
TRURO CIRCLE	10A	11A	0.17	1.10		50		9	64					0.2	64	4.00	0.9	13.0				13.2	0.96	250	15.5	58.3	1.19	0.94	23%
TRURO CIRCLE	11A	12A-E	0.36	1.46		50		18	82					0.3	82	4.00	1.1	13.0				13.3	0.49	250	86.6	41.6	0.85	0.74	32%
		12A-E	0.22	0.22		70		16	16					0.0	16	4.00	0.2	13.0				13.0							
TRURO CIRCLE	12A-E	54A	0.68	2.36		70		48	146					0.5	146	4.00	2.0	13.0				13.5	1.60	250	120.4	75.2	1.53	1.15	18%
HUMBERSTONE CRESCENT	53A-E	32A	0.30	0.30		70		21	21					0.1	21	4.00	0.3	13.0				13.1	0.91	250	74.2	56.7	1.16	0.91	23%
EXHIBITION CRESCENT	31A	32A	0.66	0.66		70		47	47					0.1	47	4.00	0.7	13.0				13.1	0.97	250	117.1	58.6	1.19	0.94	22%
		32A	0.10	0.10		50		5	5					0.0	5	4.00	0.1	13.0				13.0							
HUMBERSTONE CRESCENT	32A	33A	0.29	1.35		50		15	88					0.3	88	4.00	1.2	13.0				13.3	1.34	250	70.1	68.8	1.40	1.07	19%
EXHIBITION CRESCENT	28A	29A	0.26	0.26		70		19	19					0.1	19	4.00	0.3	13.0				13.1	1.44	250	47.3	71.4	1.45	1.09	18%
EXHIBITION CRESCENT	29A	30A	0.09	0.35		70		7	26					0.1	26	4.00	0.4	13.0				13.1	0.50	250	13.1	42.0	0.86	0.75	31%
EXHIBITION CRESCENT	30A	33A	0.48	0.83		70		34	60					0.2	60	4.00	0.8	13.0				13.2	0.62	250	1047.5	46.8	0.95	0.81	28%
		33A	0.15	0.15		50		8	8					0.0	8	4.00	0.1	13.0				13.0							
HUMBERSTONE CRESCENT	33A	34A	0.31	2.64		50		16	172					0.5	172	4.00	2.4	13.0				13.5	0.49	250	119.3	41.6	0.85	0.74	32%
		34A	0.34	0.34		70		24	24					0.1	24	4.00	0.3	13.0				13.1							
HUMBERSTONE CRESCENT	34A	35A	0.06	3.04		50		3	199					0.6	199	4.00	2.8	13.0				13.6	0.50	250	13.3	42.0	0.86	0.75	32%
BLOCK 195 (COMMERCIAL)	DEALERSHIP	CTRL 95A	0.99	0.99		50		50	50					0.2	50	4.00	0.7	13.0				13.2		250					
HUMBERSTONE CRESCENT	CTRL 95A	96A	0.02	1.01					50					0.2	50	4.00	0.7	13.0				13.2	1.79	250	35.4	79.6	1.62	1.20	17%
HUMBERSTONE CRESCENT	96A	35A	0.01	1.02					50					0.2	50	4.00	0.7	13.0				13.2	0.87	250	14.1	55.5	1.13	0.92	24%
HUMBERSTONE CRESCENT	35A	36A	0.24	4.30		70		17	266					0.9	266	4.00	3.7	13.0				13.9	0.51	250	50.8	42.5	0.87	0.75	33%
HUMBERSTONE CRESCENT	36A	37A	0.09	4.39		50		5	271					0.9	271	4.00	3.8	13.0				13.9	0.26	250	14.0	30.3	0.62	0.59	46%
HUMBERSTONE CRESCENT	37A	38A	0.31	4.70		70		22	293					0.9	293	4.00	4.1	13.0				13.9	0.50	250	65.0	42.0	0.86	0.75	33%
		38A	0.08	0.08		50		4	4					0.0	4	4.00	0.1	13.0				13.0							
HUMBERSTONE CRESCENT	38A	381A	0.54	5.32		50		27	324					1.1	324	4.00	4.5	13.0				14.1	0.49	250	87.3	41.6	0.85	0.74	34%
		381A	0.06	0.06		70		5	5					0.0	5	4.00	0.1	13.0				13.0							
HUMBERSTONE CRESCENT	381A	54A	0.37	5.75		50		19	348					1.2	348	4.00	4.9	13.0				14.2	0.45	250	114.3	39.9	0.81	0.73	35%
		54A	0.40	0.40		70		28	28					0.1	28	4.00	0.4	13.0				13.1							
ROBERT PARKINSON DRIVE	54A	55A	0.12	12.53					759					2.5	759	3.87	10.3	13.0				15.5	0.47	300	71.5	66.3	0.94	0.74	23%
CAVESSON ROAD	15A	55A	0.58	0.58		70		41	41					0.1	41	4.00	0.6	13.0				13.1	1.12	250	78.9	62.9	1.28	0.99	21%



AS CONSTRUCTED - SANITARY SEWER DESIGN SHEET

Paradise Homes North West Inc. - Phase 2

Region of Peel

PROJECT DETAILS
 Registered Plan No: 43M-1947/43M-1948/43M-1949
 City File No: C04W17.002B
 Region File No: 21T-10011Ba
 Project No: 11-368-PH2
 Date: 28-Feb-20
 Designed by: M.L.
 Checked by: J.O.

DESIGN CRITERIA

Min. Flow = 13 l/s
 Min Diameter = 250 mm
 Mannings 'n' = 0.013
 Min. Velocity = 0.75 m/s
 Max. Velocity = 3.50 m/s
 Factor of Safety = 0 %

Avg. Domestic Flow = 302.8 l/c/d
 Infiltration = 0.200 l/s/ha
 Max. Peaking Factor = 4.00
 Min. Peaking Factor = 1.50
 Domestic Sewage flow for < 1000 ppl = 0.013m³/s
 (Region of Peel Std. 2-5-2)

NOMINAL PIPE SIZE USED

STREET	FROM MH	TO MH	RESIDENTIAL							COMMERCIAL/INDUSTRIAL/INSTITUTIONAL					FLOW CALCULATIONS							PIPE DATA									
			AREA (ha)	ACC. AREA (ha)	UNITS (#)	DENSITY (P/ha)	DENSITY (P/unit)	POP	ACCUM. RES. POP.	AREA (ha)	ACC. AREA (ha)	EQUIV. POP. (p/ha)	FLOW RATE (l/s/ha)	EQUIV. POP.	ACCUM. EQUIV. POP.	INFILTRATION (l/s)	TOTAL ACCUM. POP.	PEAKING FACTOR	RES. FLOW (l/s)	MIN. RES. FLOW (l/s)	COMM. FLOW (l/s)	ACCUM. COMM. FLOW (l/s)	TOTAL FLOW (l/s)	SLOPE (%)	PIPE DIAMETER (mm)	PIPE LENGTH (m)	FULL FLOW CAPACITY (l/s)	FULL FLOW VELOCITY (m/s)	ACTUAL VELOCITY (m/s)	PERCENT FULL (%)	
MANZANITA CRESCENT	39A-N	40A	0.21	0.21		70		15	15								0.0	15	4.00	0.2	13.0			13.0	0.64	250	17.6	47.6	0.97	0.80	27%
MANZANITA CRESCENT	40A	55A	0.41	0.62		70		29	44								0.1	44	4.00	0.6	13.0			13.1	1.12	250	66.1	62.9	1.28	0.99	21%
ROBERT PARKINSON DRIVE	55A	56A	0.12	13.85					844								2.8	844	3.85	11.4	13.0			15.8	0.57	300	71.2	73.0	1.03	0.82	22%
ZENIDA ROAD	16A	56A	0.59	0.59		70		42	42								0.1	42	4.00	0.6	13.0			13.1	2.10	250	78.9	86.2	1.76	1.26	15%
MANZANITA CRESCENT	39A-S	41A	0.23	0.23		70		17	17								0.0	17	4.00	0.2	13.0			13.0	0.92	250	47.5	57.0	1.16	0.92	23%
MANZANITA CRESCENT	41A	42A	0.21	0.44		70		15	32								0.1	32	4.00	0.4	13.0			13.1	0.69	250	13.4	49.4	1.01	0.84	26%
MANZANITA CRESCENT	42A	56A	0.49	0.93		70		35	67								0.2	67	4.00	0.9	13.0			13.2	0.57	250	76.5	44.9	0.91	0.78	29%
ROBERT PARKINSON DRIVE	56A	57A	0.12	15.49					953								3.1	953	3.81	12.7	13.0			16.1	0.40	300	74.4	61.2	0.87	0.72	26%
TERRICK ROAD	12A-S	13A	0.26	0.26		50		13	13								0.1	13	4.00	0.2	13.0			13.1	0.90	250	72.3	56.4	1.15	0.91	23%
TERRICK ROAD	13A	14A	0.36	0.62		50		18	31								0.1	31	4.00	0.4	13.0			13.1	0.94	250	105.5	57.7	1.17	0.93	23%
TERRICK ROAD	14A	19A	0.19	0.81		50		10	41								0.2	41	4.00	0.6	13.0			13.2	0.72	250	42.9	50.5	1.03	0.85	26%
HAVERSTOCK CRESCENT	17A-N	18A	0.16	0.16		50		8	8								0.0	8	4.00	0.1	13.0			13.0	0.73	250	14.2	50.8	1.04	0.86	26%
HAVERSTOCK CRESCENT	18A	19A	0.70	0.86		50		35	43								0.2	43	4.00	0.6	13.0			13.2	0.68	250	99.1	49.0	1.00	0.83	27%
HAVERSTOCK CRESCENT	19A	20A	0.46	2.13		50		23	107								0.4	107	4.00	1.5	13.0			13.4	0.71	250	74.5	50.1	1.02	0.85	27%
HAVERSTOCK CRESCENT	20A	21A	0.13	2.26		50		7	114								0.5	114	4.00	1.6	13.0			13.5	0.72	250	16.5	50.5	1.03	0.85	27%
HAVERSTOCK CRESCENT	21A	57A	0.14	2.40		50		7	121								0.5	121	4.00	1.7	13.0			13.5	0.54	250	30.0	43.7	0.89	0.77	31%
BLOCK 194 (JUNIOR SCHOOL)	SCHOOL	CTRL 1A	2.85	2.85				200	200								0.6	200	4.00	2.8	13.0			13.6		250					
KILKARRIN ROAD	CTRL 1A	43A		2.85					200								0.6	200	4.00	2.8	13.0			13.6	1.13	250	12.4	63.2	1.29	0.99	21%
KILKARRIN ROAD	43A	44A	0.70	3.55		50		35	235								0.7	235	4.00	3.3	13.0			13.7	0.93	250	116.0	57.3	1.17	0.95	24%
KILKARRIN ROAD	44A	441A	0.40	3.95		50		20	255								0.8	255	4.00	3.6	13.0			13.8	0.39	250	65.3	37.1	0.76	0.68	37%
KILKARRIN ROAD	441A	57A	0.63	4.58		50		32	287								0.9	287	4.00	4.0	13.0			13.9	0.73	250	85.0	50.8	1.04	0.86	27%
ROBERT PARKINSON DRIVE	57A	58A	0.12	22.59					1361								4.5	1361	3.71	17.7	17.7			22.2	0.51	300	73.9	69.1	0.98	0.85	32%
HAVERSTOCK CRESCENT	17A-S	24A	0.25	0.25		50		13	13								0.1	13	4.00	0.2	13.0			13.1	1.04	250	60.3	60.6	1.24	0.98	22%
FRAMPTON ROAD	24A	25A	0.66	0.91		50		33	46								0.2	46	4.00	0.6	13.0			13.2	0.44	250	102.0	39.4	0.80	0.70	33%
FRAMPTON ROAD	25A	58A	0.78	1.69		50		39	85								0.3	85	4.00	1.2	13.0			13.3	0.85	250	116.7	54.8	1.12	0.90	24%
ROBERT PARKINSON DRIVE	58A	59A	0.12	24.40					1446								4.9	1446	3.69	18.7	18.7			23.6	0.53	300	71.3	70.4	1.00	0.87	34%
ENFORD CRESCENT	451A	45A	0.36	0.36		70		26	26								0.1	26	4.00	0.4	13.0			13.1	0.97	250	101.3	58.6	1.19	0.94	22%
ENFORD CRESCENT	45A	46A	0.53	1.34		50		27	76								0.1	23	4.00	0.3	13.0			13.1							
ENFORD CRESCENT	46A	47A	0.30	0.30		70		21	21								0.3	76	4.00	1.1	13.0			13.3	0.51	250	120.8	42.5	0.87	0.75	31%
ENFORD CRESCENT	46A	47A	0.12	1.76		70		9	106								0.1	21	4.00	0.3	13.0			13.1							
ENFORD CRESCENT	47A	48A	0.10	1.86		70		7	113								0.4	106	4.00	1.5	13.0			13.4	1.10	250	29.3	62.4	1.27	0.98	21%
ENFORD CRESCENT	47A	48A	0.10	1.86		70		7	113								0.4	113	4.00	1.6	13.0			13.4	1.39	250	13.3	70.1	1.43	1.09	19%
ENFORD CRESCENT	48A	49A	0.24	2.10		70		17	130								0.4	130	4.00	1.8	13.0			13.4	0.52	250	49.8	42.9	0.87	0.76	31%
ENFORD CRESCENT	49A	50A	0.09	2.19		50		5	135								0.4	135	4.00	1.9	13.0			13.4	0.61	250	13.7	46.4	0.95	0.80	29%
ENFORD CRESCENT	50A	51A	0.54	2.73		70		38	173								0.5	173	4.00	2.4	13.0			13.5	0.47	250	99.6	40.8	0.83	0.72	33%
ENFORD CRESCENT	51A	51A	0.12	0.12		50		6	6								0.0	6	4.00	0.1	13.0			13.0							
ENFORD CRESCENT	51A	511A	0.62	3.47		50		31	210								0.7	210	4.00	2.9	13.0			13.7	0.48	250	93.1	41.2	0.84	0.73	33%
ENFORD CRESCENT	511A	59A	0.08	3.55		50		4	214								0.7	214	4.00	3.0	13.0			13.7	0.58	250	73.3	45.3	0.92	0.80	30%
ENFORD CRESCENT	59A		0.40	0.40		70		28	28								0.1	28	4.00	0.4	13.0			13.1							
HAVERSTOCK CRESCENT	23A	22A	0.25	0.25		50		13	13								0.1	13	4.00	0.2	13.0			13.1	1.44	250	50.4	71.4	1.45	1.09	18%
HAVERSTOCK CRESCENT	22A	26A	0.26	0.51		50		13	26								0.1	26	4.00	0.4	13.0			13.1	0.99	250	13.3	59.2	1.21	0.95	22%
HAVERSTOCK CRESCENT	26A	27A	0.63	1.14		50		32	58								0.2	58	4.00	0.8	13.0			13.2	0.96	250	94.7	58.3	1.19	0.94	23%
HAVERSTOCK CRESCENT	27A	59A	0.76	1.90		50		38	96								0.4	96	4.00	1.3	13.0			13.4	1.85	250	116.1	80.9	1.65	1.22	17%
ROBERT PARKINSON DRIVE	59A	38A (B.O.)	0.12	30.37					1784								6.1	1784	3.62	22.7	22.7			28.7	1.73	300	71.7	127.2	1.80	1.42	23%

August 29, 2024

PROJECT NUMBER 10376


Town of Caledon
 6311 Old Church Road
 Caledon, Ontario
 L7C 1J6

**Re: Erosion and Sediment Control Report in Support of Site Alteration Permit Application – 12100 Creditview Road
 Creditview Road
 Town of Caledon**

1 Introduction and Project Description

This letter report has been prepared in support of a Site Alteration Permit application for approximately 12.9 ha of a proposed industrial development associated with 12100 Creditview Road in the Town of Caledon. The property is bound by Creditview Road to the northeast, Mayfield Road to the southeast, and existing vacant and agricultural land to the northwest and southwest as shown on **Figure 1-1**. This application is only for the southeastern portion of the property and the remaining lands are not proposed for development at this time.

Figure 1-1 Site Location



The Toronto and Region Conservation Authority (TRCA) Erosion and Sediment Control Guidelines for Urban Construction (2019) were used in the design of the erosion and sediment control plans. This letter outlines the criteria used in the design and the resulting technical characteristics of the temporary sediment control measures.

This letter report should be read in conjunction with the Site Alteration Control Plan (Drawings ESC-01 to ESC-03) prepared by TYLin (August 2024).

2 Existing Site Conditions

The subject site is currently agricultural land with an existing dwelling. The existing topography of the site has a gentle slope from west to east, towards the ditch located at Creditview and Mayfield Road with elevation differences of approximately 5.0-6.0m across the length of the site.

The TRCA and CVC watershed divide is located within the 12100 Creditview Road property. However, the subject area proposed to be developed and for the purpose of this application is located within the CVC watershed.

3 Existing Watercourse Conditions

There is no existing watercourse through the subject property.

4 Adjacent Areas and Features

The subject site is bound by Creditview Road to the northeast, Mayfield Road to the southeast, and existing vacant and agricultural land to the northwest and southwest. Adjacent lands to the east and west are being developed for commercial and residential uses. South of Mayfield Road, in the City of Brampton, there is an existing residential subdivision, developed as part of Block 51-1, Phase 2.

5 Receiving Water System

The erosion control pond will discharge to the existing 500mm diameter culvert along the Mayfield Road ditch just west of Creditview Road. The flows from the culvert will continue southerly through the clean water pipe to a realigned channel east of Thornbush Boulevard and eventually to Fletcher's Creek. The realigned channel is classified as warmwater community.

6 Soils

Soils in the area are Chinguacousy clay loam, which is characterized as a heavy textured till.

7 Critical Areas

No critical areas are located on the site.

8 Permanent Stabilization

The detailed erosion and sediment control plans (Drawings ESC-01 to ESC-03) provide the details regarding the site stabilization including the proposed seed mix to be used for stabilization.

9 Design Details of ESC Measures

9.1 Site Preparation

Prior to commencing the site alteration works, the subject site will be enclosed using silt fencing, as shown on the Site Alteration Control Plan (Drawings ESC-01 to ESC-03). Access to the subject site will be from Creditview Road and mud mats will be constructed and maintained during the duration of the construction.

Conveyance swales around the perimeter of the site will be extended to convey flows from the north and west portion of the site to the temporary SWM pond. The perimeter cut-off swales were graded to convey runoff based on existing grades. As the site is striped and filled, conveyance swales will be implemented according to Drawings ESC-01 to ESC-03. Overland swales have a trapezoidal cross section with 2:1 side slope, 0.60m bottom widths and a minimum depth of 0.5m to convey flows up to the 5-year flow. Refer to the attachments for calculations.

9.2 Temporary Sediment Control Pond

A Temporary sediment control pond shown on Drawing ESC-01 is proposed. The temporary sediment control pond is required to detain runoff long enough to allow soil particles to settle out of suspension. The temporary sediment control pond is located at the end of the drainage path. Flows will enter the temporary sediment control pond via overland swales, which have been sized to adequately convey the existing 5-year flows, as described in above sections.

9.2.1 Permanent Pool

The permanent pool has been designed with a minimum storage volume of 125 m³/hectare of contributing drainage area. With a total tributary area of 12.9 ha, the temporary sediment control pond requires a permanent pool volume of 1,613 m³.

The temporary sediment control pond design provides a total permanent pool volume of 2,240 m³ at an elevation of 260.50 m with a maximum depth of 1.0 m. The sediment forebay is proposed to pre-treat incoming flows. The designed forebay length is 49.4m, which exceeds the required settling length of 12 m and the required dispersion length of 5 m. Please refer to the attachments for detailed calculations.

9.2.2 Active Storage

As per the Erosion and Sediment Control Guidelines (2019) the active storage component of the temporary sediment control pond should have a minimum 48-hour drawdown time; and should be designed with a minimum storage volume of 125 m³/hectare of contributing drainage area. With a total tributary area of 12.9 ha, the temporary sediment control pond requires 1,613m³ of active storage. An active storage volume of 2,310m³ has been provided within the temporary sediment control pond between the elevations of 260.50m (permanent pool level) and 261.20m (maximum high water level).

The required outflow of 14L/s is calculated by dividing the required active storage volume for 12.9 ha at 125 m³/ha (1,613 m³) by the minimum drawdown time of 48 hours $[(\text{Volume} / \text{drawdown time}) \times 1.5]$.

The required outflow rate will be achieved through the implementation of a vertical riser pipe, discharging through a 200 mm diameter PVC pipe fitted with a 90 mm diameter orifice plate set at an invert elevation of 260.50 m, which is equal to the permanent pool water level. The outlet details are shown on Drawing ESC-01-03.

Table 9-1 Summary of Temporary Sediment Control Pond Specifications

Pond Component	Stage (m)	Depth (m)	Required / Provided Storage Volume (m ³)	Design Release Rate (L/s)	Outlet Description
Permanent Pool	260.50	1.0	1,613/2,240	---	---
Required Active Storage	261.00	0.50	1,613/1,650	12	Control provided by a 90 mm diameter orifice set at 260.50 m
Provided Active Storage	261.20	0.70	1,613/2,310	14	

10 Record Keeping Procedures and Maintenance

During construction the designated site inspector shall inspect the site as per the notes on Drawing ESC-01 and ensure that all required maintenance is completed. A sample Inspection Report template is attached to this letter.

The following are the maintenance and inspection activities outlined on Drawing ESC-01.

Inspections

- Weekly inspection of all sediment control measures and after each rain event, any failure must be repaired immediately.

Sediment Trap

- The sediment trap will require cleaning when sediment accumulation reaches 50% of the height of the sediment trap.
- Sediment trap inlet, outlet, and side slopes should be inspected weekly and after each rainfall and significant snowmelt events.

Temporary Sediment Pond

- Sediment accumulation in the pond must be measured a minimum of once every six (6) months. The pond will require cleaning when sediment accumulation reaches 50% of the forebay design capacity (or 0.6m depth).
- Sediment pond embankments, outlet, and spillway should be inspected weekly and after each rainfall and significant snowmelt events.

Sediment Fences

- Sediment control fences must be inspected regularly, and after every rainfall, to identify failed sections. Any repairs must be undertaken immediately to restore the fencing.
- When sediment accumulates to the half the height of the geotextile it should be removed and disposed of in a controlled area.
- A supply of sediment control fence should be kept on site to provide for quick repairs, or the installation of additional fence as required.

Mud Mat

- The granular material will require periodic replacement as it becomes contaminated by vehicle traffic.
- Sediment shall be removed from public roads by shovelling or sweeping and disposed of properly in a controlled sediment disposal area.

Conveyance Swales

- Conveyance swales should be inspected periodically, and cleaning will be required when the measured depth of the sediments accumulated reaches 30% of depth behind flow interruption devices.

11 Emergency Contact

A list of emergency and non-emergency contacts will be kept on construction site all the time.

12 Closing

We trust that this Erosion and Sediment Control Plan satisfies your requirements. Should you have any questions or comments please contact the undersigned.

Sincerely,

T.Y. LIN INTERNATIONAL CANADA INC.

Rosalie Chung, P.Eng.
Water Resources Engineer
rosalie.chung@tylin.com

Encl: Temporary Sediment Pond Calculations
Cut of Swales Calculations
Inspection Report Template

ATTACHMENTS

Temporary Sediment Ponds Calculations

**Temporary Sediment Control Pond
Storage Requirements**

**Project#: 10376
Date: August 2024**

<u>Erosion & Sediment Control Guideline for Urban Construction Sediment Pond</u>	
Drainage Area:	12.9 ha
Permanent Pool Volume:	125 m ³ /hectare drainage area
Active Storage Volume:	125 m ³ /hectare drainage area
Required Permanent Pool Volume:	1,613 m³
Required Active Storage Volume:	1,613 m³
Total	3225 m³
Drawdown Time (Minimum 48 hr Drawdown Time)	
Active Storage Volume:	1,613 m³
Estimated Peak Release Rate (1.5 times of average flow)	14.0 L/s

**Temporary Sediment Control Pond
Provided Storage Calculations**

**Project#: 10376
Date: August 2024**

STAGE / STORAGE INFORMATION

POND CHARACTERISTICS

Base of Pond:	259.50
N.W.L.:	260.50 masl
Increment for Volume:	0.1 m
Required Permanent Pool Volume:	1,613 m ³
Required Active Pool Volume:	1,613 m ³
Permanent Pool Volume Provided:	2,240 m ³

VOLUME

Known Water Level:	261.00	
	INCL. P.P.	ACTIVE ONLY
Lower Known Elevation:	260.5	
Lower Known Volume:	2,240.25	
Upper Known Elevation:	261.2	
Upper Known Volume:	4,550.74	
Volume of Known W.L. Elevation:	3,891	1,650
Active Storage Required:		1,613

Water Level of Known Volume

Known Volume:	565	1613
	INCL. P.P.	ACTIVE ONLY
Lower Known Elevation:	259.5	260.50
Lower Known Volume:	0	0.00
Upper Known Elevation:	260.5	261.20
Upper Known Volume:	2240.246	2310.50
W.L. Elevation of Known Volume:	259.75	260.99
Permanent Pool Volume Provided:	2,240 m ³	
Active Pool Volume Provided:	2,310 m ³	

	Elevation (m)	Stage (m)	Area 1 (m ²)	Area 2 (m ²)	Total Area (m ²)	Avg. Area (m ²)	Incremental Storage (m ³)	Cumulative Storage (m ³)	Cumulative Storage above Permanent Pool (m ³)
Pond Base:	259.50	0.00	445.2	1,181.5	1,626.7		0.0		
NWL	260.50	1.00	935.7	1,918.1	2,853.8	2,240.2	2,240.2	2,240	0
HWL/Regional	261.20	1.70	3,747.6		3,747.6	3,300.7	2,310.5	4,551	2,310
Freeboard	261.50	2.00	4,094.0		4,094.0	3,920.8	1,176.2	5,727	3,487

**Temporary Sediment Control Pond
Release Rate and Orifice Sizing**

Project#: 10376
August 2024

Allowable Release Rate = 0.014 m³/s (Estimated Release Rate)

CALCULATE DIAMETER KNOWING Q & H	
Q(m ³ /s) =	0.014
Td (m) =	0.70
Approx A =	0.0061
Approx D =	88
A(m ²) =	0.006
D(mm) =	90

Orifice Plate	
DIA (mm) =	90
AREA (m ²) =	0.006
COEFF =	0.62
GRAVITY =	9.81
K =	1.0

TOTAL DEPTH m	Invert= 260.50 m		TOTAL FLOW	ELEVATION	
	Head m	Qp m ³ /s	Qp m ³ /s	m	
0.00	0.000	0.000	0.000	260.50	NWL
0.100	0.055	0.004	0.004	260.60	
0.200	0.155	0.007	0.007	260.70	
0.300	0.255	0.009	0.009	260.80	
0.400	0.355	0.010	0.010	260.90	
0.500	0.455	0.012	0.012	261.00	
0.600	0.555	0.013	0.013	261.10	
0.700	0.655	0.014	0.014	261.20	hwl
0.800	0.755	0.015	0.015	261.30	
0.900	0.855	0.016	0.016	261.40	
1.000	0.955	0.017	0.017	261.50	Free board

ORIFICE FLOW

$$Q_p(m^3/s) = COEF \times AREA \times (2 \times GRAVITY \times HEAD / K)^{0.5}$$

$$Approx A = Q / (COEF \times (2 \times GRAVITY \times Td / K)^{0.5})$$

$$Approx D = ((Approx A / PI)^{0.5}) \times 2 \times 1000$$

$$A (m^2) = Q / (COEF \times (2 \times GRAVITY \times (Td - (0.5 \times Approx D / 1000)) / K)^{0.5})$$

$$D(mm) = ((A / PI)^{0.5}) \times 2 \times 1000$$

WEIR FLOW

$$Q(m^3/s) = C \times L \times H^{1.5} \quad C=1.5$$

FOREBAY CALCULATIONS

PROJECT #: 10376

Temporary Sediment Control Pond

August 2024

PERMANENT POOL REQUIREMENTS

INPUT AREA

LENGTH TO WIDTH RATIO (r):	4.2	
PEAK QUALITY STORM RELEASE RATE:	0.0140 m ³ /s	
2 YEAR PEAK STORM FLOW INTO POND:	0.37 m ³ /s	
PARTICLE SETTLING VELOCITY (v _s):	3.00E-04 m/s	3.00E-4 FOR 150um PARTICLES
PROVIDED PERMANENT POOL DEPTH:	1.00 m	
PERMANENT POOL BERM TARGET VELOCITY:	0.5 m/s	0.5 STANDARD

SETTLING LENGTH CALCULATION

PERMANENT POOL LENGTH: 14

DISPERSION LENGTH CALCULATION

PERMANENT POOL LENGTH: 6

PERMANENT POOL DIMENSIONS (REQUIRED)

PERMANENT POOL LENGTH: 14
PERMANENT POOL WIDTH: 3

Provided Forebay dimensions:

PERMANENT POOL LENGTH: 49.4 m
PERMANENT POOL WIDTH: 11.9 m
PERMANENT POOL DEPTH: 1.00 m

Temporary Sediment Control Pond
Emergency Spillway
 Date: August 2024

Project#: 10376

SWM Pond Emergency Spillway

Weir Parameters

Weir Length (L)	4 m	
Weir Top Width (Bt)	8 m	
Weir Bottom Width (Bb)	5 m	
Median Width (B)	6.5 m	
MAX Qinlet (100 year peak flow)	0.813 m ³ /s	(rational method)
Crest Elevation	261.20 m	
Top of Weir Elevation	261.50 m	
Depth of Weir	0.30 m	

Weir Calculations ($Q = C_d * b * H^{3/2}$)

Water Level (H)	H/L	Cd	Q
0.05	0.013	1.40	0.10
0.10	0.025	1.40	0.29
0.15	0.038	1.48	0.56
0.20	0.050	1.52	0.88
0.25	0.063	1.53	1.24
0.30	0.075	1.55	1.66

Therefore, maximum capacity of spillway is
 1.66 m³/s

Note: The minimum weir bottom width shall be 8.0m long as per the Erosion & Sediment Control Guideline for Urban Construction

Cut-Off Swales

12100 Creditview Road
Town of Caledon

Project # : 10376

Date: August 2024

Preconstruction Conditions

Runoff coefficient calculation

Feature	Area (ha)	Runoff Coefficient	Imperviousness
Site	12.90	0.25	0.07
Overall Total	12.90	0.25	0.07

Time of Concentration

Upland Method

Area (ha)	12.90
Length (m)	390
Slope (%)	1.03
Velocity (m/s)	0.21 pasture lands
N	3
Tc (hr)	0.51

Note:

- Velocity is obtained from Figure A.5.2
- Tc = L / V
- Tp = (N-1)/N*Tc

Tc = 30.40 min

Rainfall Intensity (Town of Milton)

Return Period	A	B	C	Rainfall Intensity, i	
2 year	779.0	6.0	0.821	40.783	mm/hr
5 year	959.0	5.7	0.802	53.958	mm/hr
10 year	1089.0	5.7	0.796	62.807	mm/hr
25 year	1234.0	5.5	0.786	73.879	mm/hr
50 year	1323.0	5.3	0.779	81.777	mm/hr
100 year	1435.0	5.2	0.775	90.012	mm/hr


Existing Peak Discharge

Rational Runoff Coefficient, c	0.25
Drainage Area, A	12.90 ha
2 Year Peak Discharge, Q ₂	0.368 m ³ /s
5 Year Peak Discharge, Q ₅	0.487 m ³ /s
10 Year Peak Discharge, Q ₁₀	0.567 m ³ /s
25 Year Peak Discharge, Q ₂₅	0.667 m ³ /s
50 Year Peak Discharge, Q ₅₀	0.738 m ³ /s
100 Year Peak Discharge, Q ₁₀₀	0.813 m ³ /s

Manning's Equation Calculator for Trapezoidal Channels

Input:

Bottom Width = **0.60** m
 Bottom 'n₁' = 0.025
 Side Slope = 2 :1
 Side 'n₂' = 0.025
 Long. Slope = **0.0076** m/m
 Depth = **0.50** m



Output:

Flow = 1.301 m³/s > 5 year flow of 0.38m³/s
 Velocity = 1.627 m/s

Top Width of water = 2.60 m

Freeboard 0.22

Summary of Channel Dimensions and Check for high velocities:

2 :1

Slope	Flow depth		Ditch Width	Flow (m ³ /s)	Velocity (m/s)	Note
0.005	0.31		1.83	0.380	1.018	
0.006	0.29		1.78	0.380	1.089	
0.007	0.28		1.73	0.380	1.152	
0.008	0.27		1.70	0.380	1.210	Use Rip-Rap Class I
0.009	0.27		1.66	0.380	1.263	Use Rip-Rap Class I
0.010	0.26		1.64	0.380	1.313	Use Rip-Rap Class I
0.011	0.25		1.61	0.380	1.359	Use Rip-Rap Class I
0.012	0.25		1.59	0.380	1.403	Use Rip-Rap Class I

Note:

As per TRCA Erosion and Control Guideline "The typical threshold velocity before a well-grassed channel begins to erode is 1.2 m/s"

Inspection Report Template



Erosion and Sediment Control Guide For Urban Construction

Prepared by:
Toronto and Region Conservation Authority

2019

APPENDIX F: ESC INSPECTION REPORT TEMPLATE

ESC INSPECTION REPORT TEMPLATE

Date: _____ Weather/Time: _____

Project Site: _____ Reason for Visit: _____

Inspector Name: _____

Recipients:

List of report recipients and e-mail

ACTION ITEMS:

Item Number	Location	Description	Date	Completion Date	Weeks Recurring

a table listing active/ongoing maintenance, repair and replacement requirements can be used to summarize a detailed report. This can provide quick reference "Checklist/To Do" for the contractor.

Detailed ESC Report to Follow:

Item #:



Clear and concise description of what should be done...action item including a representative date stamped photo of the concern.

This should be done for each item every inspection.

MAP – attach a site plan/drawing and note the action items (new and recurring) that appear on the corresponding inspection report to ensure locations of corrective/actions items are clear. This is particularly useful for large projects.

Signature _____

Date _____



LEGEND

- FILTREX CHECK DAM AS PER DETAIL (ESC03)
- × 265.36 (SWL) PROPOSED SWALE ELEVATION
- × 265.65 EX EXISTING ELEVATION
- 265 EXISTING CONTOUR
- DOUBLE ROW SILT FENCE (AS PER DETAIL ON ESC03)
- STRAW BALES
- SILT CONTROL FENCE (AS PER DETAIL ON ESC03)
- SWALE @ 1.63% CUT-OFF SWALE AS PER DETAIL ON ESC03
- OVERLAND FLOW DIRECTION
- PROPERTY LIMIT
- CONSTRUCTION LIMIT - STAGE 1
- CVC/TRCA REGULATION LIMITS
- EXISTING DWELLING, GRAVEL DRIVE, TREES, ETC. TO BE REMOVED
- MUD-MAT (AS PER DETAIL ON ESC03)
- EXISTING HEADWATER DRAINAGE/ SWALE TO BE FILLED
- PUMP STORMWATER RUN-OFF (AS-NEEDED)

REGION NOTES:

- THE APPLICANT, APPLICANT'S REPRESENTATIVE CONSULTANT, CONTRACTOR AND SUB CONTRACTOR ARE RESPONSIBLE TO ENSURE THAT THEIR DESIGN AND CONSTRUCTION PRACTICES CONFORM TO THE LATEST REGION OF PEEL STANDARDS, SPECIFICATIONS AND DESIGN CRITERIA, POSTED ON THE REGION OF PEEL'S WEBSITE (www.peelregion.ca/pw/standards).

No.	REVISIONS	Date	U.A.	A.A.
1	FIRST SUBMISSION	AUGUST 2024	By	Approved

BENCHMARK: SET CUT CROSS 0.35m FROM SOUTH FACE OF CONCRETE HEAD WALL ALONG EAST SIDE OF ENTRANCE ROAD. 200m NORTH OF MAYFIELD ROAD. ELEVATION 265.29m

ELEVATION: ELEVATIONS SHOWN ON THIS PLAN ARE RELATED TO GEODETIC DATUM AND ARE DERIVED FROM THE CITY OF BRAMPTON HORIZONTAL CONTROL MONUMENT: No. 042200357 AT ELEVATION=260.691m

CVC STANDARD NOTES

- "EROSION AND SEDIMENT CONTROL (ESC) MEASURES WILL BE IMPLEMENTED PRIOR TO, AND MAINTAINED DURING THE CONSTRUCTION PHASES, TO PREVENT ENTRY OF SEDIMENT INTO THE WATER. ALL DAMAGED EROSION AND SEDIMENT CONTROL MEASURES SHOULD BE REPAIRED AND/OR REPLACED WITHIN 48 HOURS OF THE INSPECTION."
- "DISTURBED AREAS WILL BE MINIMIZED TO THE EXTENT POSSIBLE, AND TEMPORARILY OR PERMANENTLY STABILIZED OR RESTORED AS THE WORK PROGRESSES."
- "ALL IN-WATER AND NEAR WATER WORKS WILL BE CONDUCTED IN THE DRY WITH APPROPRIATE EROSION AND SEDIMENT CONTROLS."
- "THE EROSION AND SEDIMENT CONTROL STRATEGIES OUTLINED ON THE PLANS ARE NOT STATIC AND MAY NEED TO BE UPGRADED/AMENDED AS SITE CONDITIONS CHANGE TO MINIMIZE SEDIMENT LADEN RUNOFF FROM LEAVING THE WORK AREAS. IF THE PRESCRIBED MEASURES ON THE PLANS ARE NOT EFFECTIVE IN PREVENTING THE RELEASE OF A DELETERIOUS SUBSTANCE, INCLUDING SEDIMENT, THEN ALTERNATIVE MEASURES MUST BE IMPLEMENTED IMMEDIATELY TO MINIMIZE POTENTIAL ECOLOGICAL IMPACTS. CVC ENFORCEMENT OFFICER SHOULD BE IMMEDIATELY CONTACTED. ADDITIONAL ESC MEASURES TO BE KEPT ON SITE AND USED AS NECESSARY."
- "AN ENVIRONMENTAL MONITOR WILL ATTEND THE SITE TO INSPECT ALL NEW CONTROLS, AS WELL AS ON A WEEKLY BASIS, OR FOLLOWING RAIN/SNOWMELT EVENT, TO MONITOR ALL WORKS, AND IN PARTICULAR WORKS RELATED TO EROSION AND SEDIMENT CONTROLS, DEWATERING OR UNWATERING, RESTORATION AND IN- OR NEAR- WATER WORKS. SHOULD CONCERNS ARISE ON SITE THE ENVIRONMENTAL MONITOR WILL CONTACT THE CVC ENFORCEMENT OFFICER AS WELL AS THE PROPONENT."
- "ALL ACTIVITIES, INCLUDING MAINTENANCE PROCEDURES, WILL BE CONTROLLED TO PREVENT THE ENTRY OF PETROLEUM PRODUCTS, DEBRIS, RUBBLE, CONCRETE OR OTHER DELETERIOUS SUBSTANCES INTO THE WATER. VEHICULAR REFUELLING AND MAINTENANCE WILL BE CONDUCTED A MINIMUM OF 30 METRES FROM THE WATER."
- "ALL GRADES WITHIN THE REGULATORY FLOOD PLAIN WILL BE MAINTAINED OR MATCHED."
- "THE PROPONENT/CONTRACTOR SHALL MONITOR THE WEATHER SEVERAL DAYS IN ADVANCE OF THE ONSET OF THE PROJECT TO ENSURE THAT THE WORKS WILL BE CONDUCTED DURING FAVOURABLE WEATHER CONDITIONS. SHOULD AN UNEXPECTED STORM ARISE, THE CONTRACTOR WILL REMOVE ALL UNFIXED ITEMS FROM THE REGIONAL STORM FLOOD PLAIN THAT WOULD HAVE THE POTENTIAL TO CAUSE A SPILL OR AN OBSTRUCTION TO FLOW, E.G., FUEL TANKS, PORTA-POTTIES, MACHINERY, EQUIPMENT, CONSTRUCTION MATERIALS, ETC."
- "ALL DEWATERING/UNWATERING SHALL BE TREATED AND RELEASED TO THE ENVIRONMENT AT LEAST 30 METRES FROM A WATERCOURSE OR WETLAND AND ALLOWED TO DRAIN THROUGH A WELL-VEGETATED AREA. NO DEWATERING EFFLUENT SHALL BE SENT DIRECTLY TO ANY WATERCOURSE, WETLAND OR FOREST, OR ALLOWED TO DRAIN ONTO DISTURBED SOILS WITHIN THE WORK AREA. THESE CONTROL MEASURES SHALL BE MONITORED FOR EFFECTIVENESS AND MAINTAINED OR REVISED TO MEET THE OBJECTIVE OF PREVENTING THE RELEASE OF SEDIMENT LADEN WATER."
- "ALL ACCESS TO THE WORK SITE SHALL BE FROM EITHER SIDE OF THE WATERCOURSE. NO EQUIPMENT OR VEHICLES ARE PERMITTED TO CROSS THROUGH THE WATERCOURSE UNLESS APPROVED BY CVC."
- "IN ORDER TO COMPLY WITH THE MIGRATORY BIRDS CONVECTION ACT, CVC RECOMMENDS THAT TREE REMOVALS BE COMPLETED BETWEEN AUGUST 1 AND APRIL 15."
- "TO PROTECT LOCAL FISH POPULATIONS DURING THEIR SPAWNING, NURSERY AND MIGRATORY PERIODS, IN-WATER/NEAR-WATER ACTIVITIES, MAY ONLY OCCUR DURING THE FOLLOWING TIME PERIOD: JULY 1 TO SEPT 15."
- "FISH AND WILDLIFE STRANDED WITHIN THE WORK AREA SHALL BE CAPTURED AND RELEASED LIVE IN SUITABLE HABITAT UPSTREAM OF THE WORK AREA UNDER THE SUPERVISION OF A QUALIFIED AQUATIC BIOLOGIST. A PERMIT FROM THE MINISTRY OF NATURAL RESOURCES IS REQUIRED."
- "PLEASE NOTIFY CVC ENFORCEMENT OFFICER AND CVC PROJECT MANAGER 48 HOURS PRIOR TO COMMENCING CONSTRUCTION."
- "AN ENVIRONMENTAL MONITOR WILL BE ON SITE, AND PROVIDE ADVICE, TO ENSURE THAT ACTIVITIES THAT COULD HAVE A NEGATIVE IMPACT TO THE NATURAL ENVIRONMENT ARE EFFECTIVELY MITIGATED AS CONSTRUCTION PROCEEDS. THE ENVIRONMENTAL MONITOR SHALL NOTIFY THE CVC ENFORCEMENT OFFICER AND PROJECT MANAGER IF AN ISSUE ARISES."

EROSION AND SEDIMENT CONTROL GENERAL NOTES (TOWN OF CALEDON)

- ALL CONSTRUCTION VEHICLES MUST ENTER AND EXIT THE SITE ONLY FROM THE APPROVED ACCESS ROUTE(S) AS SHOWN ON THE PLANS. CONSTRUCTION ACCESS WILL BE MAINTAINED TO THE SATISFACTION OF THE TOWN/REGION. STREET SWEEPING IS REQUIRED AS NEEDED.
- NO CONSTRUCTION ACTIVITY OR MACHINERY SHALL BE ALLOWED BEYOND THE SILT FENCE OR LIMITS OF THE SITE WORKS.
- THE CONTRACTOR IS RESPONSIBLE TO IMPLEMENT DUST CONTROL MEASURES AND CONSTRUCTION BEST PRACTICE GUIDELINES AS APPROVED BY THE TOWN AND/OR CONSERVATION AUTHORITY.
- ALL DISTURBED GROUND LEFT INACTIVE FOR 30 DAYS SHALL BE VEGETATED, SUBJECT TO WEATHER CONDITIONS. DISTURBED AREAS ARE TO BE HYDROSEEDED (OR APPROVED EQUIVALENT) TO THE SATISFACTION OF THE TOWN.
- ALL TOPSOIL STOCKPILES SHALL BE SURROUNDED WITH SEDIMENT CONTROL FENCE. THE MAXIMUM SIDE SLOPE SHALL BE 2:1 (H:V). ONCE TOPSOIL STRIPPING IS COMPLETED THE STOCKPILE SHALL BE VEGETATED, SUBJECT TO WEATHER CONDITIONS, BY HYDROSEEDING, OR AN APPROVED EQUIVALENT, TO THE SATISFACTION OF THE TOWN.

SEED MIXTURE

NATIVE PRAIRIE LOW GROW GRASS MIXTURE	
% OF MIXTURE	COMPOSITION TYPE
25%	FOWL BLUEGRASS (POA PALUSTRIS)
30%	CANADA WILD RYE (ELYMUS CANADENSIS)
15%	LITTLE BLUESTEM (SCHIZACHYRIUM SCORPARIUM)
30%	SAND DROPSEED (SPOROBOLUS CRYPTANDRUS)

SUMMARY CHART FOR ESC STAGING

ESC MEASURE	TIMING FOR INSTALLATION	INSPECTION MAINTENANCE REQUIREMENTS	TIMING FOR REMOVAL
STAGE 1 - AREA GRADING			
1. Install traffic control signs and construction access to the site.	Prior to stage 1 works.	<ul style="list-style-type: none"> Consultant to arrange inspection with Town staff once installation is complete. Consultant to undertake weekly inspections and after each rainfall event, including weekly reporting. Regular maintenance to remove accumulated sediment and repair ESC measures. 	Just prior to final grading, replacement with Stage 2 measures.
2. Install silt fences in the areas shown.			
3. Clear site of trees and vegetation as required. Clear and grub the area.			
4. Construct the temporary sediment pond.			
5. Construct the cut-off swales.			
6. Strip the topsoil from the site, and stockpile in area shown. Stockpile area to be pre-graded before stockpiling.			
7. Install double row silt fence around stockpile area.			

REGION FILE No: XX Designed By: TOWN FILE No: XX



TYLin

3381 Skeetes Avenue East,
Suite 315
Toronto, ON
M2H 3S8
p: 905.738.5700
f: 905.738.0065

12100 CREDITVIEW DEVELOPMENTS LTD.

**EROSION & SEDIMENTATION PLAN
STAGE 1 (TOPSOIL STRIPPING)**

SCALE: 1:1000	CHECKED BY: A.A.	PROJECT NO. 10376
DESIGNED BY: U.A.	DRAWN BY: U.A./R.P.	DRAWING NO. ESC01
CHECKED BY: D.M.	DATE: AUGUST 2024	SHEET NO. 01



LEGEND

- FILTRIX CHECK DAM AS PER DETAIL (ESC03)
- PRE-GRADE ELEVATIONS
- PROPOSED TOP OF SWALE
- PROPOSED BOTTOM OF SWALE
- EXISTING ELEVATION
- EXISTING CONTOUR
- DOUBLE ROW SILT FENCE (AS PER DETAIL ON ES03)
- STRAW BALES
- SILT CONTROL FENCE (AS PER DETAIL ON ES03)
- CUT OFF SWALES AS PER DETAIL ON ES03
- EXISTING STAGE 1 SWALE
- OVERLAND FLOW DIRECTION
- PROPERTY LIMIT
- CONSTRUCTION LIMIT - STAGE 2
- MUD-MAT (AS PER DETAIL ON ES03)

REGION NOTES:

- THE APPLICANT, APPLICANT'S REPRESENTATIVE CONSULTANT, CONTRACTOR AND SUB CONTRACTOR ARE RESPONSIBLE TO ENSURE THAT THEIR DESIGN AND CONSTRUCTION PRACTICES CONFORM TO THE LATEST REGION OF PEEL STANDARDS, SPECIFICATIONS AND DESIGN CRITERIA, POSTED ON THE REGION OF PEEL'S WEBSITE (www.peelregion.ca/pw/standards).

1	FIRST SUBMISSION	AUGUST 2024	U.A.	A.A.
No.	REVISIONS	Date	By	Approved

BENCHMARK: SET CUT CROSS 0.35m FROM SOUTH FACE OF CONCRETE HEAD WALL ALONG EAST SIDE OF ENTRANCE ROAD. 200m NORTH OF MAYFIELD ROAD. ELEVATION 265.29m

ELEVATION: ELEVATIONS SHOWN ON THIS PLAN ARE RELATED TO GEODETIC DATUM AND ARE DERIVED FROM THE CITY OF BRAMPTON HORIZONTAL CONTROL MONUMENT: No. 042200357 AT ELEVATION=260.691m

CVC STANDARD NOTES

- "EROSION AND SEDIMENT CONTROL (ESC) MEASURES WILL BE IMPLEMENTED PRIOR TO, AND MAINTAINED DURING THE CONSTRUCTION PHASES, TO PREVENT ENTRY OF SEDIMENT INTO THE WATER. ALL DAMAGED EROSION AND SEDIMENT CONTROL MEASURES SHOULD BE REPAIRED AND/OR REPLACED WITHIN 48 HOURS OF THE INSPECTION."
- "DISTURBED AREAS WILL BE MINIMIZED TO THE EXTENT POSSIBLE, AND TEMPORARILY OR PERMANENTLY STABILIZED OR RESTORED AS THE WORK PROGRESSES."
- "ALL IN-WATER AND NEAR WATER WORKS WILL BE CONDUCTED IN THE DRY WITH APPROPRIATE EROSION AND SEDIMENT CONTROLS."
- "THE EROSION AND SEDIMENT CONTROL STRATEGIES OUTLINED ON THE PLANS ARE NOT STATIC AND MAY NEED TO BE UPGRADED/AMENDED AS SITE CONDITIONS CHANGE TO MINIMIZE SEDIMENT LADEN RUNOFF FROM LEAVING THE WORK AREAS. IF THE PRESCRIBED MEASURES ON THE PLANS ARE NOT EFFECTIVE IN PREVENTING THE RELEASE OF A DELETERIOUS SUBSTANCE, INCLUDING SEDIMENT, THEN ALTERNATIVE MEASURES MUST BE IMPLEMENTED IMMEDIATELY TO MINIMIZE POTENTIAL ECOLOGICAL IMPACTS. CVC ENFORCEMENT OFFICER SHOULD BE IMMEDIATELY CONTACTED. ADDITIONAL ESC MEASURES TO BE KEPT ON SITE AND USED AS NECESSARY."
- "AN ENVIRONMENTAL MONITOR WILL ATTEND THE SITE TO INSPECT ALL NEW CONTROLS, AS WELL AS ON A WEEKLY BASIS, OR FOLLOWING RAIN/SNOWMELT EVENT, TO MONITOR ALL WORKS, AND IN PARTICULAR WORKS RELATED TO EROSION AND SEDIMENT CONTROLS, DEWATERING OR UNWATERING, RESTORATION AND IN-OR NEAR-WATER WORKS. SHOULD CONCERNS ARISE ON SITE THE ENVIRONMENTAL MONITOR WILL CONTACT THE CVC ENFORCEMENT OFFICER AS WELL AS THE PROPONENT."
- "ALL ACTIVITIES, INCLUDING MAINTENANCE PROCEDURES, WILL BE CONTROLLED TO PREVENT THE ENTRY OF PETROLEUM PRODUCTS, DEBRIS, RUBBLE, CONCRETE OR OTHER DELETERIOUS SUBSTANCES INTO THE WATER. VEHICULAR REFUELLING AND MAINTENANCE WILL BE CONDUCTED A MINIMUM OF 30 METRES FROM THE WATER."
- "ALL GRADES WITHIN THE REGULATORY FLOOD PLAIN WILL BE MAINTAINED OR MATCHED."
- "THE PROPONENT/CONTRACTOR SHALL MONITOR THE WEATHER SEVERAL DAYS IN ADVANCE OF THE ONSET OF THE PROJECT TO ENSURE THAT THE WORKS WILL BE CONDUCTED DURING FAVOURABLE WEATHER CONDITIONS. SHOULD AN UNEXPECTED STORM ARISE, THE CONTRACTOR WILL REMOVE ALL UNFIXED ITEMS FROM THE REGIONAL STORM FLOOD PLAIN THAT WOULD HAVE THE POTENTIAL TO CAUSE A SPILL OR AN OBSTRUCTION TO FLOW, E.G., FUEL TANKS, PORTA-POTTIES, MACHINERY, EQUIPMENT, CONSTRUCTION MATERIALS, ETC."
- "ALL DEWATERING/UNWATERING SHALL BE TREATED AND RELEASED TO THE ENVIRONMENT AT LEAST 30 METRES FROM A WATERCOURSE OR WETLAND AND ALLOWED TO DRAIN THROUGH A WELL-VEGETATED AREA. NO DEWATERING EFFLUENT SHALL BE SENT DIRECTLY TO ANY WATERCOURSE, WETLAND OR FOREST, OR ALLOWED TO DRAIN ONTO DISTURBED SOILS WITHIN THE WORK AREA. THESE CONTROL MEASURES SHALL BE MONITORED FOR EFFECTIVENESS AND MAINTAINED OR REVISED TO MEET THE OBJECTIVE OF PREVENTING THE RELEASE OF SEDIMENT LADEN WATER."
- "ALL ACCESS TO THE WORK SITE SHALL BE FROM EITHER SIDE OF THE WATERCOURSE. NO EQUIPMENT OR VEHICLES ARE PERMITTED TO CROSS THROUGH THE WATERCOURSE UNLESS APPROVED BY CVC."
- "IN ORDER TO COMPLY WITH THE MIGRATORY BIRDS CONVECTION ACT, CVC RECOMMENDS THAT TREE REMOVALS BE COMPLETED BETWEEN AUGUST 1 AND APRIL 1."
- "TO PROTECT LOCAL FISH POPULATIONS DURING THEIR SPAWNING, NURSERY AND MIGRATORY PERIODS, IN-WATER/NEAR-WATER ACTIVITIES, MAY ONLY OCCUR DURING THE FOLLOWING TIME PERIOD: JULY 1 TO SEPT 15."
- "FISH AND WILDLIFE STRANDED WITHIN THE WORK AREA SHALL BE CAPTURED AND RELEASED IN A SUITABLE HABITAT UPSTREAM OF THE WORK AREA UNDER THE SUPERVISION OF A QUALIFIED AQUATIC BIOLOGIST. A PERMIT FROM THE MINISTRY OF NATURAL RESOURCES IS REQUIRED."
- "PLEASE NOTIFY CVC ENFORCEMENT OFFICER AND CVC PROJECT MANAGER 48 HOURS PRIOR TO COMMENCING CONSTRUCTION."
- "AN ENVIRONMENTAL MONITOR WILL BE ON SITE, AND PROVIDE ADVICE, TO ENSURE THAT ACTIVITIES THAT COULD HAVE A NEGATIVE IMPACT TO THE NATURAL ENVIRONMENT ARE EFFECTIVELY MITIGATED AS CONSTRUCTION PROCEEDS. THE ENVIRONMENTAL MONITOR SHALL NOTIFY THE CVC ENFORCEMENT OFFICER AND PROJECT MANAGER IF AN ISSUE ARISES."

EROSION AND SEDIMENT CONTROL GENERAL NOTES (TOWN OF CALEDON)

- ALL CONSTRUCTION VEHICLES MUST ENTER AND EXIT THE SITE ONLY FROM THE APPROVED ACCESS ROUTE(S) AS SHOWN ON THE PLANS. CONSTRUCTION ACCESS WILL BE MAINTAINED TO THE SATISFACTION OF THE TOWN/REGION. STREET SWEEPING IS REQUIRED AS NEEDED.
- NO CONSTRUCTION ACTIVITY OR MACHINERY SHALL BE ALLOWED BEYOND THE SILT FENCE OR LIMITS OF THE SITE WORKS.
- THE CONTRACTOR IS RESPONSIBLE TO IMPLEMENT DUST CONTROL MEASURES AND CONSTRUCTION BEST PRACTICE GUIDELINES AS APPROVED BY THE TOWN AND/OR CONSERVATION AUTHORITY
- ALL DISTURBED GROUND LEFT INACTIVE FOR 30 DAYS SHALL BE VEGETATED, SUBJECT TO WEATHER CONDITIONS. DISTURBED AREAS ARE TO BE HYDROSEEDED (OR APPROVED EQUIVALENT) TO THE SATISFACTION OF THE TOWN.
- ALL TOPSOIL STOCKPILES SHALL BE SURROUNDED WITH SEDIMENT CONTROL FENCE. THE MAXIMUM SIDE SLOPE SHALL BE 2:1 (H:V). ONCE TOPSOIL STRIPPING IS COMPLETED THE STOCKPILE SHALL BE VEGETATED, SUBJECT TO WEATHER CONDITIONS, BY HYDROSEEDING, OR AN APPROVED EQUIVALENT, TO THE SATISFACTION OF THE TOWN.

SUMMARY CHART FOR ESC STAGING

ESC MEASURE	TIMING FOR INSTALLATION	INSPECTION MAINTENANCE REQUIREMENTS	TIMING FOR REMOVAL
STAGE 2 - PRE-GRADING			
1. Install cut-off swales where shown.	Prior to site servicing.	<ul style="list-style-type: none"> Consultant to arrange inspection with Town staff once installation is complete. Consultant to undertake weekly inspections and after each rainfall event, including weekly reporting. Regular maintenance to remove accumulated sediment and repair esc measures. 	Prior to final topsoil and sodding of lot/block areas.
2. Fill existing stage 1 swales.			
3. Pre-grade site to elevations shown.			
4. Maintain ESC measures as required.			

SEED MIXTURE

NATIVE PRAIRIE LOW GROW GRASS MIXTURE	
% OF MIXTURE	COMPOSITION TYPE
25%	FOWL BLUEGRASS (POA PALUSTRIS)
30%	CANADA WILD RYE (ELYMUS CANADENSIS)
15%	LITTLE BLUESTEM (SCHIZACHYRIUM SCORPIURUM)
30%	SAND DROPSEED (SPOROBOLUS CRYPTANDRUS)







REGION FILE No: XX Designed By: A.A. AHMADZAI TOWN FILE No: XX






T Lin
 3381 Steeles Avenue East,
 Suite 315
 Toronto, ON
 M2H 3S8
 P: 905.738.5700
 F: 905.738.0065

12100 CREDITVIEW DEVELOPMENTS LTD.
EROSION & SEDIMENTATION PLAN
STAGE 2 (PRE-GRADE)

SCALE: 1:1000	CHECKED BY: A.A.	PROJECT NO. 10376
DESIGNED BY: U.A.	DRAWN BY: U.A./R.P.	DRAWING NO. ESC02
CHECKED BY: D.M.	DATE: AUGUST 2024	SHEET NO. 02



* GEOTEXTILE TO BE 270R TERRAFIX OR APPROVED EQUIVALENT. GEOTEXTILE USED SHOULD NOT HAVE A PLASTIC MESH LAYER.




THE SILTATION CONTROL PLAN IS INTENDED TO ASSIST THE CONTRACTOR IN THE LAYOUT AND CONSTRUCTION OF THE SILTATION CONTROL FEATURES ONLY. THIS DRAWING SHALL NOT BE USED FOR CONSTRUCTION OF SITE SERVICES

ALL CONTROL WORKS SHALL BE IN PLACE PRIOR TO THE START OF STRIPPING OPERATIONS

NO IN-WATER WORKS ALLOWED BETWEEN APRIL 1ST TO JUNE 30TH, UNLESS AUTHORIZED BY DFO, MNR AND CH.

SILT / ENVIRONMENTAL CONTROL MEASURES TO BE INSPECTED AS REQUIRED, BY THE PROJECT ENVIRONMENTAL CONSULTANT DURING ALL PHASES OF CONSTRUCTION.



1	FIRST SUBMISSION	AUGUST 2024	U.A.	A.A.
No.	REVISIONS	Date	By	Approved
BENCHMARK: SET CUT CROSS 0.35m FROM SOUTH FACE OF CONCRETE HEAD WALL ALONG EAST SIDE OF ENTRANCE ROAD, 200m NORTH OF MAYFIELD ROAD, ELEVATION 265.29m				
ELEVATION: ELEVATIONS SHOWN ON THIS PLAN ARE RELATED TO GEODETIC DATUM AND ARE DERIVED FROM THE CITY OF BRAMPTON HORIZONTAL CONTROL MONUMENT: No. 042200357 AT ELEVATION=260.691m				
		Designed By: _____ TOWN FILE No: _____		
12100 CREDITVIEW DEVELOPMENTS LTD.				
EROSION & SEDIMENTATION PLAN DETAILS				
SCALE:	AS SHOWN	CHECKED BY:	A.A.	PROJECT NO. 10376
DESIGNED BY:	U.A.	DRAWN BY:	U.A./R.P.	DRAWING NO. ESC03
CHECKED BY:	D.M.	DATE:	AUGUST 2024	SHEET NO. 03